

Floodlights Faerber Italy.



Repair Management Nederland B.V.

More management less firefighting

Floodlight Faerber Tiger 230/250V 50Hz

Polyester coated aluminium RAL 9006 IP66
 Safety glass with silicone seal. Polyamide PG 13,5 gland
 Available with symetric and a-symetric reflector (40°)

Number	Description	Reflector
892000	1 x E40 voor halogeenbuis	Symetric
892001	1 x E40 150W Son-T / RNP-T	Symetric
892002	1 x E40 250W Son-T / RNP-T	Symetric
892003	1 x E40 400W Son-T / RNP-T	Symetric
892004	1 x E40 250W HPI-T / HRI-T	Symetric
892005	1 x E40 400W HPI-T / HRI-T	Symetric
892020	1 x E40 voor halogeenbuis	A-Symetric
892021	1 x E40 150W Son-T / RNP-T	A-Symetric
892022	1 x E40 250W Son-T / RNP-T	A-Symetric
892023	1 x E40 400W Son-T / RNP-T	A-Symetric
892024	1 x E40 250W HPI-T / HRI-T	A-Symetric
892025	1 x E40 400W HPI-T / HRI-T	A-Symetric



Floodlights Faerber Mini Tiger 70 Watt 230/250V 50Hz

Polyester Coated aluminium RAL 9006 IP66
 Safety glass with silicone seal. Polyamide PG 13,5 gland
 Available with symetric and a-symetric reflector (10°)

Number	Description	Reflector
892040	1 x Rx7S 70W MHN-TD / HRI-TS	Symetric
892041	1 x Rx7S 70W MHN-TD / HRI-TS	A-Symetric



Floodlights Faerber Mini Tiger 150 Watt 230/250V 50Hz

Polyester Coated aluminium RAL 9006 IP66
 Safety glass with silicone seal. Polyamide PG 13,5 gland
 Available with symetric and a-symetric reflector (30°)

Number	Description	Reflector
892045	1 x Rx7S 150W MHN-TD / HRI-TS	Symetric
892046	1 x Rx7S 150W MHN-TD / HRI-TS	A-Symetric



Heavy Dusty industrial fixture made by GC Illumination type PA-60 IP-65.

NON-CORROSIVE casted aluminium case with a black epoxy.

Very usefull voor heavy dute areas like seaports (salty air)

Tempered glass 5 mm thick

A-Symetric reflector with a 65 ° lightbeam

Hammersign mirror for a wide beam or glossy mirror for a narrow beam.

Type PA-60/B mounting bracket on top of the fixture.

Type PA-60/Z side mounting bracket

VSA boxes for in or mounted against the mast.



Number	Description	Reflector
893000	PA-60/B 600W-E40 Including ignitor, excluding VSA Dimension 650x410x203 mm LxBxH	A-Symetric
893001	PA-60/Z 600W-E40 Including ignitor, excluding VSA Dimension 650x410x203 mm LxBxH	A-Symetric
893010	PA-60/B 1000W-E40 Including ignitor, excluding VSA Dimension 650x410x203 mm LxBxH	A-Symetric
893011	PA-60/Z 1000W-E40 Including ignitor, excluding VSA Dimension 650x410x203 mm LxBxH	A-Symetric
893020	VSA-Box Alu 600W NAV compensated	
893021	VSA-Box Alu 1000W HQI/NAV compensated	
893030	Build in unit 600W IP-65 compensated Dimension 450x115x90 mm LxBxH	
893030	Build in unit 1000W IP-65 compensated Dimension 450x115x90 mm LxBxH	
893040	Mast bracket PA60 180 ° for PT102 mm	
893041	L-profile for mast bracket PA60	

