



rmn

Repair Management Nederland B.V.
More management less firefighting

Welding blankets for protection with welding and cutting work.

Solid fabric wire, asbestos free, on one side with alufix laminated.

Weight 660 gram/m², 0,7 mm thickness very strong.

Roll width 1,00 meter and roll length 50 meter.

Continuous temperature till 550 degrees C and a peak of 600 degrees C.

Melting point 840 degrees C.

Number	Description
6016000	Per m ² cut of the roll
6016001	1 x 1 meter seamed
6016002	1 x 2 meter seamed
6016003	2 x 2 meter seamed
6016004	3 x 3 meter seamed



Weight 1050 gram/m², 1,6 mm thickness very strong.

Roll width 1,00 meter and roll length 50 meter.

Continuous temperature till 750 degrees C and a peak of 850 degrees C.

Melting point 940 degrees C.

Number	Description
6016040	Per m ² cut of the roll
6016041	1 x 1 meter seamed
6016042	1 x 2 meter seamed
6016043	2 x 2 meter seamed
6016044	2 x 3 meter seamed



High temperature welding blankets

Weight 1000 gram/m², 1,6 mm thickness very strong.

Continuous temperature till 900 degrees C and a peak of 1150 degrees C.

Melting point 1350 degrees C.

Number	Description
6016005	Per m ² cut of the roll
6016027	1 x 1 meter seamed
6016006	1 x 2 meter seamed
6016007	2 x 2 meter seamed
6016028	2 x 3 meter seamed



High temperature welding blankets, roll width 0,9 meter.

Weight 1150 gram/m², 1,4 mm thickness very strong.

Continuous temperature 1150 degrees C and a peak of 1300 degrees C.

Melting point 1600 degrees C.

Number	Description
6016019	Per meter lenght cut from roll
6016020	0,9 x 2 meter seamed
6016021	1,8 x 2 meter seamed
6016029	1,8 x 3 meter seamed



[Top](#)

Pag. 60/16