

## Pneumatic Hand tools



### Bahco pneumatic Impact wrench BPC816

**3/8" square drive**, lightweight impact wrench with twin hammer mechanism. Light, durable and insulated composite housing. 1/4" female air connection. Powerful twin hammer mechanism. Easy one-hand forward and reverse change. Three-step power regulator. 360° swivel connection to avoid hose coiling. Progressive trigger mechanism. Built-in silencer. 6.3 Bar, 10mm hose, 113L/min, 34-338Nm - max 583Nm. 12.000rpm, 1.500 impact/min, 87dBA, vibration 7,4mm/s<sup>2</sup>.



### Bahco pneumatic Impact wrench BPC815

**1/2" square drive**, composite impact wrench with twin hammer mechanism. Light, durable and insulated composite housing. 1/4" female air connection. Powerful twin hammer mechanism. Easy one-hand forward and reverse change. Three-step power regulator. 360° swivel connection to avoid hose coiling. Progressive trigger mechanism. Built-in silencer. 6.3 Bar, 10mm hose, 113L/min, 786Nm - max 1112Nm, 8.000rpm, 1.250 impact/min, 88dBA, vibration 7,7mm/s<sup>2</sup>.



### Bahco pneumatic Impact wrench BPC817

**3/4" square drive**, composite impact wrench with twin hammer mechanism. Light, durable and insulated composite housing. 3/8" female air connection. Powerful twin hammer mechanism. Easy one-hand forward and reverse change. Three-step power regulator. 360° swivel connection to avoid hose coiling. Progressive trigger mechanism. Built-in silencer. 6.2 Bar, 10mm hose, 198L/min, 1627Nm - max 2034Nm, 5.000rpm, 916 impact/min, 96dBA, vibration 11,6mm/s<sup>2</sup>.



### Bahco pneumatic Impact wrench BP901

**1" square drive**, extremely strong machine, 2250Nm in forward and 3.500 in reverse. 1/2" female air connection. Low noise and low vibration. Durable rocking dog mechanism. Three-step power regulator. Comfortable support handle included. 6.2 Bar, 13mm hose, 460L/min, 2550Nm - max 3500Nm, 3.800rpm, 400 impact/min, 87.5dBA, vibration 6.17mm/s<sup>2</sup>.



### Bahco pneumatic Impact wrench BP901L

**1" square drive**, extremely strong machine, 2250Nm in forward and 3.500 in reverse. 1/2" female air connection. 9" anvil to reach every nut. Low noise and low vibration. Durable rocking dog mechanism. Three-step power regulator. Comfortable support handle included. 6.2 Bar, 13mm hose, 460L/min, 2550Nm - max 3500Nm, 3.800rpm, 400 impact/min, 87.5dBA, vibration 6.17mm/s<sup>2</sup>.

| Article No. | Description                                     | IMPA     |
|-------------|---|----------|
| 30BPC816    | Impact wrench Bahco BPC816 3/8"                 | -        |
| 30BPC815    | Impact wrench Bahco BPC815 1/2"                 | 59 01 01 |
| 30BPC817    | Impact wrench Bahco BPC817 3/4"                 | 59 01 05 |
| 30BP901     | Impact wrench Bahco BP901 1"                    | 59 01 06 |
| 30BP901L    | Impact wrench Bahco BP901L 1"with 9" long anvil | 59 01 06 |



### Bahco pneumatic ratchet wrench BP820

**3/8" square drive**, with rubber grip, power regulator. Swivel connection. Swivel air exhaust. 1/4" female air connection. 6.3 Bar, 10mm hose, 120L/min, 0-31Nm, 270rpm, 80dBA, vibration 2,6mm/s<sup>2</sup>.

| Article No. | Description                     | IMPA |
|-------------|---------------------------------|------|
| 30BP820     | Ratchet wrench Bahco BP820 3/8" | -    |
| 30BP821     | Ratchet wrench Bahco BP821 1/2" | -    |



### Bahco pneumatic ratchet wrench BP821

**1/2" square drive**, rigid housing covered with rubber grip, easy adjustable power regulator in the handle. Easy direction change switch, 360° swivel connection to avoid hose coiling. Progressive lever mechanism, built-in silencer. 1/4" female air connection. 6.3 Bar, 10mm hose, 120L/min, 0-67Nm, 150rpm, 80dBA, vibration 2,6mm/s<sup>2</sup>.

### Bahco pneumatic die grinder BP822

**Including 3mm collet**, rigid housing with insulated rubber grip, easy accessible air regulator at end of the handle. 360° swivel connection to avoid hose coiling, progressive lever mechanism with safety trigger. 1/4" female air connection. 6.3 Bar, 10mm hose, 170L/min, 25.000rpm, 85dBA, vibration 2,5mm/s<sup>2</sup>, 250W.



### Bahco pneumatic die grinder BP822E

**Including 3mm collet**, rigid housing with insulated rubber grip, easy accessible air regulator at end of the handle. 360° swivel connection to avoid hose coiling, progressive lever mechanism with safety trigger. 1/4" female air connection. 6.3 Bar, 10mm hose, 113L/min, 25.000rpm, 76dBA, vibration 4,53mm/s<sup>2</sup>, 200W.



| Article No. | Description                             | IMPA |
|-------------|---|------|
| 30BP822     | Die grinder Bahco BP822 with 3mm collet | -    |
| 30BP822E    | Die grinder Bahco BP821 with 3mm collet | -    |

### Bahco pneumatic angle grinder BP823

**Diameter 5" - 125mm**, for cutting and trimming. For grinding and cutting off. Light, durable and insulated composite housing. Toolless disc change mechanism. Progressive lever mechanism with safety trigger. Comfortable rubber covered support handle included. Adjustable protective steel shield. 1/4" female air connection. 6.3 Bar, 10mm hose, 340L/min, 10.000rpm, 83dBA, vibration 6.07mm/s<sup>2</sup>, 650W.



| Article No. | Description                          | IMPA     |
|-------------|--------------------------------------|----------|
| 30BP823     | Angle grinder Bahco BP823 125mm - 5" | 59 03 50 |



## Bahco pneumatic reversible drill BP825

**13mm keyless chuck**, Light, durable composite housing with rubber covered handle. Easy one-hand forward and reverse change. 360° swivel connection to avoid hose coiling. Progressive trigger mechanism. 1/4" female air connection. Comfortable rubber covered support handle included.

6.3 Bar, 10mm hose, 105L/min, 450rpm, 88dBA, vibration <2.5mm/s<sup>2</sup>, 220W.

## Bahco pneumatic reversible drill BPC825

**13mm keyless chuck**, Typical applications include general-purpose drilling, engine work and auto body repair. Excellent for drilling, honing, reaming and hole sawing. High quality Jacobs® 13 mm keyless chuck for extended life. Progressive trigger for better control. Removable 360-degree side handle. One-hand forward/reverse change. Flat back for better pushing action. Composite housing. 1/4" female air connection.

6.3 Bar, 10mm hose, 800rpm, 88.4-99.4dBA, vibration <1.2mm/s<sup>2</sup>.

## Bahco pneumatic reversible drill BPC823

**10mm keyless chuck**, Typical applications include general-purpose drilling, engine work and auto body repair. Excellent for drilling, honing, reaming and hole sawing. High quality Jacobs® 13 mm keyless chuck for extended life. Progressive trigger for better control. Removable 360-degree side handle. One-hand forward/reverse change. Flat back for better pushing action. Composite housing. 1/4" female air connection.

6.3 Bar, 10mm hose, 2000rpm, 88.7-99.7dBA, vibration 2.1mm/s<sup>2</sup>.

| Article No. | Description                                      | IMPA     |
|-------------|--|----------|
| 30BP825     | Reversible drill Bahco BP825 13mm keyless chuck  | 59 03 47 |
| 30BPC825    | Reversible drill Bahco BPC825 13mm keyless chuck | 59 03 47 |
| 30BPC823    | Reversible drill Bahco BPC823 10mm keyless chuck | 59 03 46 |

## Bahco pneumatic compact reciprocating saw BP828

An ideal tool for general auto body repair and modification, such as cutting exhaust pipes, corroded bolts and chassis beams. 10,000 strokes per minute. Lightweight and compact, low vibration. Progressive safety throttle lever with lockout feature. One blade included, 32 TPI. Comfortable non-slip grip. 1/4" female air connection.

6.3 Bar, 10mm hose, 62L/min, 10.000 stroke/min, 88-100.5dBA, vibration 5.18mm/s<sup>2</sup>, 300W.

## Bahco pneumatic reciprocating saw BP824

Reciprocating saw for cutting straight, curved and flush. 35 mm adjustable saw blade guide. Insulated composite housing. Progressive lever mechanism with safety trigger. 360° swivel connection to avoid hose coiling. Includes three precision ground bi-metal car body blades. 1/4" female air connection.

6.3 Bar, 10mm hose, 160L/min, 10.000 stroke/min, 85dBA, vibration 3.7mm/s<sup>2</sup>, 260W.

## Bahco pneumatic geared reciprocating saw BPG824

Perfect for all industrial cutting applications or general auto body modifications such as cutting exhaust pipes, corroded bolts, chassis beams, etc. 7,400 blows per minute with regulator. Gear-driven mechanism to reduce stalling and avoid blade jamming. Gear-driven mechanism provides more than twice the cutting capacity of standard air saws. Versatile toolholder for numerous saw blades and files. Progressive safety throttle lever with lockout feature. One blade included, 32 TPI. Composite housing. 1/4" female air connection.

6.3 Bar, 10mm hose, 113L/min, 7.400 stroke/min, 88.5-99.5dBA, vibration 18.3mm/s<sup>2</sup>, 450W.

| Article No. | Description                    | IMPA     |
|-------------|--------------------------------|----------|
| 30BP828     | Reciprocating saw Bahco BP828  | 59 05 71 |
| 30BP824     | Reciprocating saw Bahco BP824  | 59 05 71 |
| 30BPG824    | Reciprocating saw Bahco BPG824 | 59 05 71 |

## Bahco pneumatic hammer BP910

Typical applications include removing ball joints, tie rods and bearings, shearing metal parts, breaking bolts and rivets, breaking concrete, etc. 3200 blows per minute for fast cutting action. High performance and low weight (2.25 kg).

High quality 10.2 mm round safety-lock retainer for quick chisel change. Comfortable rubber grip. 1/4" female air connection.

6.3 Bar, 10mm hose, 55.5L/min, 3.200 stroke/min and 67mm stroke, 94.3-106.6dBA, vibration 2.4mm/s<sup>2</sup>, 10.2mm tool shank.

| Article No. | Description                                      | IMPA     |
|-------------|--|----------|
| 30BP910     | Hammer Bahco BP910                               | 59 05 52 |
| 30BP909TE   | Rotating edging chisel Bahco BP909TE (1)         | 59 05 59 |
| 30BP909NE   | Non Rotating edging chisel Bahco BP909NE (2)     | 59 05 59 |
| 30BP909TF   | Rotating flat chisel Bahco BP909TF (3)           | 59 05 55 |
| 30BP909TWF  | Rotating flat wide chisel Bahco BP909TWF (4)     | 59 05 58 |
| 30BP909TTP  | Rotating tapered punch chisel Bahco BP909TTP (5) | 59 05 56 |



(2)



(3)



(4)



(5)



(1)