

Creusen



rmn

Repair Management Nederland B.V.

More management less firefighting

Number	Description
--------	-------------

54CR1030	TB 816 230V 50/60Hz 1Ph Mk2/16 550W 12 speed 180-2740 Tpm Max. drilling depth 80 mm Throad 195 mm Total height 1065 mm Height drill chuck - table 335 mm Table 300x300 mm Max. capacity 14 mm
-----------------	---



54CR1031	TB 820 230V 50/60Hz 1Ph Mk3/20 750W 16 speed 160-3000 Tpm Max. drilling depth 80 mm Throad 215 mm Total height 1085/1640 mm Heigth drill chuck - table 305 mm Table 335x335 mm Max. capacity 16 mm
-----------------	--



54CR1032	TB 820 400V 50/60Hz 1Ph Mk3/20 750W 16 speed 160-3000 Tpm Max. drilling depth 80 mm Throad 215 mm Total height 1085/1640 mm Heigth drill chuck - table 305 mm Table 335x335 mm Max. capacity 16 mm
-----------------	--



All machines with cooling table, table with a T groove M14, 360° adjustable.
Drill chuck protection on all machines for extra safety.
Safety switch with emergency brake. Microswitch in top cover for safety.
Double V belt driven machine with aluminium belt disc for lower sound.
Chuck taper with morse cone, right turning.
Tool table adjustable in height.

54CR1033 KB 832

400V 50/60Hz 3Ph
Mk3/28
1100W
12 speed
190-2000 Tpm
Max. drilling depth 120 mm
Throat 260 mm
Total height 1700 mm
Height drill chuck - table 615 mm
Table 475x425 mm
Max. capacity 28 mm



54CR1035 Tool clamp 100mm

for TB 816 en TB 820

54CR1036 Tool clamp 150mm

for KB 832

