

High-pressure cleaners
Cold water high-pressure cleaners
Hot water high-pressure cleaners
Karcher
Eurom



Repair Management Nederland B.V.
 More management less firefighting

Cold water High-pressure cleaners

Number	Description
--------	-------------

547627	HD 5/11 P
--------	-----------

Current type: 230V **50Hz**
 Flow rate: 490 L/h
 Operating pressure: 11 Mpa / 110 bar
 Max. pressure: 16 Mpa 160 bar
 Power rating kW: 2.2
 Weight kg: 20,5
 Dimensions LxWxH: 351x312x904 mm

Compact cold water high-pressure cleaner.
 Complete with 10 meter HP hose, spray lance 840mm,
 trigger gun EASY!Force, autostop. Cable 5m.

547628	HD 5/11 Plus
--------	--------------

Current type: 230V **50Hz**
 Flow rate: 490 L/h
 Operating pressure: 11 Mpa / 110 bar
 Max. pressure: 16 Mpa /160 bar
 Power rating kW: 2.2
 Weight kg: 20,5
 Dimensions LxWxH: 351x312x904 mm

Compact cold water high-pressure cleaner.
 Complete with 10 meter HP hose, spray lance 840mm,
 dirt blaster nozzle, trigger gun EASY!Force, autostop. Cable 5m.

547629	HD 6/13 C KAP
--------	---------------

Current type: 230V **60Hz**
 Flow rate: 590 L/h
 Operating pressure: 13 Mpa / 130 bar
 Max. pressure: 19 Mpa /190 bar
 Power rating kW: 2.9
 Weight kg: 25,2
 Dimensions LxWxH: 380x360x930 mm

Compact cold water high-pressure cleaner.
 Complete with 10 meter HP hose, spray lance 840mm,
 trigger gun EASY Press, Handgun with softgrip,
 Anti-twist system, autostop, tripple nozzle
 (0° / 25° / 40°),manual. Cable 5m.

547629A	HD 6/13 C KAP
---------	---------------

Current type: 230V **50Hz**
 Flow rate: 590 L/h
 Operating pressure: 13 Mpa / 130 bar
 Max. pressure: 19 Mpa /190 bar
 Power rating kW: 2.9
 Weight kg: 25,2
 Dimensions LxWxH: 380x360x930 mm

Compact cold water high-pressure cleaner.
 Complete with 10 meter HP hose, spray lance 840mm,
 trigger gun EASY Press, Handgun with softgrip,
 Anti-twist system, autostop, tripple nozzle
 (0° / 25° / 40°),manual. Cable 5m.



547630 HD 5/12 C

Current type: 230V **50Hz**
 Flow rate: 500 L/h
 Operating pressure: 12 Mpa / 120 bar
 Max. pressure: 17.5 Mpa / 175 bar
 Power rating kW: 2.5
 Weight kg: 23,7
 Dimensions LxWxH: 380x360x930 mm

Compacte koudwater reiniger
 Compleet met 10 meter slang, lans 840mm,
 Spuitpistool EASY!Force, autostop.
 (0° / 25° / 40°), handmatig. Kabel 5m.

547631 HD 5/12 CX PLUS

Current type: 230V **50Hz**
 Flow rate: 500 L/h
 Operating pressure: 12 Mpa / 120 bar
 Max. pressure: 17.5 Mpa / 175 bar
 Power rating kW: 2.5
 Weight kg: 26
 Dimensions LxWxH: 380x360x930 mm

Compact cold water high-pressure cleaner.
 Complete with 15 meter HP hose, spray lance 840mm,
 Trigger EASY!Force, autostop, dirt blaster nozzle.
 tripple nozzle (0° / 25° / 40°), manual. Cable 5m.
 With hose reel for HP hose.

547634 HD 7/18 C

Stroomsoort: 230V **50Hz**
 Wateropbrengst: 200-700 L/h
 Werkdruk: 2-17.5 Mpa / 20-175 bar
 Max. druk: 21.5 Mpa / 215 bar
 Vermogen Kw: 4.7
 Gewicht kilo: 24
 Afmeting LxBxH mm: 360x375x925 mm

Compact cold water high-pressure cleaner.
 Compleet met 10 meter slang, lans 840mm,
 Trigger EASY!Force, autostop. Triple nozzle
 (0° / 25° / 40°), manual. Kabel 5m.
 Servo-Control.

547635 HD 7/18 CX PLUS

Current type: 230V **50Hz**
 Flow rate: 200-700 L/h
 Operating pressure: 2-17.5 Mpa / 20-175 bar
 Max. pressure: 21.5 Mpa / 215 bar
 Power rating kW: 4.7
 Weight kg: 24
 Dimensions LxWxH: 360x375x925 mm

Compact cold water high-pressure cleaner.
 Complete with 15 meter HP hose, spray lance 840mm,
 Trigger EASY!Force, autostop, dirt blaster nozzle.
 Trippel nozzle (0° / 25° / 40°), manual.
 Cable 5 meter. With hose reel for HP hose.
 Servo-Control.



Many high pressure cleaners also available in 60Hz frequency.

547638 HD 9/20-4 M

Current type: 3Ph 440V **50Hz**
 Flow rate: 460-900 L/h
 Operating pressure: 4-20 Mpa / 40-200 bar
 Max. pressure: 22 Mpa / 220 bar
 Power rating kW: 7.0
 Weight kg: 48
 Dimensions LxWxH: 467x407x1010mm

Middle class cold water high-pressure cleaner.
 Complete with 10 meter HP hose, spray lance 1050mm,
 Trigger EASY!Force, autostop.
 Tripple nozzle (0° / 25° / 40°), manual.
 Cable 5 meter. Servo-Control. Switch Chem.

547639 HD 9/20-4 MX PLUS

Current type: 3Ph 440V **50Hz**
 Flow rate: 460-900 L/h
 Operating pressure: 4-20 Mpa / 40-200 bar
 Max. pressure: 22 Mpa / 220 bar
 Power rating kW: 7.0
 Weight kg: 48
 Dimensions LxWxH: 467x407x1010 mm

Middle class cold water high-pressure cleaner.
 Complete with 10 meter HP hose, spray lance 1050mm,
 Trigger EASY!Force, autostop. Dirt blaster nozzle.
 Tripple nozzle (0° / 25° / 40°), manual.
 Cable 5 meter. Servo-Control. Switch Chem.
 Servo-Control. Switch Chem. Hose reel for HP hose.

547650 HD 7/18-4 M

Current type: 3Ph 440V **50Hz**
 Flow rate: 240-700 L/h
 Operating pressure: 3-18 Mpa / 30-180 bar
 Max. pressure: 21.5 Mpa / 215 bar
 Power rating kW: 5.0
 Weight kg: 49
 Dimensions LxWxH: 467x407x1010 mm

Middenklasse koudwater reiniger
 Complete with 10 meter HP hose, spray lance 1050mm,
 Tripple nozzle (0° / 25° / 40°), manual.
 Cable 5 meter. Servo-Control. Switch Chem.
 Servo-Control. Switch Chem.

547651 HD 7/18-4 MX PLUS

Current type: 3Ph 440V **50Hz**
 Flow rate: 240-700 L/h
 Operating pressure: 3-18 Mpa / 30-180 bar
 Max. pressure: 21.5 Mpa / 215 bar
 Power rating kW: 5.0
 Weight kg: 49
 Dimensions LxWxH: 467x407x1010 mm

Middle class cold water high-pressure cleaner.
 Complete with 15 meter HP hose, spray lance 1050mm,
 Trigger EASY!Force, autostop. Dirt blaster nozzle.
 Tripple nozzle (0° / 25° / 40°), manual.
 Cable 5 meter. Servo-Control. Switch Chem.
 Servo-Control. Switch Chem.
 Hose reel for HP hose.



Many high pressure cleaners also available in 60Hz frequency.

547677 HD 10/25-4 S

Current type: 3Ph 440V **60Hz**
 Flow rate: 500-1000 L/h
 Operating pressure: 3-25 Mpa / 30-250 bar
 Max. pressure: 27.5 Mpa / 275 bar
 Power rating kW: 9.2
 Weight kg: 62
 Dimensions LxWxH: 560x500x1090 mm

Super Class high-pressure cold water cleaner.
 Oil sight glass. Power nozzle.
 Servo Control, autostop, dirt blaster lance,
 brass water inlet fitting, 4-pole three-phase
 motor with air and water cooling.
 Integrated fine mesh water filter.
 Trigger, EASY!Force Advanced.
 Trigger gun with soft grip. Power nozzle.
 Electronic motor protection system with
 LED display. Spray lance 1050mm,
 High-pressure hose 10 meter.

**547677A HD 10/25-4 S**

Current type: 3Ph 440V **50Hz**
 Flow rate: 500-1000 L/h
 Operating pressure: 3-25 Mpa / 3-250 bar
 Max. pressure: 27.5 Mpa / 275 bar
 Power rating kW: 9.2
 Weight kg: 62
 Dimensions LxWxH: 560x500x1090 mm

Super Class high-pressure cold water cleaner.
 Oil sight glass. Power nozzle.
 Servo Control, autostop, dirt blaster lance,
 brass water inlet fitting, 4-pole three-phase
 motor with air and water cooling.
 Integrated fine mesh water filter.
 Trigger, EASY!Force Advanced.
 Trigger gun with soft grip. Power nozzle.
 Electronic motor protection system with
 LED display. Spray lance 1050mm,
 High-pressure hose 10 meter.

**547675 HD 10/25-4 SX PLUS**

Current type: 3Ph 440V **50Hz**
 Flow rate: 500-1000 L/h
 Operating pressure: 3-25 Mpa / 3-250 bar
 Max. pressure: 27.5 Mpa / 275 bar
 Power rating kW: 9.2
 Weight kg: 62
 Dimensions LxWxH: 560x500x1090 mm

Super Class high-pressure cold water cleaner.
 Oil sight glass. Power nozzle.
 Servo Control, autostop, dirt blaster lance,
 brass water inlet fitting, 4-pole three-phase
 motor with air and water cooling.
 Integrated fine mesh water filter.
 Trigger, EASY!Force Advanced.
 Trigger gun with soft grip. Power nozzle.
 Electronic motor protection system with
 LED display. Spray lance 1050mm,
 High-pressure hose 20 meter.
 Hose reel for HP hose.



547670 HD 17/14-4 S PLUS

Current type: 3Ph 440V **50Hz**
 Flow rate: 650-1700 L/h
 Operating pressure: 3-14 Mpa / 30-140 bar
 Max. pressure: 15.4 Mpa / 154 bar
 Power rating kW: 9.4
 Weight kg: 63
 Dimensions LxWxH: 560x500x1090 mm

Super Class high-pressure cold water cleaner.
 Oil sight glass. Power nozzle.
 Servo Control, autostop, dirt blaster lance,
 brass water inlet fitting, 4-pole three-phase
 motor with air and water cooling.
 Integrated fine mesh water filter.
 Trigger, EASY!Force Advanced.
 Trigger gun with soft grip. Power nozzle.
 Electronic motor protection system with
 LED display. Spray lance 1050mm,
 High-pressure hose 10 meter.

**547671 HD 17/14-4 SX PLUS**

Current type: 3Ph 440V **50Hz**
 Flow rate: 650-1700 L/h
 Operating pressure: 3-14 Mpa / 30-140 bar
 Max. pressure: 15.4 Mpa / 154 bar
 Power rating kW: 9.4
 Weight kg: 63
 Dimensions LxWxH: 560x500x1090 mm

Super Class high-pressure cold water cleaner.
 Oil sight glass. Power nozzle.
 Servo Control, autostop, dirt blaster lance,
 brass water inlet fitting, 4-pole three-phase
 motor with air and water cooling.
 Integrated fine mesh water filter.
 Trigger, EASY!Force Advanced.
 Trigger gun with soft grip. Power nozzle.
 Electronic motor protection system with
 LED display. Spray lance 1050mm,
 High-pressure hose 15 meter.
 Hose reel for HP hose.

**547681 HD 715**

Current type: 3Ph 440V **50Hz**
 Flow rate: 250-700 L/h
 Operating pressure: 1-15 Mpa / 10-150 bar
 Max. pressure: 17.5 Mpa / 175 bar
 Power rating kW: 4.7
 Weight kg: 24
 Dimensions LxWxH: 500x310x350 mm

Robust portable cold water high-pressure cleaner.
 Heavy duty frame of steel powder coated tubes.
 Integrated handle and crane lifting eye.
 Softgrip carry handle for increased safety.
 Trigger EASY! Force.
 High pressure hose 15 m.
 Spray lance 840 mm.
 Tripple nozzle (0° / 25° / 40°), manual.
 Autostop.
 High pressure lance.



547691 HD 10/25-4 Cage Plus

Current type: 3Ph 440V **50Hz**
 Flow rate: Max. 1000 L/h
 Operating pressure: Max. 25 Mpa / Max. 250 bar
 Max. pressure: 27.3 Mpa / 275 bar
 Power rating kW: 9.2
 Weight kg: 57,4
 Dimensions LxWxH: 547x543x1104 mm

Robust cold water high-pressure cleaner for heavy duty use.
 Heavy duty frame of steel powder coated tubes.
 Crane lifting eyes for easy transport.
 Ergonomic handle and hose rack.
 Fine mesh filter protects the motor against dirt particles.
 Easy to reach and easy to clean.
 Trigger, EASY!Force Advanced.
 High pressure hose 10 m.
 Spray lance 1050 mm.
 Power nozzle.
 Dirt blaster spray nozzle.
 Autostop.
 High pressure lance.

**Hot water high-pressure cleaners****547649 HDS 8/18-4 C**

Current type: 3Ph 440V **50Hz**
 Flow rate: 300-800 L/h
 Operating pressure: 3-18 Mpa / 30-180 bar
 Temperature °C: 80-155
 Power rating Kw: 6
 Consumption fuel oil (kg/u) 5
 Power cable (m) 5
 Fuel tank (l) 15
 Weight kilo: 108
 Dimensions LxWxH: 1060x650x920 mm

State-of-the-art 3 phase hot water high-pressure cleaner with unique 4-pole ECO!efficiency mode that reduces diesel consumption by 20% without compromising daily cleaning performance. Central one-button operation.
 Machine protector system that prolongs component life and protects burner coil for a long time.
 Large tank opening with filling chute for detergents.
 Soft-Damping-System (SDS) compensates vibrations and pressure peaks in the high-pressure system.
 Trigger, EASY!Force Advanced.
 High pressure hose 10 m.
 Spray lance 1050 mm.
 Power nozzle. Soft damping system SDS
 Autostop.
 Integrated fuel and detergent tank.

**547649B HDS 8/18-4 CX**

Equal to HDS 8/18-4 C but as extra an integrated hose reel for the high-pressure hose.
 High pressure hose 15 m.
 Weight kilo: 110,8
 Dimensions LxBxH mm: 1215x650x920 mm



547644 HDS 7/16 C

Current type: 3Ph 440V **50Hz**
 Flow rate: 270-660 L/h
 Operating pressure: 3-16 Mpa / 30-160 bar
 Temperature °C: Max. 80
 Power rating Kw: 4,7
 Consumption fuel oil (kg/u) 5
 Power cable (m) 5
 Fuel tank (l) 15
 Weight kilo: 100
 Dimensions LxWxH: 1060x650x920 mm

State-of-the-art 3 phase hot water high-pressure cleaner with unique 4-pole ECO!efficiency mode that reduces diesel consumption by 20% without compromising daily cleaning performance. Central one-button operation. Machine protector system that prolongs component life and protects burner coil for a long time. Large tank opening with filling chute for detergents. Soft-Demping-System (SDS) compensates vibrations and pressure peaks in the high-pressure system. Trigger, EASY!Force Advanced. High pressure hose 10 m. Autostop. Spray lance 1050 mm. Power nozzle. Soft demping sytem SDS Integrated fuel and detergent tank.

**547645 HDS 7/16 CX**

Equal to HDS 7/16 C but as extra an integrated hose reel for the high-pressure hose.
 High pressure hose 15 m.
 Weight kilo: 102,8
 Dimensions LxWxH mm: 1215x650x920 mm

**547694 HDS 6/14 C**

Current type: 1Ph 230V **50Hz**
 Flow rate: 240-560 L/h
 Operating pressure: 3-14 Mpa / 30-140 bar
 Temperature °C: 80-155
 Power rating Kw: 3,6
 Consumption fuel oil (kg/u) 5
 Power cable (m) 5
 Fuel tank (l) 15
 Weight kilo: 100,5
 Dimensions LxWxH: 1060x650x920 mm

State-of-the-art 3 phase hot water high-pressure cleaner with unique 4-pole ECO!efficiency mode that reduces diesel consumption by 20% without compromising daily cleaning performance. Central one-button operation. Machine protector system that prolongs component life and protects burner coil for a long time. Large tank opening with filling chute for detergents. Soft-Demping-System (SDS) compensates vibrations and pressure peaks in the high-pressure system. Trigger, EASY!Force Advanced. High pressure hose 10 m. Autostop. Spray lance 1050 mm. Power nozzle. Soft demping sytem SDS Integrated fuel and detergent tank.

**547695 HDS 6/14 CX**

Equal to HDS 6/14 C but as extra an integrated hose reel for the high-pressure hose.
 High pressure hose 15 m.
 Weight kilo: 102,2
 Dimensions LxWxH mm: 1215x650x920 mm



547686 HDS 5/12 C

Current type:	1Ph 230V 50Hz
Flow rate:	500 L/h
Operating pressure:	12 Mpa / 120 bar
Temperature °C	80
Power rating Kw:	2,9
Consumption fuel oil (kg/u)	5
Power cable (m)	5
Fuel tank (l)	15
Weight kilo:	82,7
Dimensions LxWxH:	1060x650x920 mm

Base model hot water high-pressure cleaner.
 1-phase motor of the compact class.
 Unique ECO!efficiency mode that reduces fuel consumption.
 Central one-button operation.
 Machine protector system that prolongs component life and protects burner coil for a long time.
 Soft-Damping-System (SDS) compensates vibrations and pressure peaks in the high-pressure system.
 Trigger, EASY!Force Advanced.
 High pressure hose 10 m. Spray lance 840 mm.
 Autostop.
 Integrated fuel and detergent tank.

**547697 HDS 7/12-4 MX**

Current type:	1Ph 230V 50Hz
Flow rate:	300-700 L/h
Operating pressure:	3-12 Mpa / 30-120 bar
Temperature °C	80-155
Power rating Kw:	3,4
Consumption fuel oil (kg/u)	5
Power cable (m)	5
Fuel tank (l)	25
Weight kilo:	154
Dimensions LxWxH:	1330x750x1060 mm

Hot water high-pressure cleaner of the middle-super class.
 Eco setting, service switch to adjust water hardness.
 Turbo fan, accurate dosing of detergents, highly efficient burner technology. High efficiency pump.
 1-pole slow-running electric motor.
 Integrated hose reel with 20 m high pressure hose.
 EASY!Lock quick-release locks durable and robust and five times faster than screws.
 Trigger, EASY!Force Advanced.
 High pressure hose 20 m., Spray lance 1050 mm.
 Power nozzle. Control panel with indicator lamps.
 Integrated tanks for detergent and fuel.
 Tanks can be filled from outside.
 Autostop. Elektronik control with LED-display.
 2 detergent tanks for detergent and scale inhibitor..
 Dry running protection.

**547698 HDS 8/18-4 MX**

Current type:	3Ph 400V 50Hz
Flow rate:	400-800 L/h
Operating pressure:	3-18 Mpa / 30-180 bar
Temperature °C	80-155
Power rating Kw:	5,5
Consumption fuel oil (kg/u)	5
Power cable (m)	5
Fuel tank (l)	25
Weight kilo:	154
Dimensions LxWxH:	1330x750x1060 mm

Other characteristics as HDS 7/12-4 MX



547720 HDS 13/20-4 S

Current type:	3Ph 400V 50Hz
Flow rate:	600-1300 L/h
Operating pressure:	3-20 Mpa / 30-200 bar
Temperature °C	80-155
Power rating Kw:	9,3
Consumption fuel oil (kg/u)	5
Power cable (m)	5
Fuel tank (l)	25
Weight kilo:	186
Dimensions LxWxH:	1330x750x1060 mm

Hot water high-pressure cleaner of the middle-super class.
 Eco setting, service switch to adjust water hardness.
 Turbo fan, accurate dosing of detergents, highly efficient burner technology. High efficiency pump.
 4-pole ECO!efficiency motor.
 Integrated hose reel with 20 m high pressure hose.
 EASY!Lock quick-release locks durable and robust and five times faster than screws.
 Integrated operating hours counter.
 Detergent regulation ensures low consumption.
 Easy switching between both cleaning agent tanks.
 Rinsing takes place automatically in 0 position.
 Trigger, EASY!Force Advanced.
 High pressure hose 10 m., Spray lance 1050 mm.
 Power nozzle.
 Optional two-lance operation.
 Two detergent tanks integrated.
 Control panel with indicators.
 Autostop. Elektronik control system with LED-display.
 Dry running protection
 3-phase plug (CEE)
 Soft demping (SDS)

**547680 HDS 5/11 U**

Current type:	1Ph 230V 50Hz
Flow rate:	450 L/h
Operating pressure:	11 Mpa / 110 bar
Temperature °C	Max. 80
Power rating Kw:	2,2
Consumption fuel oil (kg/u)	5
Power cable (m)	5
Fuel tank (l)	6,5
Weight kilo:	61,4
Dimensions LxWxH:	618x618x994 mm



Base model of the upright class hot water high-pressure cleaner.
 Effortless transport over landings or stairs.
 Compact design space-saving storage and transport.
 Fine-mesh water filter, efficiently protects high-pressure pump against contamination. Easy to remove from outside.
 Trigger, EASY!Force Advanced.
 High pressure hose 10 m.
 Spray lance 840 mm.
 Autostop.
 EASY!Lock quick-release locks durable and robust and five times faster than screws.
 Detergent dosing at low pressure.



Current type: 1Ph 230V **50Hz**
 Flow rate: 450 L/h
 Operating pressure: 11 Mpa / 110 bar
 Temperature °C: Max. 80
 Power rating Kw: 2,2
 Consumption fuel oil (kg/u) 5
 Power cable (m) 5
 Fuel tank (l) 6,5
 Weight kilo: 70
 Dimensions LxWxH: 620x620x1160 mm

Base model of the upright class hot water high-pressure cleaner.
 Effortless transport over landings or stairs.
 Compact design space-saving storage and transport.
 Fine-mesh water filter, efficiently protects high-pressure pump against contamination. Easy to remove from outside.
 Trigger, EASY!Force Advanced.
 High pressure hose 15 m.
 Spray lance 840 mm.
 Autostop.
 EASY!Lock quick-release locks durable and robust and five times faster than screws.
 Detergent dosing at low pressure.
 Integrated hose reel for high-pressure hose.



Several accessories available such as hoses, couplings, brushes, nozzles, triggers and detergents.



Eurom cold water high-pressure cleaners.

548255 KRD200

Current type: n.v.t.
Flow rate: 900 L/h
Operating pressure: 20 Mpa / 200 bar
Temperatur °C Supply water Max. 60
Power rating PK: 10
Motor Type: Yanmar L100N6
Type fuel: Diesel
Power cable (m) n.a.
Weight kilo: 85
Dimension LxWxH: 1130x640x850 mm
Stainless steel cover.
High pressure hose 10 m.
Without accessories.



548256 KRB200

Current type: n.v.t.
Flow rate: 900 L/h
Operating pressure: 20 Mpa / 200 bar
Temperatur °C Supply water Max. 60
Power rating PK: 10
Motor Type: Honda GX390
Type fuel: Petrol
Power cable (m) n.a.
Weight kilo: 85
Dimension LxWxH: 1130x640x850 mm
Stainless steel cover.
High pressure hose 10 m.
Without accessories.



Spray lance

Single stainless steel lance.

54EUM153262 Length 1200 mm

Max. pressure 350 bar
Water consumption 30 l/m
Max. water temperature 150°C
Connection 1/4"



Trigger

54EUM153903 HG350

Max. pressure 350 bar
Water consumption 40 l/m
Max. water temperature 150°C



54EUM3927 HG2600

Max. pressure 310 bar
Water consumption 45 l/m
Max. water temperature 150°C
Low Trigger force

Couplings

54EUM155044 3/8" female

Max. pressure 275 bar
Water consumption 40 l/m
Max. water temperature 150°C
SU screw coupling M22x1,5 (M)
Male part black



Coupling

54EUM155242	3/8" female
--------------------	--------------------

Max. pressure 275 bar
Water consumption 40 l/m
Max. water temperature 150°C
SU screw coupling M22x1,5 (M)
Female part brass

Spray nozzles

54EUM152104	Flush front SK250
--------------------	--------------------------

Pressure 100-275 bar
Capacity 10-17 l/m
Max. water temperature 100°C
Connection 1/4" v/f
Nozzle 045-1,4



54EUM152111	Flush front SK250
--------------------	--------------------------

Pressure 100-275 bar
Capacity 10-17 l/m
Max. water temperature 100°C
Connection 1/4" v/f
Nozzle 05-1,55



54EUM152128	Flush front SK250
--------------------	--------------------------

Pressure 100-275 bar
Capacity 10-17 l/m
Max. water temperature 100°C
Connection 1/4" v/f
Nozzle 055-1,6



High pressure hose

Standard type A black hose with 3/8" male connection.
Max. pressure 250 bar
Water consumption 40 l/m.
Max. water temperature 155°C.

54EUM154016	10 mtr
54EUM154023	15 mtr
54EUM154030	20 mtr
54EUM154047	25 mtr
54EUM154054	30 mtr
54EUM154061	35 mtr
54EUM154078	40 mtr
54EUM154085	50 mtr

