

Prolumia LED Linkable luminaires

Prolumia LED Pro-Linea




Prolumia LED Pro-Linea Series (IP20)

Linkable LED luminaire. The use of the LED technology guarantees low power consumption and a long lifetime. Housing made of extruded aluminium with a polycarbonate opal cover which shows a light such as a normal fluorescent tube. Separate LED's are due to this not visible which makes it perfect for architectural use in interiors. The Prolumia Pro-Linea series is easy and quick to install, using the included stainless steel mounting clips. Building height of the fixture is very small makes it useful in narrow spaces. Linkable with a connector or with an interconnector cord (25 cm) which can be ordered separately. The Pro-Linea fixture is powered on one side, where up to 20 luminaires can be linked as on linear lighting system. Connection cable, end cap and stainless steel mounting clips (2 pieces) are included. Applications are: Ideal as replacement for conventional T5 & T8 fluorescent fixtures, between racks in warehouses, as commercial lighting, in areas with an extreme low height and many other linear lighting applications.

Specifications LED Pro-Linea:

Available in 100/240V 50/60Hz AC.
Operating temperature: -20°C up to +40°C.
Rated life time: Approx. 50.000
Color rendering index: ≥80
Power factor: ≥0.93
LED driver: build in.
Light output angle: 120°
Wattages: 11W/20W/24W



Number	Length	light color	Lumen	Wattage
83PR408714	0 = 60 cm	4 = Warm white		11W
		3000K	1095 lm	
		5 = Pure white		
		4000K	1155 lm	
		6= Cool white		
		6000K	1155 lm	
				<i>Dimensions: 565 x 32mm</i>
Number	Length	light color	Lumen	Wattage
83PR408714	3 = 120 cm	4 = Warm white		20W
		3000K	1800 lm	
		5 = Pure white		
		4000K	2100 lm	
		6= Cool white		
		6000K	2100 lm	
				<i>Dimensions: 1174 x 32mm</i>
Number	Length	light color	Lumen	Wattage
83PR408714	4 = 150 cm	4 = Warm white		24W
		3000K	2390 lm	
		5 = Pure white		
		4000K	2520 lm	
		6= Cool white		
		6000K	2520 lm	
				<i>Dimensions: 1475 x 32mm</i>



Accessories included:

Connection cable 1 meter

End cap

Stainless steel mounting
clips 2 pieces



Accessories optional:

Number	Description
--------	-------------

83PR40871490	Connection cable 2 meter
--------------	--------------------------



Number	Description
--------	-------------

83PR40871492	Interconnection cord 25 cm.
--------------	-----------------------------

Number	Description
--------	-------------

83PR40871491	Connector
--------------	-----------



Number	Description
--------	-------------

83PR40871493	Switch
--------------	--------



LED PRO-LINEA SERIE

Elegante lijnverlichting

KOPPELEN.

CREËER EGAL E LICHTLIJNEN ZONDER ONDERBREKINGEN