

The Miko Anchor Magnets form a series of powerful and robust underwater fixing points. With holding forces ranging from 90 kg to 2 000 kg, these magnets are used worldwide for a wide range of applications.

The magnetic component consists of neodymium which is coated with epoxy to improve its corrosion resistance in sea water.

MAM-005 has a holding force of 1 000 kg* and can be used for heavy duty applications such as fastening oil booms, fenders or temporary mooring to ship sides and other steel structures.

The magnet is equipped with a mooring lug and rotating lever for easy release and safe operation.



All Miko magnets are shipped in a double-skin steel box to isolate the magnetic field and to prepare them for air freight. MAM-005 is also shipped with a keeper disk for further shielding.

CHARACTERISTICS

Holding Force **Gross Weight (Box)**
1 000 kg * 21 kg

Footprint **Quantity in Box**
282 x 183 mm 1 pcs

Net Weight
8 kg

CONTACT

Miko Marine AS
P.O. Box 1534 Vika
N-0117 Oslo
Norway

Website: www.miko.no
E-mail: info@miko.no
Telephone: +47 46 90 50 00

Read "IMPORTANT NOTES ABOUT MIKO MAGNETS" enclosed in each box before use.

*Refers to the perpendicular holding force when applied directly onto a clean mild steel plate of minimum thickness 30 mm.