


Fischer fastening materials



Repair Management Nederland B.V.

More management less firefighting

Ultraplugs hammerfix plugs PA 6. for wood screws till 16 mm diameter

S4 until S6 are specially designed for use with head screws.

Suited for concrete, rock, natural stone, perforated stone, hollow stone.

Article	Type	Screw in Depth	Total Length	Drill Size	Min. drill Depth	Screw diam.	Head screw diam.
170101	S 4	25 mm.	20 mm.	4 mm.	25 mm.	2.0-3 mm.	4.0 mm.
170102	S 5	30 mm.	25 mm.	5 mm.	35 mm.	2.5-4 mm.	5.0 mm.
170103	S 6	35 mm.	30 mm.	6 mm.	40 mm.	3.5-5 mm.	6.0 mm.
170104	S 7	40 mm.	30 mm.	7 mm.	40 mm.	4.0-5.5 mm.	
170105	S 8	50 mm.	40 mm.	8 mm.	55 mm.	4.5-6 mm.	
170106	S 10	60 mm.	50 mm.	10 mm.	70 mm.	6.0-8 mm.	
170107	S 12	70 mm.	60 mm.	12 mm.	80 mm.	8.0-10 mm.	
170108	S 14	80 mm.	75 mm.	14 mm.	95 mm.	10.0-12 mm.	
170109	S 16	90 mm.	80 mm.	16 mm.	100 mm.	12.0-14 mm.	
170110	S 20	100 mm.	90 mm.	20 mm.	120 mm.	16.0 mm.	



Hammerfix plugs, plugs for quick installation in concrete and massive stone type,

Suited for indoor and outdoor. Also available in stainless steel A2 for outdoor in damp conditions.

This plug is made of high quality nylon PA 6.6 and screw plug is zinc plated.

Suited for concrete, natural stone and massive stone.

Article	Type	Max. Thickness	Total Length	Drill Size	Min. drill Depth
170121	N 5 x 30Z	5 mm.	30 mm.	5 mm.	45 mm.
170122	N 5 x 40Z	15 mm.	40 mm.	5 mm.	55 mm.
170123	N 5 x 50Z	25 mm.	50 mm.	5 mm.	65 mm.
170125	N 6 x 40Z	10 mm.	40 mm.	6 mm.	55 mm.
170126	N 6 x 60Z	30 mm.	60 mm.	6 mm.	75 mm.
170127	N 6 x 80Z	50 mm.	80 mm.	6 mm.	95 mm.
170129	N 8 x 60Z	20 mm.	60 mm.	8 mm.	75 mm.
170130	N 8 x 80Z	40 mm.	80 mm.	8 mm.	95 mm.
170131	N 8 x 100Z	60 mm.	100 mm.	8 mm.	115 mm.
170132	N 8 x 120Z	80 mm.	120 mm.	8 mm.	135 mm.

