

**Power distribution boxes**



**rmm**

Repair Management Nederland B.V.  
More management less firefighting

**Distribution box Robuust 32A**

Robust full rubber housing, impact resistant, oil-, UV- and acid resistant.  
Protected with a ground fault interrupter and circuit breaker.  
All protections covered by transparent impact resistant cover.  
*Double insulated. Standard IP44*  
Standards: NEN-60439-1/4/ NEN-1010 CE-Approval

Number	Description
--------	-------------

606150	Portable box R32-062-4 Power supply CEE-TCD 32A 5P 400V/6h 1 x socket 32A 5p 400V/6h (to next box) 1 x ground fault interrupter 40A 4p/0,03A <b>1 x circuit breaker C-16A 3p</b> 2 x socket CEE 16A 5p 400V/6h 2 x circuit breaker C-16A 1p 4 x socket Schuko 2P+E 230V Dimensions: 300x340x240mm
--------	---



**Distribution box Robuust 32A**

Number	Description
--------	-------------

606151	Portable box R32-011-1 Power supply CEE-TCD 32A 5P 400V/6h 1 x socket 32A 5p 400V/6h (to next box) 1 x ground fault interrupter 40A 4p/0,03A <b>1 x circuit breaker C-32A 3p</b> 1 x socket CEE 32A 5p 400V/6h 1 x socket CEE 32A 4p 400V/6h 3 x circuit breaker C-16A 1p 6 x socket Schuko 2P+E 230V Dimensions: 300x340x240mm
--------	--



**Distribution box Robuust 32A**

Number	Description
--------	-------------

606151	Portable box R32-011-2 Power supply CEE-TCD 32A 5P 400V/6h 1 x socket 32A 5p 400V/6h (to next box) 1 x ground fault interrupter 40A 4p/0,03A <b>1 x circuit breaker C-25A 3p</b> 1 x socket CEE 32A 5p 400V/6h 1 x socket CEE 32A 4p 400V/6h 1 x ground fault interrupter 40A 4p/0,03A 3 x circuit breaker C-16A 1p 6 x socket Schuko 2P+E 230V Dimensions: 300x340x240mm
--------	---



**Distribution box Robuust 32A**

Number	Description
--------	-------------

606152	Portable box R32-011-4 Power supply CEE-TCD 32A 5P 400V/6h 1 x socket 32A 5p 400V/6h (to next box) 1 x ground fault interrupter 40A 4p/0,03A <b>1 x circuit breaker C-25A 3p</b> 1 x socket CEE 32A 5p 400V/6h 1 x socket CEE 32A 4p 400V/6h 4 x ground fault interrupter C-16A 1p 6 x socket Schuko 2P+E 230V Dimensions: 300x340x240mm
--------	---



### Distribution box Rubber Handy 6

Robust full rubber housing, impact resistant, oil-, UV- and acid resistant.  
Protected with a ground fault interrupter and circuit breaker.  
All protections covered by transparent impact resistant cover.  
Double insulated. Standard IP44  
Standards: NEN-60439-1/4/ NEN-1010 CE-Approval  
Equipped with MENNEKES sockets and Doepke protection.

Number	Description
--------	-------------

606153	Compact portable box Handy 6 Power supply CEE-TCD 32A 5P 400V/6h 1 x ground fault interrupter 40A 4p/0,03A 1 x socket CEE 32A 5p 400V/6h <b>1 x circuit breaker C-16A 3p</b> 1 x socket CEE 16A 5p 400V/6h 3 x circuit breaker B-16A 1p 3 x socket Schuko 16A 2P+E 230V Dimensions: 300x260x300mm
--------	---



### Distribution box Rubber Handy 5

Specifications as the Handy 6

Number	Description
--------	-------------

606154	Compact portable box Handy 5 Power supply CEE-TCD 32A 5P 400V/6h 1 x ground fault interrupter 40A 4p/0,03A 2 x socket CEE 32A 5p 400V/6h 3 x circuit breaker B-16A 1p 3 x socket Schuko 16A 2P+E 230V Dimensions: 300x260x300mm
--------	---



### Distribution box Rubber Handy 4

Specifications as the Handy 6

Number	Description
--------	-------------

606155	Compact portable box Handy 4 Power supply CEE-TCD 32A 5P 400V/6h 1 x ground fault interrupter 40A 4p/0,03A 6 x circuit breaker B-16A 1p 6 x socket Schuko 16A 2P-RA 230V Dimensions: 300x260x300mm
--------	---



### Distribution box Rubber Handy 3

Specifications as the Handy 6

Number	Description
--------	-------------

606156	Compact portable box Handy 3 Power supply CEE-TCD 16A 5P 400V/6h 1 x ground fault interrupter 40A 4p/0,03A 2 x socket CEE 16A 5p 400V/6h 3 x socket Schuko 16A 2P+E 230V Dimensions: 300x260x300mm
--------	---



### Verdeler Rubber Handy 2

Specifications as the Handy 6

Number	Description
--------	-------------

606165	Compact portable box Handy 2 Power supply : 5 m cable H07RN-F 5x2,5mm <sup>2</sup> with CEE-male plug 16A 5p 400V/6h 1 x ground fault interrupter 40A 4p/0,03A 6 x socket Schuko 16A 2P+E 230V Dimensions: 300x260x300mm
--------	---



### Verdeler Rubber Handy 1

Specifications as the Handy 6

Number	Description
--------	-------------

606166	Compact portable box Handy 1 Power supply : 5 m cable H07RN-F 3x2,5mm <sup>2</sup> with vulcanized male schuko plug, 16A 2P+E 230V 1 x ground fault interrupter 40A 4p/0,03A 6 x socket Schuko 16A 2P+E 230V Dimensions: 300x260x300mm
--------	--



### Construction site distribution box Multipower

Robust full rubber housing, impact resistant, oil-, UV- and acid resistant.  
Stable steel fully galvanized frame.

Protected with a ground fault interrupter and circuit breaker.  
All protections covered by transparent impact resistant cover.

Double insulated. Standard IP44

Standards: NEN-60439-1/4/ NEN-1010 CE-Approval

Number	Description
--------	-------------

606157	Construction site box 63A 21.M63-0201-1 Power supply CEE-TCD 63A 5p 400V/6h IP67 1 x socket CEE 63A 5p 400V/6h IP67 for through wiring to the next box. Main on/off switch 63A 4p 1 x ground fault interrupter 63A 4p/0,03A 2 x circuit breaker C-32A 3p 2 x socket CEE 32A 5p 400V/6h 1 x circuit breaker C-16A 3p 1 x socket CEE 16A 5p 400V/6h 1 x ground fault interrupter 40A 4p/0,03A 3 x circuit breaker C-16A 1p 6 x socket Schuko 2p+E 230V Dimensions. 500x500x760mm (incl. standard frame)
--------	--



### Construction site distribution box Multipower

Number	Description
--------	-------------

606158	Construction site box 63A 21.M63-021-1 Power supply CEE-TCD 63A 5p 400V/6h IP67 1 x socket CEE 63A 5p 400V/6h IP67 for through wiring to the next box. Main on/off switch 63A 4p 1 x ground fault interrupter 63A 4p/0,03A 3 x circuit breaker C-32A 3p 2 x socket CEE 32A 5p 400V/6h 1 x socket CEE 32A 4p 400V/6h 1 x ground fault interrupter 40A 4p/0,03A 3 x circuit breaker C-16A 1p 6 x socket Schuko 2p+E 230V Dimensions. 500x500x760mm (incl. standard frame)
--------	---



### Construction site distribution box Compact power

Specificaties als Multipower

Number	Description
--------	-------------

606159	Construction site box C32-020 Power supply CEE-TCD 32A 5p 400V/6h 1 x socket 32A 5p 400V/6h (to next box) 1 x ground fault interrupter 40A 4p/0,03A 1 x circuit breaker C-25A 3p 2 x socket CEE 32A 5p 400V/6h 3 x circuit breaker C-16A 1p 6 x socket Schuko 2p+E 230V Dimensions 300x340x640mm (incl. standard frame)
--------	---



### Construction site distribution box Compactpower

Specificaties als Multipower

Number	Description
606160	Construction site box C32-011 Power supply CEE-TCO 32A 5p 400V/6h 1 x socket 32A 5p 400V/6h (to next box) 1 x ground fault interrupter 40A 4p/0,03A 1 x circuit breaker C-25A 3p 2 x socket CEE 32A 5p 400V/6h 1 x socket CEE 32A 4p 400V/6h 3 x circuit breaker C-16A 1p 6 x socket Schuko 2p+E 230V Dimensions. 300x340x640mm (incl. standard frame)



### Construction site distribution box Deltapower

Specificaties als Multipower

Number	Description
606161	Construction site box 125A D125-23-1 Power supply CEE-TCO 125A 5p 400V/6h IP67 1 x socket CEE 125A 5p 400V/6h IP67 for through wiring to the next box. Main on/off switch 125A 4p 2 x ground fault interrupters 63A 4p/0,03A 2 x circuit breaker C-63A 3p 2 x socket CEE 63A 5p 400V/6h IP67 1 x ground fault interrupter 63A 4p/0,03A 2 x circuit breaker C-32A 3p 2 x socket CEE 32A 5p 400V/6h 1 x ground fault interrupter 40A 4p/0,03A 1 x circuit breaker C-32A 3p 1 x socket CEE 32A 5p 400V/6h 1 x ground fault interrupter 40A 4p/0,03A 3 x circuit breaker C-16A 1p 6 x socket Schuko 2p+E 230V Dimensions 500x500x930mm (incl. standard frame)



### Voltage Transformer box

Number	Description
606170	Transformer box T42-11 Power supply by 5 mtr cable H07RN-F 2x1mm <sup>2</sup> with vulcanized schuko male plug 230V 16A 2P+E Voltage transformer (ring type) 230V -42V, 120VA Internal thermal protection. 1 x socket CEE 16A 2p 42V/12h Dimensions 445x135x96mm



Number	Description
606171	Transformer T42-32 Power supply by 5 mtr cable H07RN-F 2x1mm <sup>2</sup> with vulcanized schuko male plug 230V 16A 2P+E Voltage transformer (ring type) 230V -42V, 300VA Internal thermal protection. 2 x socket CEE 16A 2p 42V/12h Dimensions 445x135x96mm

Number	Description
606172	Transformer TC11-12 Power supply by 5 mtr cable H07RN-F 2x1mm <sup>2</sup> with vulcanized schuko male plug 230V 16A 2P+E Voltage transformer (ring type) 230V-230V-42V, 1100VA External reset breaker 5A 1 x socket CEE 16A 3p 230V/12h (800VA) 1 x socket CEE 16A 2p 42V/12h (300VA) Dimensions 295x255x240mm



Number	Description
--------	-------------

606173	Transformer T42-62 Power supply by 5 mtr cable H07RN-F 2x1mm <sup>2</sup> with vulcanized schuko male plug 230V 16A 2P+E Voltage transformer (ring type) 230V-42V, 600VA External reset breaker 3A 2 x sockets CEE 16A 2p 42V/12h Dimensions 295x255x240mm
--------	---



**Distribution box rubber Ergosafe**

Robust full rubber housing, impact resistant, oil-, UV- and acid resistant. Protected with a ground fault interrupter.  
All protections covered by transparent impact resistant cover.  
*Double insulated. Standard IP44*  
Standards: NEN-60439-1/4/ NEN-1010 CE-Approval

Number	Description
--------	-------------

606180	Distribution box Ergosafe 4V 230V 1 x ground fault interrupter 1P+N 13A/10mA C-car. 4 x socket Schuko 16A 2p+RA 230V 5 meter cable H07RN-F 3x2,5mm <sup>2</sup> with vulcanized male plug Schuko type 230V 16A 2p+RA IP44 Optional with circuit breakers.
--------	---



Number	Description
--------	-------------

606181	Distribution box Ergosafe 6V 230V 1 x ground fault interrupter 40A 2p/0,03A 6 x socket Schuko 16A 2p+RA 230V 5 meter cable H07RN-F 3x2,5mm <sup>2</sup> with vulcanized male plug Schuko type 230V 16A 2p+RA IP44 Optional with circuit breakers.
--------	---



Number	Description
--------	-------------

606182	Distribution box Ergo 2 1 x ground fault interrupter 40A 2p/0,03A 6 x socket Schuko 16A 2p+RA 230V 5 meter cable H07RN-F 5x2,5mm <sup>2</sup> with CEE male plug 16A 5p 400V/6h Optional with circuit breakers.
--------	---



**Construction site power cabinet**

Robust steel plate cabinet with high quality powder coating. Impact resistant, oil- UV- and acid resistant. Extreme stable steel frame full galvanized. Protected with ground fault interrupters and circuit breakers. Door lockable with (optional) padlock.  
Other lock systems on request. Standard IP44  
Lockable power consumption meter compartment with watertight plywood mounting plate. Space for horizontal mounting of the knife fuses holde and kWh-counter by the energy supplier.  
Standards: NEN-60439-1/4/ NEN-1010 CE-Approval  
According to the latest Dutch energy supplier requirements 12/2016.  
Optional in plastic coomposite available.

Number	Description
--------	-------------

606190	Construction site cabinet B63-130-2 Main on/off switch 63A 4p 1 x ground fault interrupter 63A 4p/0,3A 1 x circuit breaker C-50A 3p 1 x socket CEE 63A 5p 400V/6h 1 x ground fault interrupter 63A 4p/0,03A 3 x circuit breaker C-25A 3p 3 x socket CEE 32A 5p 400V/6h 2 x circuit breaker C-16A 1p 6 x socket Schuko 2p+E 230V Dimensions 1500x600x630mm (incl. standard frame).
--------	---



Number	Description
--------	-------------

606191	<p>Construction site cabinet B63-121-2</p> <p>Main switch on/off 63A 4p</p> <p>1 x ground fault interrupter 63A 4p/0,3A</p> <p>1 x circuit breaker C-50A 3p</p> <p>1 x socket CEE 63A 5p 400V/6h</p> <p>1 x ground fault interrupter 63A 4p/0,03A</p> <p>3 x circuit breaker C-25A 3p</p> <p>2 x socket CEE 32A 5p 400V/6h</p> <p>1 x socket CEE 32A 4p 400V/6h</p> <p>2 x circuit breaker C-16A 1p</p> <p>6 x socket Schuko 2p+E 230V</p> <p>Dimensions 1500x600x630mm (incl. standard frame).</p>
--------	---



Number	Description
--------	-------------

606192	<p>Construction site cabinet 40A 21.B40-030</p> <p>Main on/off swicht 40A 4p</p> <p>1 x ground fault interrupter 40A 4p/0,03A</p> <p>3 x circuit breaker C-25A 3p</p> <p>3 x socket CEE 32A 5p 400V/6h</p> <p>1 x ground fault interrupter 40A 4p/0,03A</p> <p>2 x circuit breaker C-16A 1p</p> <p>6 x socket Schuko 2p+E 230V</p> <p>Dimensions 1500x600x630mm (incl. standard frame).</p>
--------	---



Number	Description
--------	-------------

606193	<p>Construction site cabinet B40-021</p> <p>Main on/off swicht 40A 4p</p> <p>1 x ground fault interrupter 40A 4p/0,03A</p> <p>3 x circuit breaker C-25A 3p</p> <p>2 x socket CEE 32A 5p 400V/6h</p> <p>1 x socket CEE 32A 4p 400V/6h</p> <p>1 x ground fault interrupter 40A 4p/0,03A</p> <p>2 x circuit breaker C-16A 1p</p> <p>6 x socket Schuko 2p+E 230V</p> <p>Dimensions 1500x600x630mm (incl. standard frame).</p>
--------	---

