

Cable Protectors

Cable Protectors

For a safe and clean workplace. Protects cables and hose and prevent tripping hazards. Visible and non-slip and safe to walk on thanks to brightly colored lids and a non-slip surface. Suitable for intensive use in industry, events or logistic. Expandable due to its modular system. High quality polyurethane (PU). Oil and grease resistant.



Type 2-channel straight

Cable protector 2-channel straight 980 x 245 x 40 mm. 2-channels for cable diameter 20-30 mm. Max. load capacity 2 Ton. Color yellow/black. For use in temperatures -30°C to +60°C.

Article No.	Description	Length	Packed
75CP02	Cable protector 2-channel 30 mm capacity	980 mm	1 pcs



Type 3-channel straight

Cable protector 3-channel straight 900 x 345 x 50 mm. 3-channels for cable diameter 33-35 mm. Max. load capacity 5 Ton. Color yellow/black. For use in temperatures -30°C to +60°C.


Article No.	Description	Length	Packed
75CP03	Cable protector 3-channel 35 mm capacity	900 mm	1 pcs



Type 5-channel straight

Cable protector 5-channel straight 800 x 445 x 45 mm. 5-channels for cable diameter 30-33 mm. Max. load capacity 3 Ton. Color yellow/black. For use in temperatures -30°C to +60°C.

Article No.	Description	Length	Packed
75CP05	Cable protector 5-channel 33 mm capacity	800 mm	1 pcs



Type 2-channel angle bend 30°

Cable protector 2-channel straight 285 x 245 x 40 mm. 2-channels for cable diameter 20-30 mm. Max. load capacity 2 Ton. Color yellow/black. For use in temperatures -30°C to +60°C. **For a 90° turn use 3 pieces.**

Article No.	Description	Length	Packed
75CP02C	Cable protector 2-channel 30 mm capacity	285 mm	1 pcs



Type 3-channel angle bend 30°

Cable protector 3-channel straight 410 x 345 x 50 mm. 3-channels for cable diameter 33-35 mm. Max. load capacity 5 Ton. Color yellow/black. For use in temperatures -30°C to +60°C. **For a 90° turn use 3 pieces.**

Article No.	Description	Length	Packed
75CP03C	Cable protector 3-channel 35 mm capacity	410 mm	1 pcs



Type 5-channel angle bend 30°

Cable protector 5-channel straight 385 x 445 x 45 mm. 5-channels for cable diameter 30-33 mm. Max. load capacity 3 Ton. Color yellow/black. For use in temperatures -30°C to +60°C. **For a 90° turn use 3 pieces.**

Article No.	Description	Length	Packed
75CP05C	Cable protector 5-channel 33 mm capacity	385 mm	1 pcs



Type 2-channel straight Heavy Duty

Cable protector 2-channel straight 980 x 240 x 40 mm. 2-channels for cable diameter 30 mm. Max. load capacity 5,5 Ton. Color yellow/black. For use in temperatures -30°C to +60°C. Made of recycled plastic composite.

Article No.	Description	Length	Packed
02KBB1250	Cable protector 2-channel 30 mm capacity	980 mm	1 pcs



Type 3-channel straight Heavy Duty

Cable protector 2-channel straight 900 x 500 x 70 mm. 3-channels for cable diameter 50 mm. Max. load capacity 9 Ton. Color yellow/black. For use in temperatures -30°C to +60°C. Made of recycled plastic composite.


Article No.	Description	Length	Packed
02KBB1350	Cable protector 3-channel 50 mm capacity	900 mm	1 pcs



Type 5-channel straight Heavy Duty

Cable protector 2-channel straight 900 x 500 x 50 mm. 5-channels for cable diameter 35 mm. Max. load capacity 9 Ton. Color yellow/black. For use in temperatures -30°C to +60°C. Made of recycled plastic composite.

Article No.	Description	Length	Packed
02KBB1450	Cable protector 5-channel 35 mm capacity	900 mm	1 pcs



Type 2-channel straight Light Duty

Cable protector 2-channel straight 800 x 600 x 80 mm. 2-channels for cable diameter 50 mm. Color yellow with reflective material. For use in temperatures -30°C to +60°C. Only for light traffic with rubber tyres. Complete with connector pieces.

Article No.	Description	Length	Packed
02KBB1500	Cable protector 2-channel 50 mm capacity	800 mm	1 pcs

