

Couplings Cam & Groove Polypropylene

Cam & Groove couplings

Robust quick, tight and leakproof connections to pipes, tubing and hoses. Available in different sizes and materials.

Cam & Groove couplings Polypropylene

Buna seal temperature resistant from -5°C to +80°C. For bulk-transport, shipping, industry, food, water etc.
Max. Pressure at +20°C, 1/2" - 1" 8 bar, 1.1/4" - 2" 6 bar, > 2.1/2" 5 bar.



Type A with BSP female thread

Article No.	Description	Thread BSP (F)	Type	IMPA
432407PP	Plug DN20 male	3/4"	A	-
432408PP	Plug DN25 male	1"	A	-
432409PP	Plug DN32 male	1.1/4"	A	-

Article No.	Description	Thread BSP (F)	Type	IMPA
432410PP	Plug DN40 male	1.1/2"	A	-
432411PP	Plug DN50 male	2"	A	-
432413PP	Plug DN75 male	3"	A	-



Type B with BSPT male thread

Article No.	Description	Thread BSP (M)	Type	IMPA
432417PP	Coupling DN20 female	3/4"	B	-
432418PP	Coupling DN25 female	1"	B	-
432419PP	Coupling DN32 female	1.1/4"	B	-

Article No.	Description	Thread BSP (M)	Type	IMPA
432420PP	Coupling DN40 female	1.1/2"	B	-
432421PP	Coupling DN50 female	2"	B	-
432423PP	Coupling DN75 female	3"	B	-



Type C with hose end

Article No.	Description	Hose end mm	Type	IMPA
432427PP	Coupling DN20 female	19	C	-
432428PP	Coupling DN25 female	25	C	-
432429PP	Coupling DN32 female	31	C	-

Article No.	Description	Hose end mm	Type	IMPA
432430PP	Coupling DN40 female	38	C	-
432431PP	Coupling DN50 female	50	C	-
432433PP	Coupling DN75 female	77	C	-



Type D with BSP female thread

Article No.	Description	Thread BSP (F)	Type	IMPA
432437PP	Coupling DN20 female	3/4"	D	-
432438PP	Coupling DN25 female	1"	D	-
432439PP	Coupling DN32 female	1.1/4"	D	-

Article No.	Description	Thread BSP	Type	IMPA
432440PP	Coupling DN40 female	1.1/2"	D	-
432441PP	Coupling DN50 female	2"	D	-
432443PP	Coupling DN75 female	3"	D	-



Type E with hose end

Article No.	Description	Hose end mm	Type	IMPA
432447PP	Plug DN20 male	19	E	-
432448PP	Plug DN25 male	25	E	-
432449PP	Plug DN32 male	31	E	-

Article No.	Description	Hose end mm	Type	IMPA
432450PP	Plug DN40 male	38	E	-
432451PP	Plug DN50 male	50	E	-
432453PP	Plug DN75 male	77	E	-



Type F with BSPT male thread

Article No.	Description	Thread BSP (M)	Type	IMPA
432457PP	Plug DN20 male	3/4"	F	-
432458PP	Plug DN25 male	1"	F	-
432459PP	Plug DN32 male	1.1/4"	F	-

Article No.	Description	Thread BSP (M)	Type	IMPA
432460PP	Plug DN40 male	1.1/2"	F	-
432461PP	Plug DN50 male	2"	F	-
432463PP	Plug DN75 male	3"	F	-



Type DP dust plug

Article No.	Description	DN	Type	IMPA
432471PP	Dust plug DN20 male	20	DP	-
432472PP	Dust plug DN25 male	25	DP	-
432473PP	Dust plug DN32 male	32	DP	-

Article No.	Description	DN	Type	IMPA
432474PP	Dust plug DN40 male	40	DP	-
432475PP	Dust plug DN50 male	50	DP	-
432477PP	Dust plug DN75 male	75	DP	-



Type DC dust cap

Article No.	Description	DN	Type	IMPA
432483PP	Dust cap DN20 female	20	DC	-
432484PP	Dust cap DN25 female	25	DC	-
432485PP	Dust cap DN32 female	32	DC	-

Article No.	Description	DN	Type	IMPA
432486PP	Dust cap DN40 female	40	DC	-
432487PP	Dust cap DN50 female	50	DC	-
432489PP	Dust cap DN75 female	75	DC	-



Couplings Cam & Groove Aluminium

Cam & Groove couplings Aluminium

Buna seal temperature resistant from -5°C to +100°C. For food, water, oil, diesel fuel etc.
Max. Pressure at +20°C, 1/2"- 2" 17 bar, 2.1/2" 10 bar, 3"-4" 8 bar.



Type A with BSP female thread

Article No.	Description	Thread BSP (F)	Type	IMPA	Article No.	Description	Thread BSP (F)	Type	IMPA
432406	Plug DN15 male	1/2"	A	35 17 01	432411	Plug DN50 male	2"	A	35 17 06
432407	Plug DN20 male	3/4"	A	35 17 02	432412	Plug DN65 male	2.1/2"	A	35 17 07
432408	Plug DN25 male	1"	A	35 17 03	432413	Plug DN75 male	3"	A	35 17 08
432409	Plug DN32 male	1.1/4"	A	35 17 04	432414	Plug DN100 male	4"	A	35 17 09
432410	Plug DN40 male	1.1/2"	A	35 17 05	432415	Plug DN150 male	5"	A	35 17 11



Type B with BSPT male thread

Article No.	Description	Thread BSP (M)	Type	IMPA	Article No.	Description	Thread BSP (M)	Type	IMPA
432416	Coupling DN15 female	1/2"	B	35 18 51	432421	Coupling DN50 female	2"	B	35 18 56
432417	Coupling DN20 female	3/4"	B	35 18 52	432422	Coupling DN65 female	2.1/2"	B	35 18 57
432418	Coupling DN25 female	1"	B	35 18 53	432423	Coupling DN75 female	3"	B	35 18 58
432419	Coupling DN32 female	1.1/4"	B	35 18 54	432424	Coupling DN100 female	4"	B	35 18 59
432420	Coupling DN40 female	1.1/2"	B	35 18 55	432425	Coupling DN150 female	6"	B	35 18 61



Type D female with hose end

Article No.	Description	Hose end mm	Type	IMPA	Article No.	Description	Hose end mm	Type	IMPA
432426	Coupling DN15 female	13	C	35 20 00	432431	Coupling DN40 female	50	C	35 20 05
432427	Coupling DN20 female	19	C	35 20 01	432432	Coupling DN50 female	64	C	35 20 06
432428	Coupling DN25 female	25	C	35 20 02	432433	Coupling DN75 female	77	C	35 20 07
432429	Coupling DN32 female	31	C	35 20 03	432434	Coupling DN100 female	101	C	35 20 08
432430	Coupling DN40 female	38	C	35 20 04	432435	Coupling DN150 female	152	C	35 20 10



Type D with BSP female thread

Article No.	Description	Thread BSP (F)	Type	IMPA	Article No.	Description	Thread BSP (F)	Type	IMPA
432436	Coupling DN15 female	1/2"	D	35 18 01	432441	Coupling DN40 female	2"	D	35 18 06
432437	Coupling DN20 female	3/4"	D	35 18 02	432442	Coupling DN50 female	2.1/2"	D	35 18 07
432438	Coupling DN25 female	1"	D	35 18 03	432443	Coupling DN75 female	3"	D	35 18 08
432439	Coupling DN32 female	1.1/4"	D	35 18 04	432444	Coupling DN100 female	4"	D	35 18 09
432440	Coupling DN40 female	1.1/2"	D	35 18 05	432445	Coupling DN150 female	6"	D	35 18 11



Type E with hose end

Article No.	Description	Hose end mm	Type	IMPA	Article No.	Description	Hose end mm	Type	IMPA
432446	Plug DN15 male	13	E	35 19 00	432451	Plug DN50 male	50	E	35 19 05
432447	Plug DN20 male	19	E	35 19 01	432452	Plug DN65 male	64	E	35 19 06
432448	Plug DN25 male	25	E	35 19 02	432453	Plug DN75 male	77	E	35 19 07
432449	Plug DN32 male	31	E	35 19 03	432454	Plug DN100 male	101	E	35 19 08
432450	Plug DN40 male	38	E	35 19 04	432455	Plug DN150 male	152	E	35 19 10



Type F with BSPT male thread

Article No.	Description	Thread BSP (M)	Type	IMPA	Article No.	Description	Thread BSP (M)	Type	IMPA
432456	Plug DN15 male	1/2"	F	35 17 51	432461	Plug DN50 male	2"	F	35 17 56
432457	Plug DN20 male	3/4"	F	35 17 52	432462	Plug DN65 male	2.1/2"	F	35 17 57
432458	Plug DN25 male	1"	F	35 17 53	432463	Plug DN75 male	3"	F	35 17 58
432459	Plug DN32 male	1.1/4"	F	35 17 54	432464	Plug DN100 male	4"	F	35 17 59
432460	Plug DN40 male	1.1/2"	F	35 17 55	432465	Plug DN150 male	6"	F	35 17 61



Type DP dust plug

Article No.	Description	DN	Type	IMPA	Article No.	Description	DN	Type	IMPA
432470	Dust plug DN15 male	15	DP	35 19 50	432475	Dust plug DN50 male	50	DP	35 19 55
432471	Dust plug DN20 male	20	DP	35 19 51	432476	Dust plug DN65 male	65	DP	35 19 56
432472	Dust plug DN25 male	25	DP	35 19 52	432477	Dust plug DN75 male	75	DP	35 19 57
432473	Dust plug DN32 male	32	DP	35 19 53	432478	Dust plug DN100 male	100	DP	35 19 58
432474	Dust plug DN40 male	40	DP	35 19 54	432479	Dust plug DN150 male	150	DP	35 19 60



Couplings Cam & Groove Brass

Cam & Groove couplings Aluminium

Buna seal temperature resistant from -5°C to +100°C. For food, water, oil, diesel fuel etc.
Max. Pressure at +20°C, 1/2"- 2" 17 bar, 2.1/2" 10 bar, 3"-4" 8 bar.

Type DC dust cap

Article No.	Description	DN	Type	IMPA	Article No.	Description	DN	Type	IMPA
432482	Dust cap DN15 female	15	DC	35 20 50	432487	Dust cap DN50 female	50	DC	35 20 55
432483	Dust cap DN20 female	20	DC	35 20 51	432488	Dust cap DN65 female	65	DC	35 20 56
432484	Dust cap DN25 female	25	DC	35 20 52	432489	Dust cap DN75 female	75	DC	35 20 57
432485	Dust cap DN32 female	32	DC	35 20 53	432490	Dust cap DN100 female	100	DC	35 20 58
432486	Dust cap DN40 female	40	DC	35 20 54	432491	Dust cap DN150 female	150	DC	35 20 60



Cam & Groove couplings Brass

Buna seal temperature resistant from -5°C to +100°C. For food, water, oil, diesel fuel, air etc.
Max. Pressure at +20°C, 1/2"- 2" 17 bar, 2.1/2" 10 bar, 3"-4" 8 bar.

Type A with BSP female thread

Article No.	Description	Thread BSP (F)	Type	IMPA	Article No.	Description	Thread BSP (F)	Type	IMPA
432406BR	Plug DN15 male	1/2"	A	35 17 15	432411BR	Plug DN50 male	2"	A	35 17 20
432407BR	Plug DN20 male	3/4"	A	35 17 16	432412BR	Plug DN65 male	2.1/2"	A	35 17 21
432408BR	Plug DN25 male	1"	A	35 17 17	432413BR	Plug DN75 male	3"	A	35 17 22
432409BR	Plug DN32 male	1.1/4"	A	35 17 18	432414BR	Plug DN100 male	4"	A	35 17 23
432410BR	Plug DN40 male	1.1/2"	A	35 17 19	432415BR	Plug DN150 male	5"	A	35 17 25



Type B with BSPT male thread

Article No.	Description	Thread BSP (M)	Type	IMPA	Article No.	Description	Thread BSP (M)	Type	IMPA
432416BR	Coupling DN15 female	1/2"	B	35 18 65	432421BR	Coupling DN50 female	2"	B	35 18 70
432417BR	Coupling DN20 female	3/4"	B	35 18 66	432422BR	Coupling DN65 female	2.1/2"	B	35 18 71
432418BR	Coupling DN25 female	1"	B	35 18 67	432423BR	Coupling DN75 female	3"	B	35 18 72
432419BR	Coupling DN32 female	1.1/4"	B	35 18 68	432424BR	Coupling DN100 female	4"	B	35 18 73
432420BR	Coupling DN40 female	1.1/2"	B	35 18 69	432425BR	Coupling DN150 female	6"	B	35 18 75



Type C with hose end

Article No.	Description	Hose end mm	Type	IMPA	Article No.	Description	Hose end mm	Type	IMPA
432426BR	Coupling DN15 female	13	C	35 20 14	432431BR	Coupling DN40 female	50	C	35 20 19
432427BR	Coupling DN20 female	19	C	35 20 15	432432BR	Coupling DN50 female	64	C	35 20 20
432428BR	Coupling DN25 female	25	C	35 20 16	432433BR	Coupling DN75 female	77	C	35 20 21
432429BR	Coupling DN32 female	31	C	35 20 17	432434BR	Coupling DN100 female	101	C	35 20 22
432430BR	Coupling DN40 female	38	C	35 20 18	432435BR	Coupling DN150 female	152	C	35 20 23



Type D with BSP female thread

Article No.	Description	Thread BSP (F)	Type	IMPA	Article No.	Description	Thread BSP (F)	Type	IMPA
432436BR	Coupling DN15 female	1/2"	D	35 18 15	432441BR	Coupling DN40 female	2"	D	35 18 20
432437BR	Coupling DN20 female	3/4"	D	35 18 16	432442BR	Coupling DN50 female	2.1/2"	D	35 18 21
432438BR	Coupling DN25 female	1"	D	35 18 17	432443BR	Coupling DN75 female	3"	D	35 18 22
432439BR	Coupling DN32 female	1.1/4"	D	35 18 18	432444BR	Coupling DN100 female	4"	D	35 18 23
432440BR	Coupling DN40 female	1.1/2"	D	35 18 19	432445BR	Coupling DN150 female	6"	D	35 18 25



Type E with hose end

Article No.	Description	Hose end mm	Type	IMPA	Article No.	Description	Hose end mm	Type	IMPA
432446BR	Plug DN15 male	13	E	35 19 14	432451BR	Plug DN50 male	50	E	35 19 19
432447BR	Plug DN20 male	19	E	35 19 15	432452BR	Plug DN65 male	64	E	35 19 20
432448BR	Plug DN25 male	25	E	35 19 16	432453BR	Plug DN75 male	77	E	35 19 21
432449BR	Plug DN32 male	31	E	35 19 17	432454BR	Plug DN100 male	101	E	35 19 22
432450BR	Plug DN40 male	38	E	35 19 18	432455BR	Plug DN150 male	152	E	35 19 24



Type F with BSPT male thread

Article No.	Description	Thread BSP (M)	Type	IMPA	Article No.	Description	Thread BSP (M)	Type	IMPA
432456BR	Plug DN15 male	1/2"	F	35 17 65	432461BR	Plug DN50 male	2"	F	35 17 70
432457BR	Plug DN20 male	3/4"	F	35 17 66	432462BR	Plug DN65 male	2.1/2"	F	35 17 71
432458BR	Plug DN25 male	1"	F	35 17 67	432463BR	Plug DN75 male	3"	F	35 17 72
432459BR	Plug DN32 male	1.1/4"	F	35 17 68	432464BR	Plug DN100 male	4"	F	35 17 73
432460BR	Plug DN40 male	1.1/2"	F	35 17 69	432465BR	Plug DN150 male	6"	F	35 17 75



Couplings Cam & Groove Stainless Steel

Cam & Groove couplings Brass

Buna seal temperature resistant from -5°C to +100°C. For food, water, oil, diesel fuel, air etc.
Max. Pressure at +20°C, 1/2"- 2" 17 bar, 2.1/2" 10 bar, 3"-4" 8 bar.

Type DP dust plug

Article No.	Description	DN	Type	IMPA	Article No.	Description	DN	Type	IMPA
432470BR	Dust plug DN15 male	15	DP	35 19 64	432475BR	Dust plug DN50 male	50	DP	35 19 69
432471BR	Dust plug DN20 male	20	DP	35 19 65	432476BR	Dust plug DN65 male	65	DP	35 19 70
432472BR	Dust plug DN25 male	25	DP	35 19 66	432477BR	Dust plug DN75 male	75	DP	35 19 71
432473BR	Dust plug DN32 male	32	DP	35 19 67	432478BR	Dust plug DN100 male	100	DP	35 19 72
432474BR	Dust plug DN40 male	40	DP	35 19 68	432479BR	Dust plug DN150 male	150	DP	35 19 74



Type DC dust cap

Article No.	Description	DN	Type	IMPA	Article No.	Description	DN	Type	IMPA
432482BR	Dust cap DN15 female	15	DC	35 20 64	432487BR	Dust cap DN50 female	50	DC	35 20 69
432483BR	Dust cap DN20 female	20	DC	35 20 65	432488BR	Dust cap DN65 female	65	DC	35 20 70
432484BR	Dust cap DN25 female	25	DC	35 20 66	432489BR	Dust cap DN75 female	75	DC	35 20 71
432485BR	Dust cap DN32 female	32	DC	35 20 67	432490BR	Dust cap DN100 female	100	DC	35 20 72
432486BR	Dust cap DN40 female	40	DC	35 20 68	432491BR	Dust cap DN150 female	150	DC	35 20 74



Cam & Groove couplings Stainless Steel AISI-316

Buna seal temperature resistant from -5°C to +100°C. For food, water, oil, diesel fuel, air etc.
Max. Pressure at +20°C, 1/2"- 2" 17 bar, 2.1/2" 10 bar, 3"-4" 8 bar.

Type A with BSP female thread

Article No.	Description	Thread BSP (F)	Type	IMPA	Article No.	Description	Thread BSP (F)	Type	IMPA
432406A4	Plug DN15 male	1/2"	A	35 17 31	432411A4	Plug DN50 male	2"	A	35 17 36
432407A4	Plug DN20 male	3/4"	A	35 17 32	432412A4	Plug DN65 male	2.1/2"	A	35 17 37
432408A4	Plug DN25 male	1"	A	35 17 33	432413A4	Plug DN75 male	3"	A	35 17 38
432409A4	Plug DN32 male	1.1/4"	A	35 17 34	432414A4	Plug DN100 male	4"	A	35 17 39
432410A4	Plug DN40 male	1.1/2"	A	35 17 35	432415A4	Plug DN150 male	5"	A	35 17 41



Type B with BSPT male thread

Article No.	Description	Thread BSP (M)	Type	IMPA	Article No.	Description	Thread BSP (M)	Type	IMPA
432416A4	Coupling DN15 female	1/2"	B	35 18 81	432421A4	Coupling DN50 female	2"	B	35 18 86
432417A4	Coupling DN20 female	3/4"	B	35 18 82	432422A4	Coupling DN65 female	2.1/2"	B	35 18 87
432418A4	Coupling DN25 female	1"	B	35 18 83	432423A4	Coupling DN75 female	3"	B	35 18 88
432419A4	Coupling DN32 female	1.1/4"	B	35 18 84	432424A4	Coupling DN100 female	4"	B	35 18 89
432420A4	Coupling DN40 female	1.1/2"	B	35 18 85	432425A4	Coupling DN150 female	6"	B	35 18 91



Type C with hose end

Article No.	Description	Hose end mm	Type	IMPA	Article No.	Description	Hose end mm	Type	IMPA
432426A4	Coupling DN15 female	13	C	35 20 30	432431A4	Coupling DN40 female	50	C	35 20 35
432427A4	Coupling DN20 female	19	C	35 20 31	432432A4	Coupling DN50 female	64	C	35 20 36
432428A4	Coupling DN25 female	25	C	35 20 32	432433A4	Coupling DN75 female	77	C	35 20 37
432429A4	Coupling DN32 female	31	C	35 20 33	432434A4	Coupling DN100 female	101	C	35 20 38
432430A4	Coupling DN40 female	38	C	35 20 34	432435A4	Coupling DN150 female	152	C	35 20 40



Type D with BSP female thread

Article No.	Description	Thread BSP (F)	Type	IMPA	Article No.	Description	Thread BSP (F)	Type	IMPA
432436A4	Coupling DN15 female	1/2"	D	35 18 31	432441A4	Coupling DN40 female	2"	D	35 18 36
432437A4	Coupling DN20 female	3/4"	D	35 18 32	432442A4	Coupling DN50 female	2.1/2"	D	35 18 37
432438A4	Coupling DN25 female	1"	D	35 18 33	432443A4	Coupling DN75 female	3"	D	35 18 38
432439A4	Coupling DN32 female	1.1/4"	D	35 18 34	432444A4	Coupling DN100 female	4"	D	35 18 39
432440A4	Coupling DN40 female	1.1/2"	D	35 18 35	432445A4	Coupling DN150 female	6"	D	35 18 41



Couplings Cam & Groove Stainless Steel

Cam & Groove couplings Stainless Steel AISI-316

Buna seal temperature resistant from -5°C to +100°C. For food, water, oil, diesel fuel, air etc.
Max. Pressure at +20°C, 1/2"- 2" 17 bar, 2.1/2" 10 bar, 3"-4" 8 bar.



Type E with hose end

Article No.	Description	Hose end mm	Type	IMPA	Article No.	Description	Hose end mm	Type	IMPA
432446A4	Plug DN15 male	13	E	35 19 30	432451A4	Plug DN50 male	50	E	35 19 35
432447A4	Plug DN20 male	19	E	35 19 31	432452A4	Plug DN65 male	64	E	35 19 36
432448A4	Plug DN25 male	25	E	35 19 32	432453A4	Plug DN75 male	77	E	35 19 37
432449A4	Plug DN32 male	31	E	35 19 33	432454A4	Plug DN100 male	101	E	35 19 38
432450A4	Plug DN40 male	38	E	35 19 34	432455A4	Plug DN150 male	152	E	35 19 40



Type F with BSPT male thread

Article No.	Description	Thread BSP (M)	Type	IMPA	Article No.	Description	Thread BSP (M)	Type	IMPA
432456A4	Plug DN15 male	1/2"	F	35 17 81	432461A4	Plug DN50 male	2"	F	35 17 86
432457A4	Plug DN20 male	3/4"	F	35 17 82	432462A4	Plug DN65 male	2.1/2"	F	35 17 87
432458A4	Plug DN25 male	1"	F	35 17 83	432463A4	Plug DN75 male	3"	F	35 17 88
432459A4	Plug DN32 male	1.1/4"	F	35 17 84	432464A4	Plug DN100 male	4"	F	35 17 89
432460A4	Plug DN40 male	1.1/2"	F	35 17 85	432465A4	Plug DN150 male	6"	F	35 17 91



Type DP dust plug

Article No.	Description	DN	Type	IMPA	Article No.	Description	DN	Type	IMPA
432470A4	Dust plug DN15 male	15	DP	35 19 80	432475A4	Dust plug DN50 male	50	DP	35 19 85
432471A4	Dust plug DN20 male	20	DP	35 19 81	432476A4	Dust plug DN65 male	65	DP	35 19 86
432472A4	Dust plug DN25 male	25	DP	35 19 82	432477A4	Dust plug DN75 male	75	DP	35 19 87
432473A4	Dust plug DN32 male	32	DP	35 19 83	432478A4	Dust plug DN100 male	100	DP	35 19 88
432474A4	Dust plug DN40 male	40	DP	35 19 84	432479A4	Dust plug DN150 male	150	DP	35 19 90



Type DC dust cap

Article No.	Description	DN	Type	IMPA	Article No.	Description	DN	Type	IMPA
432482A4	Dust cap DN15 female	15	DC	35 20 80	432487A4	Dust cap DN50 female	50	DC	35 20 85
432483A4	Dust cap DN20 female	20	DC	35 20 81	432488A4	Dust cap DN65 female	65	DC	35 20 86
432484A4	Dust cap DN25 female	25	DC	35 20 82	432489A4	Dust cap DN75 female	75	DC	35 20 87
432485A4	Dust cap DN32 female	32	DC	35 20 83	432490A4	Dust cap DN100 female	100	DC	35 20 88
432486A4	Dust cap DN40 female	40	DC	35 20 84	432491A4	Dust cap DN150 female	150	DC	35 20 90



Cam & Groove arm, pin, ring set Stainless Steel AISI-316

Spare set for all Cam & Groove couplings.

Article No.	Description	IMPA
432495	Arm set for 1/2" - 3/4"	35 21 51 / 35 21 52
432496	Arm set for 1"	35 21 53
432497	Arm set for 1.1/4" - 2.1/2"	35 21 54 / 35 21 55 / 35 21 56 / 35 21 57
432498	Arm set for 3" - 4"	35 21 58 / 35 21 59



Cam & Groove locking chains with both sides a connection ring

For all Cam & Groove couplings.

Article No.	Description	IMPA
432495CH	Chain 6" Brass	-
432496CH	Chain 6" Stainless Steel	-
432497CH	Chain 12" Brass	-
432498CH	Chain 12" Brass	-



Couplings Cam & Groove

Cam & Groove replacement seal rings

Several seal types for use on the Cam & Groove couplings.
Pay always attentions on the material properties of the seal before use.

Cam & Groove EPDM Seals resistant against (warm)water, leach, acid, solvents. Good weather resistant. Not oil and fuel resistant.
Temperature range from -40°C to +140°C.



Article No.	Description	For	IMPA	Article No.	Description	For	IMPA
432406EP	EPDM Seal DN15	1/2"	-	432411EP	EPDM Seal DN50	2"	-
432407EP	EPDM Seal DN20	3/4"	-	432412EP	EPDM Seal DN65	2.1/2"	-
432408EP	EPDM Seal DN25	1"	-	432413EP	EPDM Seal DN75	3"	-
432409EP	EPDM Seal DN32	1.1/4"	-	432414EP	EPDM Seal DN100	4"	-
432410EP	EPDM Seal DN40	1.1/2"	-	432415EP	EPDM Seal DN150	6"	-



Cam & Groove VITON (FKM) Seals limited resistant against acids and glycol based products, not suitable for warm water and steam. Very suitable for hydrocarbons, acids and vegetable oils.
Temperature range from -10°C to +130°C.

Article No.	Description	For	IMPA	Article No.	Description	For	IMPA
432406VI	Viton Seal DN15	1/2"	-	432411VI	Viton Seal DN50	2"	-
432407VI	Viton Seal DN20	3/4"	-	432412VI	Viton Seal DN65	2.1/2"	-
432408VI	Viton Seal DN25	1"	-	432413VI	Viton Seal DN75	3"	-
432409VI	Viton Seal DN32	1.1/4"	-	432414VI	Viton Seal DN100	4"	-
432410VI	Viton Seal DN40	1.1/2"	-	432415VI	Viton Seal DN150	6"	-



Cam & Groove PTFE Seals envelope open type, for acid and high temperatures. Resistant against almost all liquids.
The seal material is not flexible.
Temperature range from -20°C to +180°C.

Article No.	Description	For	IMPA	Article No.	Description	For	IMPA
432406PT	PTFE Seal DN15	1/2"	35 21 21	432411PT	PTFE Seal DN50	2"	35 21 26
432407PT	PTFE Seal DN20	3/4"	35 21 22	432412PT	PTFE Seal DN65	2.1/2"	35 21 27
432408PT	PTFE Seal DN25	1"	35 21 23	432413PT	PTFE Seal DN75	3"	35 21 28
432409PT	PTFE Seal DN32	1.1/4"	35 21 24	432414PT	PTFE Seal DN100	4"	35 21 29
432410PT	PTFE Seal DN40	1.1/2"	35 21 25	432415PT	PTFE Seal DN150	6"	



Cam & Groove BUNA Seals resistant against water, fuel, grease, mineral oil, heat and leach. sensitive to ozone.
Temperature range from -30°C to +75°C

Article No.	Description	For	IMPA	Article No.	Description	For	IMPA
432406BU	Buna Seal DN15	1/2"	35 21 01	432411BU	Buna Seal DN50	2"	35 21 06
432407BU	Buna Seal DN20	3/4"	35 21 02	432412BU	Buna Seal DN65	2.1/2"	35 21 07
432408BU	Buna Seal DN25	1"	35 21 03	432413BU	Buna Seal DN75	3"	35 21 08
432409BU	Buna Seal DN32	1.1/4"	35 21 04	432414BU	Buna Seal DN100	4"	35 21 09
432410BU	Buna Seal DN40	1.1/2"	35 21 05	432415BU	Buna Seal DN150	6"	35 21 11



Whip Check safety cable for air hoses with claw couplings

Essential safety device for any hose-to-hose and hose-to-outlet connection.
Galvanised Steel spring loaded wire nooses can easily be opened up to grip the hose firmly.
Attach the whip check safety device always in the correct way. See picture below.

Article No.	Description	Size
431050	Whip Check Ø3 x 530, pull dint 8.250 N	1/2" - 1.1/4"
431051	Whip Check Ø6.2 x 970 pull dint 30.000 N	1.1/2" - 3"

