

Electrical extension cable reels

EXTENSION CABLE REEL HEAVY DUTY 230/250V 16A SCHUKO

Thermoplastic rubber impact resistant cable drum with robust rotary knob. Mounted on a steel tube frame constructed in a way that cable cannot be clamped between drum and frame. Equipped with a neoprene cable with a vulcanized rubber male plug. Heavy Duty for building construction, industry and marine. Max. Voltage 250V, splash watertight IP44 with spring activated self-locking covers. Thermal protection for enhanced safety. Cable H07RN-F, 3x Schuko 2P+E 16A socket.

Article No.	Cable	Length mtr.	Max. output on drum	Max. output rolled of drum	IMPA
780203A	3x1.5mm ²	25	1000W	3600W	79 43 95
780204A	3x1.5mm ²	50	1000W	3600W	79 43 97
780205A	3x2.5mm ²	40	1500W	3600W	-
780206A	3x2.5mm ²	25	1500W	3600W	79 43 95



EXTENSION CABLE REEL HEAVY DUTY 230/250V 16A CEE

Full rubber impact resistant cable drum with robust rotary knob. Oil, fuel grease, acid and UV-radiation resistant. Mounted on a steel tube frame constructed in a way that cable cannot be clamped between drum and frame. Equipped with a neoprene cable with a CEE 230/250V male plug. Heavy Duty for building construction, industry and marine. Max. Voltage 250V, splash watertight IP44 with spring activated self-locking covers. Thermal protection for enhanced safety. Cable H07RN-F, 3x CEE 2P+E 16A socket.

Article No.	Cable	Length mtr.	Max. output on drum	Max. output rolled of drum	IMPA
780191A	3x2.5mm ²	25	1500W	3600W	79 43 95
780192A	3x2.5mm ²	40	1500W	3600W	-



EXTENSION CABLE REEL HEAVY DUTY 400V 16A CEE

Full rubber impact resistant cable drum with robust rotary knob. Oil, fuel grease, acid and UV-radiation resistant. Mounted on a steel tube frame constructed in a way that cable cannot be clamped between drum and frame. Equipped with a neoprene cable with a CEE 400V male plug. Heavy Duty for building construction, industry and marine. Max. Voltage 400V, splash watertight IP44 with spring activated self-locking covers. Thermal protection for enhanced safety. Cable H07RN-F, 2x CEE 4P+E 16A socket.

Article No.	Cable	Length mtr.	Max. output on drum	Max. output rolled of drum	IMPA
780190A	5x2.5mm ²	25	2500W	6400W	79 43 95



EXTENSION CABLE REEL HEAVY DUTY 400V 32A CEE

Special thermoplastic cable drum with robust rotary knob. Oil, fuel grease, acid and UV-radiation resistant. Frame made of the same material as the drum. Equipped with a neoprene cable with a CEE 400V male plug. Heavy Duty for building construction, industry and marine. Max. Voltage 400V, splash watertight IP44 with spring activated self-locking covers. Thermal protection for enhanced safety. Cable H07RN-F, 2x CEE 4P+E 32A socket. Special item can also be ordered as IP67.

Article No.	Cable	Length mtr.	Max. output on drum	Max. output rolled of drum	IMPA
780195	5x4.0mm ²	40	4500W	11600W	-



EXTENSION CABLE REEL HEAVY DUTY 400V 32A CEE

Special thermoplastic cable drum with robust rotary knob. Oil, fuel grease, acid and UV-radiation resistant. Frame made of the same material as the drum. Equipped with a neoprene cable with a CEE 400V male plug. Heavy Duty for building construction, industry and marine. Max. Voltage 400V, splash watertight IP44 with spring activated self-locking covers. Thermal protection for enhanced safety. Cable H07RN-F, 1x CEE 4P+E 32A socket through wire, 1x CEE 4PE 16A socket, 1x CEE 2P+E 16A socket, 2x Schuko 2P+E 16A socket. Protection 400V socket with circuit breaker 3C16A. Protection 230V sockets with circuit breaker 1C16A. 1x Ground fault inrupter 40A 4P 30mA. Special item can also be ordered with custom made specifications.

Article No.	Cable	Length mtr.	Max. output on drum	Max. output rolled of drum	IMPA
780255	5x2.5mm ²	50	2500W	6400W	-
780256	5x4.0mm ²	40	4000W	11600W	-



EXTENSION CABLE REEL BALANCER WALL MOUNT SPRING RETURN 230V SCHUKO

Yellow impact resistant thermoplastic cable drum. Automatic brake. Thermal protection. Rubber stopping ball on the cable end to protect the cable. Complete with wall / ceiling bracket. Cable H05VV-F (Vinyl), max. voltage 230V. Only for indoor use IP42.

Article No.	Cable	Length mtr.	Max. output on drum	Max. output rolled of drum	IMPA
780250V9	3x2.5mm ²	9+1	1,9 kW	2,5 kW	-



DISTRIBUTION BLOCK with multiple sockets 230V 16A SCHUKO

Heavy duty almost unbreakable nylon with socket outlets IP44 with self-closing covers. Equipped with a red neon voltage indicator. The base has 4 mounting holes in case the distribution block is used on a fixed place on the wall or workbench. Available with or without H07RN-F (neoprene NWPK) cable. Max. Voltage 230V and 16A.

Article No.	Cable	Length mtr.	Number of sockets	IMPA
780214	-	-	3	-
780213	-	-	4	-
780216	3x1.5mm ²	5	3	-
780217	3x1.5mm ²	10	3	-
780218	3x2.5mm ²	5	3	-
780220	3x2.5mm ²	10	3	-
780219	3x1.5mm ²	5	4	-
780221	3x1.5mm ²	10	4	-
780220B	3x1.5mm ²	25	3	-

