

LED ATEX EX Flashlights and Handlamps Rechargeable

KIRA AccuLux HL-35-Ex ATEX EX Zone 0 LED flashlight complies with DIN 14649

Robust plastic impact resistant housing, LED lantern for Zone 0/1/2/20/21/22.
Waterproof Protection IP67.
Adjustable luminaire head of 180° (can be rotated in both directions by 90°).
Exchangeable lithium-ion rechargeable battery 3,7V 5,0Ah. Emergency power function, can be deactivated.
Light output 380 lumen (3-steps). Distance beam appr. 200/300 mtr., weight 600gr.
Dimensions 237x105x77mm.
For hazard zone: 0, 1, 2 / 20, 21, 22. ATEX-Nr.: TÜV-A 19ATEX0002X, II 1 G Ex ia IIC T4 Ga and II 1 D Ex ia IIIC T135°C Da.
Illuminating duration up to 10 hours. Charging time appr. 9 hours. Digital charge indicator.
Practical rotary switch. Made in Germany.
Application areas: Rescue, Sewer Cleaning, Offshore.
Optional: multichargers available for 2, 3, 4 or 5-fold.

| Article No. | Description |
|-------------|---|
| 89KRL290787 | KIRA HL-35 EX Set Zone 0/1/2/20/21/22 + charger 100-230V & 12/24V |
| 89KRL290783 | KIRA HL-35 EX SET Zone 0/1/2/20/21/22 + charger 12/24V |
| 89KRL290784 | KIRA HL-35 EX Zone 0/1/2/20/21/22 Lamp Only |
| 89KRL290634 | KIRA Charger single 230V |
| 89KRL290635 | KIRA Charger single 12/24V |



KIRA AccuLux HL-30-Ex ATEX EX Zone 1 LED flashlight complies with DIN 14649 for fire service standard

Robust plastic impact resistant housing, LED lantern for Zone 1/2/21/22.
Waterproof Protection IP67.
Adjustable luminaire head of 180° (can be rotated in both directions by 90°).
Exchangeable lithium-ion rechargeable battery 3,7V 5,0Ah. Emergency power function, can be deactivated. Digital display showing the remaining light time.
Light output 300 lumen (3-steps) 300/250/135 lumens.
Distance beam appr. 250 mtr. near and high beam, weight 600gr.
Dimensions 237x105x77mm. Made in Germany.
For hazard zone 1, 2 / 21, 22. ATEX-Nr.: TÜV-A 20ATEX0001X, II 2 G Ex ib IIC T4 Gb and II 2 D Ex ib IIC T135°C Db.
Illuminating duration up to 10 hours (135 lumens). Charging time appr. 9 hours.
Application areas: Rescue, Sewer Cleaning, Offshore.
Optional: multichargers available for 2, 3, 4 or 5-fold.

| Article No. | Description |
|-------------|--|
| 89KRL290819 | KIRA HL-30 EX Set Zone 1/2/21/22 + charger 100-230V & 12/24V |
| 89KRL290818 | KIRA HL-30 EX Set Zone 1/2/21/22 + charger 12/24V |
| 89KRL290817 | KIRA HL-30 EX Zone 1/2/21/22 Lamp Only |
| 89KRL290634 | KIRA Charger single 230V |
| 89KRL290635 | KIRA Charger single 12/24V |



KIRA AccuLux HL-12-Ex ATEX EX Zone 0 LED flashlight

Robust plastic impact resistant housing, LED 90° angle light (not adjustable).
for Zone 0/20. Waterproof Protection IP67.
Lithium-ion battery rechargeable 3,7V 2600mAh. Illuminating duration up to 5/11 hours.
Made in Germany.
Light output 170/55 lumen. Distance beam appr. 200 mtr., weight 280gr.
Dimensions 61x90x200mm.
For hazard zone: 0/20 (No. **89KRL290777**). ATEX-Nr.: TÜV-A 16ATEX0003X, II 1 G Ex ia IIC T4 Ga and II 1 D Ex ia IIIC T135°C Da.
For hazard zone: 1/2/21/22 (No. **89KRL290774**). ATEX-Nr.: TÜV-A 16ATEX0003X, II 2 G Ex ib IIC T4 Gb and II 2 D Ex ib IIIC T135°C Db.
Application areas: Rescue, Sewer Cleaning, Offshore.

| Article No. | Description |
|-------------|---|
| 89KRL290777 | KIRA HL-12 EX Zone 0/20 Lamp only |
| 89KRL290774 | KIRA HL-12 EX Zone 1/21/2/22 Lamp only |
| 89KRL290776 | KIRA HL-12 EX Zone 1/21/2/22 + charger 100-230V |
| 89KRL290775 | KIRA HL-12 EX Zone 1/21/2/22 + charger 12/24V |
| 89KRL290634 | KIRA Charger single 100-230V |



Adalit L-3000 POWER ATEX ZONE 0/20 Handlamp

High performance 90° adjustable head handlamp for use in hazardous locations. Gas Zone: 0/1/2, Dust Zone: 20/21/22.
Thermoplastic body with high resistance to impacts, extreme temperatures and corrosive substances. Duo switch for extra comfort.
Light output 300 lumens, 15000cd peak beam intensity. Distance beam 245 mtr.
Waterproof class IP67, Impact resistance 4 mtr.
Maximum burntime on battery charge 4-6-8 hours, 3 modes. Dimension 225x7.0cm, weight 500 grams. Charging voltage standard 230V. Also possible with 12V, 24V charger.
Battery Li-Ion 3.7V, Low battery warning, blinking signal 15 min. before running out of battery.
Digital display. ATEX Approval: LOM 12ATEX2087. ATEX: II 1 G Ex ia op is IIC T4 Ga. ATEX: II 1 D Ex ia op is IIIC T85 °C Da.

| Article No. | Description |
|-------------|---|
| 900520 | Adaro Adalit L-3000 ATEX Zone 0 LED rechargeable 230V |



LED ATEX EX Flashlights and Handlamps Rechargeable

STREAMLIGHT SURVIVOR LED ATEX ZONE 0 Handlamp

A lightweight 90° angled head handlamp for use in hazardous locations.
 Light output 175 lumens, 41000cd peak beam intensity. Distance beam 405 mtr.
 Waterproof class IP66, Impact resistance 2 mtr.
 Maximum burntime on battery charge 3.5-10 hours, 2 modes.
 Dimension 17.92x7.24cm, weight 388 grams.
 Charging voltage standard 230V. Also possible with 12V, 24V charger.
 Battery Li-Ion 6.4V 1.5Ah. * = Without battery.
 ATEX Approval: FTZU 15 ATEX 0046X II 1G Ex ia IIB T4 Ga; II 2G Ex ia IIC T4 Gb
 IECEx Approval: Ex ia IIC T3/T4 Ga and Ex IIIB T270°C Db Tamb: -20°C to +40°C.
 Application areas: Rescue, Sewer Cleaning, Offshore.



| Article No. | Description |
|-------------|---|
| 900143 | Streamlight Survivor LOW Profile ATEX Zone 0 LED + charger 230V |
| 900144 | Streamlight Survivor LOW Profile ATEX Zone 0 LED + charger 12V |
| 900145 | Streamlight Survivor LOW Profile ATEX Zone 0 LED + charger 24V |
| 900143A | Spare Li-Ion battery for LOW Profile |
| 900143B | Survivor LOW Profile ATEX Zone 0 Lantern ONLY* |
| 900143C | Survivor LOW Profile 230 Charger (without holder) |
| 900143D | Survivor LOW Profile Lamp holder without charger |
| 900143E | Survivor LOW Profile ATEX 5-bay charging station 230V |

PELI 9415Z0 ATEX Zone 0 Rechargeable LED flashlight


High performance safety lantern with 4 LED's in the head.
 Light output 530 lumens, 18480cd peak beam intensity.
 Distance beam 272 mtr. Waterproof class IP X4, Impact resistance 1 mtr.
 Maximum burntime on battery charge 4.5 hours.
 3 modes, High 530 lumens, Low 202 lumens, Strobe. Dimension 22.2cm, 1650 gram.
 Rechargeable, NiMH batteries size C, 4 pcs. as pack 9418Z0. Charge time 15 hrs.
 Battery pack included. Battery pack total 4.8V. Battery level indicator.
 Certification: IECEx ia / ATEX Zone 0.



| Article No. | Description |
|-------------|---|
| 900518 | Peli 9415Z0 ATEX Zone 0 LED rechargeable 230V |

Scangrip UNI-EX ATEX Zone 0-20 Rechargeable LED flashlight


Multifunctional rechargeable ATEX LED worklamp. For use in Gas Zone 0 and Dust 20.
 UPGRADED MODEL. COB LED for a powerfull and uniform illumination.
 SPOT LED in the lantern for illumination as a flashlight.
 Light output COB Main LED 350 lumens, 500 lux @0.5 mtr.
 Light output SPOT SMD LED 150 lumens, 1200 lux @0.5 mtr.
 Waterproof class IP65, Impact resistance 1 mtr.
 Maximum burntime on battery charge up to 15 hours.
 3 modes, High 350 lumen, Low 175 lumen, and Spot 150 lumen.
 Dimension 22x7cm, weight 750 gram. Charging time 12 hours.
 Built-in magnet, belt clip and sturdy hook.
 Battery 3.6V Lithium Iron Phosphate 6700 mAh.
 Incl. charging base charger 100-240Vac 50/60Hz. Intelligent battery indicator.
 Certifications II 1G Ex ia IIC T3 Ga, II 1D Ex ia IIIC T130°C Da IP65.
 ATEX certificate no. TÜV IT 16 ATEX 083 X.
 IECEx certificate no. IECEx TPS 17.0003X.



| Article No. | Description |
|--------------|---|
| 90SCAN035617 | Scangrip UNI-EX ATEX Zone 0 LED rechargeable 230V |

Scangrip MIDI-EX ATEX Zone 2-22 Rechargeable LED flashlight

Multifunctional rechargeable ATEX LED worklamp. For use in Gas Zone 2 and Dust 22.
 COB LED for a powerfull and uniform illumination.
 SPOT LED in the lantern for illumination as a flashlight.
 Light output COB Main LED 200 lumens, 280 lux @0.5 mtr.
 Light output SPOT SMD LED 100 lumens, 560 lux @0.5 mtr.
 Waterproof class IP65, Impact resistance 1 mtr.
 Maximum burntime on battery charge 2.5 hours depending on light output.
 3 modes, High 200 lumen, Low 100 lumen, and Spot 100 lumen.
 Dimension 18x5cm, weight 236 gram. Built-in magnet, belt clip and sturdy hook.
 Battery 3.8V Lithium Iron Phosphate 1600 mAh.
 Incl. charger 100-240Vac 50/60Hz.
 Certifications II 3G Ex ic IIC T5 Gc, II 3D Ex ic IIIC T100°C Dc.
 ATEX certificate no. TPS 18 ATEX 054006 0015 X Rev.00.
 IECEx certificate no. IECEx TPS 18.0018X.



| Article No. | Description |
|--------------|---|
| 90SCAN035611 | Scangrip MIDI-EX ATEX Zone 2-22 LED rechargeable 230V |