Fein Hand Drills & Drill Drivers

Fein Electric Drill BOP 6

Fast running single-speed drill with good speed stability up to 6 mm in steel in metal construction. Cable 5 mtr. High precision metal drill chuck 0,5-10 mm, Fein high-power motor, Softgrip, Reversible. Variable speed control. 230V 50Hz, 500W, 0-2.700 rpm. Torque at max. output power 3.5 Nm. Capacity in steel 6 mm, Stainless Steel 6 mm, alu 10 mm, wood 20 mm. Collar ø 43 mm to use in a drill jig. **Type BOP 6 set** = including plastic case.

Article No.	Description	Steel ø mm	SS ø mm	Alu ø mm	Wood ø mm
560340	Fein Drill BOP 6	6	6	10	20
560341	Fein Drill BOP 6 set	6	6	10	20









Compact single speed drill with speed stability up to 10 mm in steel for on-site installation work. Cable 5 mtr. High precision metal drill chuck 1,5-13 mm, Fein high-power motor, Softgrip, Reversible. Variable speed control. 230V 50Hz, 500W, 0-900 rpm. Torque at max. output power 9 Nm. Capacity in steel 10 mm, Stainless Steel 10 mm, alu 15 mm, wood 30 mm. Collar ø 43 mm to use in a drill jig. **Type BOP 10 set** = including plastic case.

Article No.	Description	Steel ø mm	SS ø mm	Alu ø mm	Wood ø mm
560342	Fein Drill BOP 10	10	10	15	30
560343	Fein Drill BOP 10 set	10	10	15	30





Fein Electric Drill BOP 10-2

Universal two-speed drill up to 10 mm with ideal speed range for steel and stainless steel. Cable 5 mtr. High precision metal drill chuck 1,5-13 mm, Fein high-power motor, Softgrip, Reversible. Variable speed control. 230V 50Hz, 500W, 0-460/0-1.350 rpm. Torque at max. output power 20/7 Nm. Capacity in steel 10 mm, Stainless Steel 10 mm, alu 16 mm, wood 35 mm. Collar ø 43 mm to use in a drill jig. **Type BOP 10-2 set** = including plastic case.

Article No.	Description	Steel ø mm	SS ø mm	Alu ø mm	Wood ø mm
560354	Fein Drill BOP 10-2	10	10	16	35
560354B	Fein Drill BOP 10-2 set	10	10	16	35





Fein Electric Drill BOP 13-2

Universal two-speed drill up to 13 mm with ideal speed range for steel and stainless steel. Cable 5 mtr. High precision metal drill chuck 1,5-13 mm, Fein high-power motor, Softgrip, Reversible. Variable speed control. 230V 50Hz, 550W, 0-440/0-1.300 rpm. Torque at max. output power 20/7 Nm. Capacity in steel 10 mm, Stainless Steel 10 mm, alu 16 mm, wood 37 mm. Collar ø 43 mm to use in a drill jig. **Type BOP 13-2 set** = including plastic case.

Article No.	Description	Steel ø mm	SS ø mm	Alu ø mm	Wood ø mm
560352	Fein Drill BOP 13-2	10	10	16	37
560352B	Fein Drill BOP 13-2 set	10	10	16	37





Fein Electric Drill BOS 16Powerful drill with speed setting for flexible use in metal construction 16 mm. Cable 4 mtr.
High precision metal drill chuck 3,0-16 mm, Fein high-power motor, Softgrip, Forward/reverse running and electronic speed preselection. Speed control tacho electronics. 230V 50Hz, 1200W, 0-520 rpm.
Spade handle for optimum power transfer. Torque slipping clutch. Torque at max. output power 50 Nm. Capacity in steel 16 mm, Stainless Steel 16 mm, alu 20 mm, wood 50 mm.

Article No.	Description	Steel ø mm	SS ø mm	Alu ø mm	Wood ø mm
560345	Fein Drill BOS 16	16	16	20	50



Fein Electric Drill BOS 16-2

Powerful two-speed drill with speed setting for flexible use in metal construction up to16 mm. Cable 4 mtr. High precision metal drill chuck 3,0-16 mm, Fein high-power motor, Softgrip, Forward/reverse running and electronic speed preselection. Speed control tacho electronics 230V 50Hz, 1200W, 0-520/0-1.600 rpm. Spade handle for optimum power transfer. Torque slipping clutch. Torque at max. output power 50/16 Nm. Capacity in steel 16 mm, Stainless Steel 16 mm, alu 20 mm, wood 50 mm, hole saws 80 mm, countersingking 31mm.

Article No.	Description	Steel ø mm	SS ø mm	Alu ø mm	Wood ø mm
560346	Fein Drill BOS 16-2	16	16	20	50





Extremely small angle drill for working in difficult-to-reach spots 10 mm. Cable 5 mtr. High precision metal drill chuck 0,8-10 mm (keyed), Fein high-power motor, Softgrip, Reversible. 230V 50Hz, 500W, speed full load 0-1.030 tpm. Stall torque 21 Nm. Torque at max. output power 8 Nm. Capacity in steel 10 mm, Stainless Steel 10 mm, alu 15 mm, wood 25 mm. Tapping to max. M6.

Article No.	Description	Steel ø mm	SS ø mm	Alu ø mm	Wood ø mm
560347	Fein Angle Drill BWP 10	10	10	15	25



Fein Hand Drills & Drill Drivers

Fein Accu Boormachine ABOP 13-2 SELECT

Universal two-speed cordless drill up to 13 mm with ideal speed range for steel and stainless steel . Fein brushless PowerDrive-Motor, fully encapsulated and dust protected, 30% higher efficiency and long service life. High precision metal drill chuck 1,5-13 mm, Softgrip, Reversible, variable speed control. Mechanical two-speed gearbox for optimum speed adjustment for a wide range of uses, Speed at full load 0-500/0-1.500 tpm.

Torque at maximal power output 24/8 Nm. Capacity in steel 13 mm, Stainless Steel 13 mm, alu 16 mm,

wood 37 mm. Tapping max. M10. Collar ø 43 mm to use in a drill jig.

Fein SafetyCell Technology. Protects the battery and tool from overload, overheating and total discharge.

Battery voltage 18V, Battery-compability Li-ion/HighPower Li-ion, Battery interface 18V.

Supplied without batteries and charger. Body Only. Batteries and charger order separate.

Article No.	Description	Steel ø mm	SS ø mm	Alu ø mm	Wood ø mm
54F71050362000	Fein Cordless Drill ABOP 13-2 SE- LECT incl. plastic tool case	13	13	16	37

Fein Cordless Angle Drill AWBP 10 SELECT

Extremely small cordless angle drill for working in difficult-to-reach spots up to 10 mm. Fein brushless Extremely small cordless angle drill for working in difficult-to-reach spots up to 10 mm. Fein brushless PowerDrive-Motor, fully encapsulated and dust protected, 30% higher efficiency and long service life. High precision metal drill chuck 0,8-10 mm (keyed), Softgrip, Revesible, Speed full load 0-1.260 rpm. Stall Torque 17 Nm., Torque at maximal power output 9,5 Nm.

Capacity in steel 10 mm, Stainless Steel 10 mm, alu 15 mm, wood 25 mm. Tapping max. M6. Fein SafetyCell Technology. Protects the battery and tool from overload, overheating and total discharge. Battery voltage 18V, Battery-compability Li-ion/HighPower Li-ion, Battery interface 18V.

Supplied without batteries and charger. Body Only. Batteries and charger order separate.

Article No.	Description	Steel ø mm	SS ø mm	Alu ø mm	Wood ø mm
54F71050462000	Fein Angle Cordless Drill AWBP-10 SELECT incl. plastic tool case	10	10	15	25

Fein Industrial Drill Jig IBS-16

Industrial Drill Jig for drills with a drilling capacity of up to 16 mm. Lightweight, compact industrial drill Jig with aluminium base plate for univesal use, including drilling, tapping, reaming and countersinking. Double drill motor guide for use with very large drill tools. Base plate with hole pattern for Demmeler and Siegmund System 28 welding tables. Integrated coolant tank with flexible jointed hose. Feed handwheel can be moved from one side to the other. Carriage height adjustable without tools. For collar ø 53 mm. For BOP 10, BOP 13-2, ABOP 13-2 SELECT, GWP 10.

Capacity twist drill max. 16 mm, tapping M12, countersinking max. 50 mm, reaming max. 16 mm. Stroke 145 mm and total stroke range 295 mm.

Article No.	Description
54F90320223000 Fein Industrial Drill Jig IBS-16	
Article No.	Description
Description	
54F32623014010	Fein reducing ring for machines with collar ø 43 mm







Fein Drill Drivers

Fein Cordless Drill Drivers ASCM 18 QM SELECT
4-speed cordless drill/driver. Fein brushless PowerDrive-Motor, fully encapsulated and dust protected, 30% higher efficiency and long service life. QuickIN Max-interface for all QuickIN MAX and QuickIN accessories. No compromise on performance for drilling and tapping up to 12 mm and drilling with carbide hole saws. Electronic torque setting. Battery voltage 18V.

Including QuickIN solid metal drill chuck 1,5-13 mm with high clamping forces, Softgrip, Reversible. Fixes 10x400 mm screws without pre-drilling.

4-speed solid metal gearbox. Optimum cutting speeds for drilling in metal and self-drilling screwdriving, Speed no-load 400/800/1.950/3.850 rpm. Max torque hard/soft 90/45 Nm., torque levels 15+1. Capacity in steel 25 mm, wood 50 mm. Tapping max. M12. Fein SafetyCell Technology. Protects the battery and tool from overload, overheating and total discharge. Restart protection and brake. Battery-compability Li-ion/HighPower Li-ion, Battery interface 18V. incl. plastic tool case.

Supplied without batteries and charger. Body Only. Batteries and charger order separate

Article No.	Description	Steel ø mm	Wood ø mm	Tapping max.
54F71161164000	Fein Cordless Drill Driver ASCM 18QM SELECT	25	50	M12



4-speed cordless drill/driver. Fein brushless PowerDrive-Motor, fully encapsulated and dust protected, 30% higher efficiency and long service life. QuickIN interface for all QuickIN accessories. Fein MultiVolt Interface.

Tool works with all Fein Li-ion batteries (12 till 18 volt).

Metal QuickIN solid metal drill chuck 1,5-13 mm with high clamping forces, Softgrip, Reversible. Fixes 8x200 mm screws without pre-drilling. 550 screw connections (5x40 mm in wood) with one battery charge (3 Ah). 4-speed solid metal gearbox. Optimum cutting speeds for drilling in metal and self-drilling screwdriving, Speed no-load 400/700/1.400/2.500 rpm. Max torque hard/soft 40/20 Nm., torque levels 20+1. Capacity in steel 13 mm, wood 40 mm. Tapping max. M8. Fein SafetyCell Technology. Protects the battery and tool from overload, overheating and total discharge. Restart protection and brake. Battery voltage 18V,

Battery-compability Li-ion/HighPower Li-ion, Battery interface Multivolt. incl. plastic tool case.

Supplied without batteries and charger. Body Only. Batteries and charger order separate.

Article No.	Description	Steel ø mm	Wood ø mm	Tapping max.
54F71161264000	Fein Cordless Drill Driver ASCM 18QSW SELECT	13	40	M8





Fein Drill Drivers

Fein Cordless Drill Driver ABS 18 Q SELECT

2-speed cordless drill/driver. Fein brushless PowerDrive-Motor, fully encapsulated and dust protected, 30% higher efficiency and long service life. QuickIN interface for all QuickIN accessories. Fein MultiVolt Interface. Tool works on all Fein Li-ion batteries (12 till 18 volt).

Metal QuickIN solid metal drill chuck 1,5-13 mm with high clamping forces, Softgrip, Reversible. Fixes 8x300 mm without pre-drilling. 900 screw connections (5x40 mm in wood)on one battery charge (3 Ah).

2-speed solid metal gearbox. Optimum cutting speeds for drilling in metal and self-drilling screwdriving, Speed no-

load 450/2.000 rpm. Max torque hard/soft 60/32 Nm., torque levels 22+1. Capacity in steel 13 mm, wood 50 mm. Tapping max. M10.

Fein SafetyCell Technology. Protects the battery and tool from overload, overheating and total discharge. Restart protection and brake. Battery voltage 18V, Battery-compability Li-ion/HighPower Li-ion, Battery interface Multivolt. Incl. plastic tool case

Supplied without batteries and charger. Body Only. Batteries and charger order separate.

Article No.	Description	Steel ø mm	Wood ø mm	Tapping max.
54F71132264000	Fein Cordless Drill Driver ABS 18Q SELECT	13	50	M10





Fein Cordless Combi Drill ASB 18 Q SELECT

2-speed cordless combi drill. Fein brushless PowerDrive-Motor, fully encapsulated and dust protected, 30% higher efficiency and long service life. QuickIN interface for all QuickIN accessories. Fein MultiVolt Interface.


Tool works on all Fein Li-ion batteries (12 till 18 volt).

Metal QuickIN solid metal drill chuck 1,5-13 mm with high clamping forces, Softgrip, Reversible. Fixes 8x300 mm screws without pre-drilling. 900 screw connections (5x40 mm in wood)on one battery charge (3 Ah).

2-speed solid metal gearbox with switchable striking mechanism for drilling in metal, stone and masonry. Speed no-load 450/2.000 rpm. Max torque hard/soft 60/32 Nm., Torque levels 22+1.

Capacity in steel 13 mm, wood 50 mm, stone 13 mm. Tapping max. M10. incl. plastic tool case. Fein SafetyCell Technology. Protects the battery and tool from overload, overheating and total discharge. Restart protection and brake. Battery voltage 18V, Battery-compability Li-ion/HighPower Li-ion, Battery interface Multivolt. Supplied without batteries and charger. Body Only. Batteries and charger order separate.

Article No.	Description	Steel ø mm	Wood ø mm	Tapping max.
54F71132364000	Fein Cordless Combi Drill ASB 18Q SELECT	13	50	M10



Fein Battery Pack 18V

Li-ion battery with charge status indicator and Fein SafetyCell Technology. Protects the battery and tool from overload, overheating and total discharge. Can be used with all Fein 18V cordless tools.

Article No.	Description
54F92604182020	Fein Battery pack 18V Li-Ion 3 Ah
54F92604175020	Fein Battery pack 18V Li-Ion 6 Ah

Fein Highpower Battery Starter Set 18V

2 pieces Li-ion batteries with charge status indicator and Fein SafetyCell Technology. Protects the battery and tool from overload, overheating and total discharge. With ALG 80 BC rapid charger, can be used on Fein 12V and 18V batteries. With USB port for mobile charging of small electronic devices. Charging times (80% of the maximum capacity) 12 and 18V / 3Ah: 31 minutes, 12 and 18V / 6Ah: 38 minutes and 18V / 5,2Ah: 33

Article No.	Description
54F92604324010	Fein Battery Starter set 18V Li-Ion 3 Ah
54F92604323010	Fein Battery Starter set 18V Li-Ion 6 Ah
54F92604210010	Fein Separate Rapid Charger ALG 80 BC

Fein Cordless LED-Lamp ALED 12-18V

Compact and durable cordless LED-lamp swivel-mounted lamp head. Compatible with all 12/14/18V Fein Li-ion batteries. Including hook for attaching the lamp. Extremely lightweight at 130 gram and very bright at 900 Lumen. Colour temperature is the equivalent to daylight. Brightness can be set to 2 levels.

Artikel No.	Description
54F92604200020	Fein Accu LED-Lamp ALED 12-18V without battery

Fein Tool Case

Plastic sturdy carrying case with inner dimensions of 470x275x116 mm

Article No.	Descriptiom
54F33901118010	Fein Plastic tool case

Fein OuickIN Accessories Set Metaal

QuickIN accessory set metal for cordless drill drivers for efficient metal working. Set contains bit holder 1/4", socket adapter 1/2", and tapping adapter with 2 collets for 4,5 and 6 mm.

Compatible with all Fein cordless drill drivers with a QuickIN / QuickIN MAX-interface.

Article No.	Description
54F64203017020	Fein QuickIN Accessory set Metal
54F64203003010	Fein Separate tapping adapter QuickIN with 2 collets for M4/M5/M6/M8
54F64203002010	Fein Separate socket adapter QuickIN 1/2" square connection
54F60510222010	Fein Separate bit holder QuickIN 1/4" magnetic
54F64203007010	Fein Separate hole saw adapter QuickIN for maximum diameter 40 mm

















Many other Fein accessories available, such as Drill Chucks and tapping adapters.