

## PELI ATEX Flashlight NON-Rechargeable LED Zone 0

### PELI type 2010Z0 SABRELITE FLASHLIGHT EXPLOSION-PROOF NON-RECHARGEABLE FLASHLIGHT FOR ZONE 0

#### Peli's Flagship LED Torch:

The SabreLite 2010Z0 is Peli's flagship LED torch. The rugged, light weight anti-static PC/PBT resin body is submersible to 1 meter for 30 mins (IPX7). The twist ON/OFF lens shroud eliminates accidental discharge. The flashlight is powered by 3 C alkaline cells. The SabreLite 2010Z0 is the future of LEDs and is certified to ATEX Zone 20



INDEX

#### Technical specifications:

**Battery:** 3x C Cell Alkaline batteries **not included**  
**IP Protection Class:** IPX7  
**Impact Resistant housing:** Plastic composite  
**Weight:** Approx. 380gr. with batteries  
**Headlight range:** Approx. 135m  
**Light level:** 129 lumen  
**Flash function:** No  
**Duration:** Approx. 22 h  
**Type LED's:** Power LED  
**Headlight:** Not adjustable  
**Tamb:** T4 / T3 depend on battery maker  
**Others:** Submersible till 1mtr

#### ATEX Identification:

II 1 G Ex ia op is IIC T4/T3 Ga(Gas)  
**Tool group:** II  
**Category:** 1G  
**Approvals:** ATEX Zone 0  
**ATEX Number:** TÜV-A 15ATEX0096X

**Important note:**  
 Panasonic C Cell LR14 = T4  
 Energize C Cell LR14 = T3

#### Dimensions:

Length in mm 206



#### Technical specifications:

**Body:** Anti-static PC/PBT  
**O-ring:** Ethylene Propylene  
**Lens:** Anti-static PMMA  
**Shroud:** Antistatic modified PC/PBT  
**Clip:** Antistatic modified PC/PBT  
**Contact spring retainer:** Stainless steel / Brass nickel

Article No.	Description	Charger	Range	Lumen	IP Class
900501	PELI 2010Z0 flashlight - Battery Version Zone 0 (3x C battery)	-	135 m	129 lm	IPX7

## PELI ATEX Flashlight NON-Rechargeable LED Zone 0

### PELI type 3315Z0 FLASHLIGHT EXPLOSION-PROOF NON-RECHARGEABLE FLASHLIGHT FOR ZONE 0

#### Peli's Lightweight LED Torch:

The 3315Z0, the lightweight compact design houses 3x AA batteries that power a single LED for 138 lumens of super bright LED light. Safety approved for the most volatile work environments ATEX Zone 20, the 3315Z0 LED light is one of the most efficient torches on the market today.

#### Technical specifications:

**Battery:** 3x AA Cell Alkaline batteries **included**  
**IP Protection Class:** IP67  
**Impact Resistant housing:** Plastic composite  
**Weight:** Approx. 176gr. with batteries  
**Headlight range:** Approx. 146m  
**Light level:** 138 lumen  
**Flash function:** No  
**Duration:** Approx. 19 h  
**Type LED's:** Power LED  
**Headlight:** Not adjustable  
**Tamb:** T4 / T3 depend on battery maker  
**Tamb:** -20°C - +40°C  
**Others:** Submersible till 1mtr

#### ATEX Identification:

II 1 G Ex ia IIC T4 Ga(Gas) (\*)  
 II 1 G Ex ia IIC T3 Ga (Gas) (\*)  
 II 1 D Ex ia IIIC T200 135°C Da (Dust) (\*)  
 II 1 D Ex ia IIIC T200 153°C Da (Dust) (\*)  
**Tool group:** II  
**Category:** 1G / 1D  
**Approvals:** ATEX Zone 0  
**ATEX Number:** TExVeritas 22ATEX1339X

**Important notes:**  
 Duracell MN1500, Panasonic AM-3PA/4B, Sanyo SEC-AC4AA  
 Group II: T4  
 Group III: T200 135°C

NX Power PCA9047  
 Group II: T3  
 Group III: T200 153°C

\* The NX Power PCA9047 is only used in the 3315Z0 and NOT in the 3315 flashlight

#### Dimensions:

Length in mm 156



#### Body specifications:

**Body:** Anti-static PC/PBT  
**O-ring:** Ethylene Propylene  
**Lens:** Anti-static PMMA  
**Shroud:** Antistatic modified PC/PBT  
**Clip:** Antistatic modified PC/PBT  
**Contact spring retainer:** Stainless steel / Brass nickel

Article No.	Description	Charger	Range	Lumen	IP Class
900502	PELI 3315Z0 flashlight - Battery Version Zone 0 (3x AA battery)	-	135 m	129 lm	IP67