

## PELI ATEX Flashlight NON-Rechargeable LED Zone 0

INDEX



### PELI type 3610Z0 FLASHLIGHT

EXPLOSION-PROOF NON-RECHARGEABLE RIGHT ANGLE FLASHLIGHT FOR **ZONE 0**

#### Peli's ANGLE HEAD LED Torch:

The 3610Z0 is a right angle light that uses the latest "Deep Mount" LED technology, delivering impressive lumens and lux performance. The stainless steel mounting clip allows for hands free applications. The body is made of tough ABS resin that's corrosion proof and resistant to extreme temperatures. It is powered by 4 AA alkaline cells. Certified to ATEX Zone 0 (Category 1). This flashlight is equipped with an One-handed safety switch. Is the angled version of the 2410Z0.

#### Technical specifications:

**Battery:** 4x AA Cell Alkaline batteries **not included**  
**IP Protection Class:** IPX7  
**Impact Resistant housing:** Plastic composite  
**Weight:** Approx. 298gr. with batteries  
**Headlight range:** Approx. 165m  
**Light level:** 153 lumen  
**Flash function:** No  
**Duration:** Approx. 5 h 45 min  
**Type LED's:** Power LED  
**Headlight:** Not adjustable  
**Tamb:** T4  
**Others:** Submersible till 1mtr

#### ATEX Identification:

II 1 G Ex ia IIC T4 Ga (Gas)  
 II 1 D Ex ia op is IIIC T200 135°C Da (Dust)

**Tool group:** II  
**Category:** 1G / 1D  
**Approvals:** ATEX Zone 0  
**ATEX Number:** TRAC 15ATEX0005X

**Important notes Approved for batteries:**  
 Energizer E91  
 Panasonic LR6  
 Sanyo SEC-AC4AA  
 Duracell MN1500

\* Do not mix cells from other manufacturers.  
 Replace all cells at the same time.

#### Dimensions:

Length in mm 191



#### Body specifications:

**Body:** Anti-static PC/PBT  
**O-ring:** Ethylene Propylene  
**Lens:** Anti-static PMMA  
**Shroud:** Antistatic modified PC/PBT  
**Clip:** Stainless steel  
**Contact spring retainer:** Stainless steel / Phosphore bronze / Brass Nickel Plate

Article No.	Description	Charger	Range	Lumen	IP Class
900506	PELI 3610Z0 flashlight - Battery Version Zone 0 (4x AA battery)	-	165 m	153 lm	IPX7

## PELI ATEX Flashlight NON-Rechargeable LED Zone 0

### PELI type 2410Z0 FLASHLIGHT

EXPLOSION-PROOF NON-RECHARGEABLE RIGHT ANGLE FLASHLIGHT FOR **ZONE 0**

#### Peli's StealthLite LED Torch:

Same features as the StealthLite 2400 but with the LED module that produces a true, bright colimated LED beam. The StealthLite 2410Z0 Zone 0 is corrosion proof, resistant to extreme temperatures, and submersible. It is powered by 4 AA alkaline cells. Certified to ATEX Zone 0 (gas) and 20 (dust). This flashlight is equipped with an One-handed safety switch.

#### Technical specifications:

**Battery:** 4x AA Cell Alkaline batteries **not included**  
**IP Protection Class:** IPX7  
**Impact Resistant housing:** Plastic composite  
**Weight:** Approx. 207gr. with batteries  
**Headlight range:** Approx. 165m  
**Light level:** 153 lumen  
**Flash function:** No  
**Duration:** Approx. 5 h 45 min  
**Type LED's:** Power LED  
**Headlight:** Not adjustable  
**Tamb:** T4  
**Others:** Submersible till 1mtr

#### ATEX Identification:

II 1 G Ex ia IIC T4 Ga (Gas)  
 II 1 D Ex ia op is IIIC T200 135°C Da (Dust)

**Tool group:** II  
**Category:** 1G / 1D  
**Approvals:** ATEX Zone 0  
**ATEX Number:** TRAC 15ATEX0005X

**Important notes Approved for batteries:**  
 Energizer E91  
 Panasonic LR6  
 Sanyo SEC-AC4AA  
 Duracell MN1500

\* Do not mix cells from other manufacturers.  
 Replace all cells at the same time.

#### Dimensions:

Length in mm 178



#### Body specifications:

**Body:** Anti-static PC/PBT  
**O-ring:** Ethylene Propylene  
**Lens:** Anti-static PMMA  
**Shroud:** Antistatic modified PC/PBT  
**Clip:** Stainless steel  
**Contact spring retainer:** Stainless steel / Phosphore bronze

Article No.	Description	Charger	Range	Lumen	IP Class
900503	PELI 2410Z0 flashlight - Battery Version Zone 0 (4x AA battery)	-	165 m	153 lm	IPX7