

# Streamlight ATEX Hand Lamp Rechargeable LED Zone 0- 20

## STREAMLIGHT SURVIVOR LED ATEX LED handlamp Zone 0 and 20 RECHARGEABLE LED ATEX RIGHT ANGLE FIRE FIGHTER LAMP



The Streamlight Survivor Low Profile is rated for Zone 0 with a low-profile bezel that doesn't interfere with gear and equipment. The clip securely grabs onto gear, and the D-ring allows your light to hang forward.

### Choice in rechargeable and Non-rechargeable:

The hand lamp is available in Rechargeable and Non-Rechargeable models and can work with Li-ion cell pack, AA Alkaline or AA lithium.

### Multiple light modes:

Four light modes as High, Low, Flash and Moonlight

### Battery protection:

Integrated safety circuit protects the battery from overcharge/overdischarge.

### Super strong and durable design:

The rubber push-button at the top of the hand lamp offers a simple operation even when using gloves. The housing is made of High-Impact resistant superstrong non-conductive rugged nylon polymer. One-way valve for case venting. The lens is made of unbreakable polycarbonate protected with a silicone anti-scratch coating. Low profile means that the lens ring is extremely compact, thereby reducing the chance of interfering with the rest of your equipment.

### RECHARGEABLE MODEL:

Pay attention the product specifications below refers to the rechargeable model only.



INDEX

### Technical specifications:

**Battery:** Li-ion Streamlight 90316 6,2V 1,5 Ah  
**IP Protection Class:** IP66  
**Impact Resistance:** 2 mtr height  
**Weight:** Approx. 0,39 kg  
**Tamb:** -20°C - +45°C  
**Lumen output:** 175 lm (High) / 60 lumen (Low)  
**Main light beam:** 405m (High) / 237m (Low)  
**Adjustable light output:** 4 steps  
**Working time:** 3,5 h (High) 10 h (Low)  
**Working time:** 5 hours continuous (Flash)  
**Working time:** 15 days continuous (Moonlight)  
**Charging time:** 10 h standard charger  
**Charging time:** 2,5 h fast charger

Chargers are not ex-proof  
 Charging always outside EX area

### ATEX Identification:

II 1 G Ex ia IIC T3/T4 Ga (Gas)  
 II 1 G Ex ia IIC T3/T4 Gb (Gas)  
**Tool group:** II  
**Category:** 1G  
**Approvals:** Zone 0 (Gas), 20 (Dust)  
**ATEX Number:** FTZU 15 ATEX 046X

### IECEx Identification:

Ex ia IIB T3/T4 Ga (Gas)  
 Ex ia IIC T3/T4 Gb (Gas)  
**Tool group:** II  
**Category:** 1G  
**Approvals:** Zone 0 (Gas), 20 (Dust)  
**IECex Number:** IECEx FTZU 15.0029X

### Dimensions:

L (in mm)  
 179,3



Article No.	Description	Charger	Lumen High	Lumen Low	IP Class
900143	Streamlight Survivor LOW profile Rechargeable ATEX Zone 0 + charger 230V	230V	175	60	IP66
900144	Streamlight Survivor LOW profile Rechargeable ATEX Zone 0 + charger 12V	12V	175	60	IP66
900145	Streamlight Survivor LOW profile Rechargeable ATEX Zone 0 + charger 24V	24V	175	60	IP66
900143A	Replacement rechargeable battery pack Li-ion for Survivor Low Profile	-	-	-	-
900143B	Streamlight Survivor LOW profile Rechargeable ATEX Zone 0 Lantern ONLY *	-	175	60	IP66
900143C	Streamlight Survivor LOW profile Charger 230V (without lamp holder)	230V	-	-	-
900143D	Streamlight Survivor LOW profile Lamp holder (without charger)	-	-	-	-
900143E	Streamlight Survivor LOW profile 5-Bay charging station 230V	230V	-	-	-