

## LED ATEX EX Flashlights and Handlamps NON Rechargeable

### KIRA AccuLux HL-12-Ex ATEX EX Zone 0 LED flashlight

Robust plastic impact resistant housing, LED 90° angle light (not adjustable) for Zone 0/20. Waterproof Protection IP65. Batteries 3x AAA included. Light output 170/55 lumen. Distance beam appr. 200 mtr., weight 280gr. Dimensions 61x90x200mm. For hazard zone: 0, 1, 2 / 20, 21, 22. ATEX-Nr.: TÜV-A 16ATEX0003X, II 1 G Ex ia IIC T4 Ga and II 1 D ia IIIC T135°C Da. Illuminating duration up to 5 hours. Made in Germany.

Article No.	Description
89KRL290773	KIRA AccuLux HL-12 Ex Battery version 3x AAA



### KIRA AccuLux HL-10-Ex ATEX EX Zone 1, 2, 21, 22 LED flashlight

Robust plastic impact resistant housing, LED light for Zone 1, 2, 21, 22. Waterproof Protection IP68. Batteries 4x AA included. Light output 110 lumen. Distance beam appr. 150 mtr., weight 167gr. Dimensions 172x41mm. For hazard zone: 1, 2 / 21, 22. ATEX-Nr.: TÜV-A 10ATEX0003X, II 2 G Ex ib IIC T4 and II 2 D ibD 21 T135°C. Illuminating duration up to 11 hours. Made in Germany. Submersible to 5mtr.

Article No.	Description
89KRL290771	KIRA AccuLux HL-10 Ex Battery version 4x AA
89KRL290654	AccuLux Hook- and loop helmet fastener for HL-10 Ex



### KIRA AccuLux MHL-5-Ex ATEX EX Zone 1, 2, 21, 22 LED Mini Torch

Robust plastic impact resistant housing, LED light for Zone 1, 2, 21, 22. Waterproof Protection IP65. Batteries 2x AAA included. Light output 42 lumen. Distance beam appr. 30mtr., weight 45gr. Dimensions 145x20mm. For hazard zone: 1, 2 / 21, 22. ATEX-Nr.: TÜV-A 13ATEX0004X, II 2 G Ex ib IIC T4 Gb and II 2 D ib IIIC T135°C Db. Illuminating duration up to 4 hours. Made in Germany.

Article No.	Description
89KRL290649	KIRA AccuLux MHL-5 Ex Battery version 2x AAA



### Peli 2010Z0 ATEX EX Zone 0 LED flashlight

ABS resin housing. Safety strap. For use in Gas Zone 0. On/off switch by turning lensring prevent unwanted discharging battery. Light output 129 lumens, 4582cd peak beam intensity Distance beam 135 mtr. Waterproof class IP X7 up to 1 mtr for 30 minutes. Impact resistance 1 mtr. Maximum burntime on battery pack 22 hours. Dimension 20.6cm, weight 380 grams. Battery 3 pcs Alkaline C-type total 4.5V (not included).

Article No.	Description
900501	Peli 2010Z0 ATEX Zone 0 flashlight 3x C Alkaline



### Peli 3315Z0 ATEX EX Zone 0 LED flashlight

Battery level indicator. Anti static PC/PBT housing. Safety strap. Push button switch. For use in Gas Zone 0. Light output 138 lumens, 5350cd peak beam intensity. Distance beam 146 mtr. Waterproof class IP67. Impact resistance 1 mtr. Maximum burntime on battery pack 19 hours. Dimension 15.6cm, weight 176 grams. Battery 3 pcs Alkaline AA-type total 4.5V (included).

Article No.	Description
900502	Peli 3315Z0 ATEX Zone 0 flashlight 3x AA Alkaline



### Peli 3610MZ0 ATEX EX Zone 0 LED flashlight

Right angle light with deep mount LED technology. ABS housing extreme temperature and corrosion resistant. For use in Gas Zone 0. On-handed safety switch on/off. Light output 153 lumens, 6837cd peak beam intensity. Distance beam 165 mtr. Waterproof class IP X7 1 mtr submersible. Impact resistance 1 mtr. Maximum burntime on battery pack 5 hours and 45 minutes. Dimension 19.1cm, weight 298 grams. Battery 4 pcs Alkaline AA-type total 6.0V (not included).

Article No.	Description
900506	Peli 3610Z0 ATEX Zone 0 flashlight 4x AA Alkaline



### STREAMLIGHT PROPOLYMER 3C LED ATEX EX Zone 0 LED flashlight

Ideally suited light suited for situations where gloves are typically worn. ABS housing extreme temperature and corrosion resistant. For use in Gas Zone 0. Safety screw avoid batteries being changed out, or the housing inadvertently being opened in hazardous environment. Safety clip. Light output 150 lumens, 7000cd peak beam intensity. Distance beam 167 mtr. Waterproof class IP67 1 mtr submersible for 30 minutes. Impact resistance 3 mtr. Maximum burntime on battery pack 18 hours. Dimension 23.62cm, weight 394 grams. Battery 3 pcs Alkaline C-type total 4.5V (not included).

Article No.	Description
900968	Streamlight Propolymer 3C LED ATEX Zone 0 flashlight 3x C Alkaline



### STREAMLIGHT SURVIVOR LOW PROFILE LED ATEX Zone 0 LED flashlight

Lightweight, angled head handlamp. Microprocessor controlled. Housing superstrong plastic compound, anti-static. Scratch resistant lens. For use in Zone 0. Rubber push button switch ideally to use in situations where gloves are typically worn. Powerful safety clip, ideal to attach to firemans suit. Light output 175 lumens, 41000cd peak beam intensity. Distance beam 405 mtr. 4 modes: High 175lm, Low 60lm, Moonlight (15 day runtime), Flash (5 hours signalling). Waterproof class IP66 Impact resistance 3 mtr. Maximum burntime on battery pack 20 hours. Dimension 17.92x7.24cm, weight 388 grams. Battery 4 pcs Alkaline or lithium AA-type total 6.0V (not included). Approval: FTZU 15 ATEX 0046X II 1G Ex ia IIB T3 Ga; II 2G Ex ia IIC T3 Gb.

Article No.	Description
900142	Streamlight Survivor Low Profile LED ATEX Zone 0 flashlight 4x AA Alkaline or Lithium

