

LED ATEX EX Flashlights and Handlamps Rechargeable

KIRA AccuLux HL-35-Ex ATEX EX Zone 0 LED flashlight

Robust plastic impact resistant housing, LED 180° adjustable head light for Zone 0/20. Waterproof Protection IP67. Exchangeable lithium-ion rechargeable battery 3,7V 5,0Ah. Emergency power function, can be deactivated. Light output 380 lumen (3-steps). Distance beam appr. 200/300 mtr., weight 600gr. Dimensions 237x105x77mm. For hazard zone: 0, 1, 2 / 20, 21, 22. ATEX-Nr.: TÜV-A 19ATEX0002X, II 1 G Ex ia IIC T4 Ga and II 1 D Ex ia IIIC T135°C DA. Illuminating duration up to 10 hours. Charging time appr. 9 hours. Made in Germany. Optional multichargers available.

Article No.	Description
89KRL290787	KIRA HL-35 EX Set with charger 100-230V & 12/24V
89KRL290783	KIRA HL-35 EX SET with charger 12/24V
89KRL290784	KIRA HL-35 EX Lamp Only

Article No.	Description
89KRL290634	KIRA Charger single 230V
89KRL290635	KIRA Charger single 12/24V



KIRA AccuLux HL-30-Ex ATEX EX Zone 0 LED flashlight complies with DIN 14649 for fire service standard

Robust plastic impact resistant housing, LED 180° adjustable head light for Zone 0/20. Waterproof Protection IP67. Exchangeable lithium-ion rechargeable battery 3,7V 5,0Ah. Emergency power function, can be deactivated. Digital display. Light output 380 lumen (3-steps). Distance beam appr. 200/250 mtr., weight 600gr. Dimensions 237x105x77mm. For hazard zone: 0, 1, 2 / 21, 22. ATEX-Nr.: TÜV-A 20ATEX0001X, II 2 G Ex ib IIC T4 Gb and II 2 D Ex ib IIC T135°C Db. Illuminating duration up to 10 hours. Charging time appr. 9 hours. Made in Germany. Optional multichargers available.

Article No.	Description
89KRL290819	KIRA HL-30 EX Set with charger 100-230V & 12/24V
89KRL290818	KIRA HL-30 EX SET with charger 12/24V
89KRL290817	KIRA HL-30 EX Lamp Only

Article No.	Description
89KRL290634	KIRA Charger single 230V
89KRL290635	KIRA Charger single 12/24V



KIRA AccuLux HL-12-Ex ATEX EX Zone 0 LED flashlight and ATEX Zone 1, 21, 2, 22

Robust plastic impact resistant housing, LED 90° angle light (not adjustable) for Zone 0/20. Waterproof Protection IP67. Lithium-ion battery rechargeable 3,7V 2600mAh. Illuminating duration up to 5/11 hours. Made in Germany. Light output 170/55 lumen. Distance beam appr. 200 mtr., weight 280gr. Dimensions 61x90x200mm. For hazard zone: 0/ 20 (No. 89KRL290777). ATEX-Nr.: TÜV-A 16ATEX0003X, II 1 G Ex ia IIC T4 Ga and II 1 D ia IIIC T135°C Da. For hazard zone: 1, 2, 21, 22 (No. 89KRL290774). ATEX-Nr.: TÜV-A 16ATEX0003X, II 2 G Ex ib IIC T4 Gb and II 2 D ib IIIC T135°C Db.

Article No.	Description
89KRL290777	KIRA HL-12 EX Zone 0 lamp only
89KRL290774	KIRA HL-12 EX Zone 1/21/2/22 lamp only
89KRL290776	KIRA HL-12 EX Zone 1/21/2/22 + charger 100-230V

Article No.	Description
89KRL290778	KIRA HL-12 EX Zone 1/21/2/22 + charger 12/24V
89KRL290634	KIRA Charger single 100-230V



STREAMLIGHT SURVIVOR LED ATEX ZONE 0 Handlamp

A lightweight 90° angled head handlamp for use in hazardous locations. Light output 175 lumens, 41000cd peak beam intensity. Distance beam 405 mtr. Waterproof class IP66, Impact resistance 2 mtr. Maximum burntime on battery charge 3.5-10 hours, 2 modes. Dimension 17.92x7.24cm, weight 388 grams. Charging voltage standard 230V. Also possible with 12V, 24V charger. Battery Li-Ion 6.4V 1.5Ah: *= without battery ATEX Approval: FTZU 15 ATEX 0046X II 1G Ex ia IIB T4 Ga; II 2G Ex ia IIC T4 Gb

Article No.	Description
900143	Streamlight Survivor LOW Profile ATEX Zone 0 LED 230V
900144	Streamlight Survivor LOW Profile ATEX Zone 0 LED 12V
900145	Streamlight Survivor LOW Profile ATEX Zone 0 LED 24V
900143A	Spare Li-Ion battery for LOW Profile

Article No.	Description
900143B	Survivor LOW Profile ATEX Zone 0 Lantern ONLY *
900143C	Survivor LOW Profile 230 Charger (without holder)
900143D	Survivor LOW Profile Lamp holder whitout charger
900143E	Survivor LOW Profile ATEX 5-bay charging station 230V



Adalit L-3000 POWER ATEX ZONE 0/20 Handlamp

High performance 90° adjustable head handlamp for use in hazardous locations. Gas Zone: 0/1/2, Dust Zone: 20/21/22. Thermoplastic body with high resistance to impacts, extreme temperatures and corrosive substances. Duo switch for extra comfort. Light output 300 lumens, 15000cd peak beam intensity Distance beam 245 mtr. Waterproof class IP67, Impact resistance 4 mtr. Maximum burntime on battery charge 4-6-8 hours, 3 modes. Dimension 225x7.0cm, weight 500 grams. Charging voltage standard 230V. Also possible with 12V, 24V charger. Battery Li-Ion 3.7V Low battery warning, blinking signal 15 min. before running out of battery. Digital display. ATEX Approval: LOM 12ATEX2087. ATEX: II 1G Ex ia op is IIC T4 Ga. ATEX: II 1D Ex ia op is IIIC T85 °C Da.

Article No.	Description
900520	Adaro Adalit L-3000 ATEX Zone 0 LED rechargeable 230V



PELI 3315Z0 ATEX Zone 0 Rechargeable LED flashlight

Ergonomic anti-static PC/PBT body. Safety strap. Light output 138 lumens, 5350cd peak beam intensity. Distance beam 146 mtr. Waterproof class IP67, Impact resistance 1 mtr. Maximum burntime on battery charge 19 hours. Switch type: push button, light modes on/off. Dimension 15.6cm, weight 176 gram. Battery: 3x AA Alkaline 4.5 volts total (included). Certification: IECEx ia / ATEX Zone 0.

Article No.	Description
900503	Peli 3315Z0 ATEX Zone 0 LED



PELI 9415Z0 ATEX Zone 0 Rechargeable LED flashlight

High performance safety lantern with 4 LED's in the head. Light output 530 lumens, 18480cd peak beam intensity. Distance beam 272 mtr. Waterproof class IP X4, Impact resistance 1 mtr. Maximum burntime on battery charge 4.5 hours. With 3 modes, High, Low, Strobe. Dimension 22.2cm, weight 1650 gram. Rechargeable, NiMH batteries size C, 4 pcs. as pack 9418Z0. Battery pack included. Battery pack total 4.8V. Certification: IECEx ia / ATEX Zone 0.

Article No.	Description
900518	Peli 9415Z0 ATEX Zone 0 LED rechargeable 230V



LED ATEX EX Flashlights and Handlamps Rechargeable

Scangrip UNI-EX ATEX Zone 0- 20 Rechargeable LED flashlight

Multifunctional rechargeable ATEX LED worklamp. For use in Zones Gas 0 & DUST 20 NEW UPGRADED MODEL COB LED for a powerfull and uniform illumination. SPOT LED in the lantern for illumination as a flashlight. Light output COB Main LED 350 lumen, 500 lux @0.5 mtr. Light output SPOT SMD LED 150 lumen, 1200 lux @0.5 mtr. Waterproof class IP65, Impact resistance 1 mtr. Maximum burntime on battery charge up to 15 hours. Light 3 modes, High 350 lumen, Low 175 lumen, and Spot 150 lumen. Dimension 22x7cm, weight 750 gram. Charging time 12 hours. Built-in magnet, belt clip and sturdy hook. Battery 3.6V Lithium Iron Phosphate 6700 mAh. Incl. charging base charger 100-240Vac 50/60Hz. Intelligent battery indicator. Certifications II 1G Ex ia IIC T3 Ga, II 1D Ex ia IIIC T130°C Da IP65 ATEX certificate no. TUV IT 16 ATEX 083 X, IECx certificate no. IECEx TPS 17.0003X

Article No.	Description
90SCAN035617	Scangrip UNI-EX ATEX LED rechargeable 230V



SCANGRIP®
INNOVATION FROM DENMARK



rmn
Repair Management Nederland B.V.
More management less firefighting



Scangrip MIDI-EX ATEX Zone 2-22 Rechargeable LED flashlight

Multifunctional rechargeable ATEX LED worklamp. For use in Gas Zone 2 and Dust 22. COB LED for a powerfull and uniform illumination. SPOT LED in the lantern for illumination as a flashlight. Light output COB Main LED 200 lumen, 280 lux @0.5 mtr. Light output SPOT SMD LED 100 lumen, 560 lux @0.5 mtr. Waterproof class IP65, Impact resistance 1 mtr. Maximum burntime on battery charge 2.5-5 hours depending on light output. Light 3 modes, High 200 lumen, Low 100 lumen, and Spot 100 lumen. Dimension 18x5cm, weight 236 gram. Charging time 3,5 hours. Built-in magnet, belt clip and sturdy hook. Battery 3.8V Lithium Iron Phosphate 1600 mAh. Incl. charger 100-240Vac 50/60Hz Certifications II 3G Ex ic IIC T5 Gc, II 3D Ex ic IIIC T100°C Dc. ATEX certificate no. TPS 18 ATEX 054006 0015 X Rev.01, IECx certificate no. IECEx TPS 18.0018X.

Article No.	Description
90SCAN035611	Scangrip MIDI-EX ATEX LED rechargeable 230V



LED ATEX EX Floodlights Rechargeable

Scangrip NOVA-EX ATEX Zone 1-21 Rechargeable LED floodlight

Multifunctional rechargeable ATEX LED worklamp. For use in Gas Zone 1 and Dust 21. COB LED for a powerfull and uniform illumination. Light output 4000 lumen, 6000 lux @0.5 mtr. Beam angle 110° and CRI Ra>90. Waterproof class IP65, Impact resistance IK07 (diecast shockproof aluminium). Maximum burntime on battery charge 4,3/2,15 hours depending on light output. Light 2 modes, High 4000 lumen, Low 2000 lumen. Dimension 27x26cm, weight 750 gram. Charging time 3 hours. Integrated carrying handle. The flexible stand can be used as a hanger and to position the lamp in the desired angle. Battery 21.6V Li-Ion 3350 mAh. Incl. charger 100-240Vac 50/60Hz with 5 meter H05RN-F cable. Intelligent battery indicator. Certifications II 2G Ex db eb mb IIC T6 Gb, II 2D Ex tb IIIC T85°C Db IP65. ATEX Certificate no. TUV IT 16 ATEX 081X, IECEx TPS 17.0001X.

Article No.	Description
90SCAN035618	Scangrip NOVA-EX-R ATEX LED rechargeable 230V



SCANGRIP®
INNOVATION FROM DENMARK




Scangrip ATEX LED Floodlight accessories

Scangrip offers several accessories for the EX ATEX floodlights which helps to illuminate the workplace optimum. The products are powder coated. The range consists of a NOVA-EX Tripot, a NOVA-EX Magnetic Bracket and a NOVA-EX Scaffolding bracket for pipe diameters 40-50mm.

Article No.	Description
90SCAN035616	Scangrip NOVA-EX Magnetic Bracket Zone 1 and 2, IIC, T6 Zone 21 and 22, IIIC, T85°C

Article No.	Description
90SCAN035609	Scangrip NOVA-EX Scaffolding Bracket Zone 1 and 2, IIC, T6 Zone 21 and 22, IIIC, T85°C

Article No.	Description
90SCAN035607	Scangrip NOVA-EX Tripot 1.35-3.00 mtr Zone 1 and 2, IIC, T6 Zone 21 and 22, IIIC, T85°C



KIRA LED ATEX EX Working & Emergency Power LAMP

KIRA AccuLux EX SLE 15 LED / EX SLE 16 LED ATEX EX Zone 1, 2, 21, 22 LED working- and emergency power lamp

Robust pABS impact resistant housing, POWER LED 90° with rotatable head for Zone 1, 2, 21, 22. Waterproof Protection IP54. Rechargeable lead gel battery 3,7V 4,6Ah. Light output 15 lumen for the EX SLE 15 and 170 lumen for the EX SLE 16. Distance beam appr. 150 mtr or 170 mtr., weight 1100gr. Dimensions 104x245x72mm. Complete as set with accessories. Nominal voltage charging 230Vac, 24V and 12Vdc. Trickle charge permitted by internal charging management. Current draw U/I: 230Vac/30mA, 12Vdc/290mA, 24Vdc/145mA. For ambient temperature -20°C - +40°C. For hazard zone: 1, 2 / 21, 22. ATEX-Nr.: TÜV-A 07ATEX0001X, II 2 G Ex ib IIC T4 Gb and II 2 D ib IIIC T135°C Db. Illuminating duration up to 5 hours and for the 5mm pilot LED approx. 85 hours. Made in Germany. The EX SLE 15 LED: wide homogeneous illumination. The EX SLE 16 LED: with focus lens for wide headlight range. Set consist of: Hand Lamp with charger, 1x front cover lens "orange colour", 1x front cover lens "clear", 1x power cable 230V with Euro plug, 1x power cable 12/24V with mounted car plug, user manual.

Article No.	Description
89KRL290645	KIRA EX SLE 15 LED SET POWER LED
89KRL290647	KIRA EX SLE 15 LED (lamp only)
89KRL290615	KIRA EX LE Charger
89KRL290646	KIRA EX SLE 16 LED SET POWER LED & Focus Lens
89KRL290648	KIRA EX SLE 16 LED (lamp only)
89KRL457810	KIRA EX SLE Rechargeable battery lead gel 4V 3,5Ah
89KRL457845	KIRA EX SLE AccuLux housing cover with sealing



KIRA
KIRA Leuchten GmbH

