

Headlamps Rechargeable

SCANGRIP I-VIEW Rechargeable LED Headlamp

Professional headlamp with a wide view, illuminates the entire workplace. Easy to switch the lamp on/off due to a touchless sensor. This provides the user more freedom even when using thick gloves. Main light: Light output 40-400 lumens, 1000 lux @0.5 mtr. Beam angle 120°/60°. Waterproof class IP65 IK07. Impact resistant 1 mtr. Maximum burntime on battery charge 2.5-5.5 hours. Main light adjustable light output in 2 levels. Dimension 10.5x5.2x4.3cm, weight 130 gram. Incl. Rechargeable battery Li-ion 3.8V 1600 mAh, with USB charge cable. Scangrip Schuko C-plug USB charger to be order separate.

SCANGRIP®
INNOVATION FROM DENMARK

rmn
Regel Management Nederland B.V.
More management less firefighting

Article No.	Description
90SCAN035626	Scangrip I-VIEW rechargeable headlamp version 2
90SCAN035782	Scangrip Powerbank 4000mAh for 90SCAN035782



SCANGRIP ZONE 2 Rechargeable LED Headlamp

Professional headlamp with a wide view, illuminates the entire workplace. On/off switch on the side of the lamp. Sturdy and light weight. Main light: Light output 20-200 lumens, 40-400 lux @0.5 mtr. Beam angle 120°/60°. Light color 6000K. RA >80. Waterproof class IP65, IK07. Impact resistant 1 mtr. Maximum burntime on battery charge 2 hours. Main light adjustable light output in 2 levels. Dimension 8,4x3,15x3,7cm, weight 84 gram. Incl. Rechargeable battery Li-Polymer 3.7V 1200 mAh, with USB charge cable. Scangrip Schuko C-plug USB charger to be order separate.

Article No.	Description
90SCAN035850	Scangrip ZONE 2 rechargeable headlamp



STANDARD HEADLAMP I-VIEW HEADLAMP



SCANGRIP NIGHT-VIEW Rechargeable LED Headlamp

Professional headlamp with a wide view, illuminates the entire workplace. Easy to switch the lamp on/off due to a touchless sensor. This provides the user more freedom even when using thick gloves. Choice between white and red light in one lamp for ultimate flexibility. Red light mainly used in night situations to read maps or for work on ships and offshore. On ships particularly useful on the bridge at night. Main light: Light output 80-160 lumens, 250-500 lux @0.5 mtr. Beam angle 120°/60°. Waterproof class IP65 IK07. Impact resistant 1 mtr. Maximum burntime on battery charge 2.5-5.0 hours. Main light adjustable light output in 2 levels. Dimension 10.5x5.2x4.3cm, weight 130 gram. Incl. Rechargeable battery Li-Polymer 3.8V 1600 mAh, with USB charge cable.

Article No.	Description
90SCAN035438	Scangrip I-VIEW rechargeable headlamp

2 COLOUR LIGHT



SCANGRIP I-VIEW Headlamp with high efficiency multi-LED design

Rechargeable head lamp with touchless sensor. OPTILight settings for optimized light and runtime with a simple touch. Dedicated buttons for on/off and brightness levels. Battery indicator. When set on sensor mode I-VIEW is switched on/off only by waving a hand on front of the lamp. Adjustable light output 3 levels. Light output 40-400 lumens. OPTILight settings: 500 lux @0.5 mtr. (EN 12464-1). High efficiency multi-LED design with 12 LED's. Maximum burntime on battery charge 21-2 hours. OPTILight 4 hours. Charging time 4,5 hours. Operating temperature -10°C to +40°C. Rechargeable battery Li-Ion 3.7V 1400 mAh, and USB to mini charge cable, charge voltage 100-240V 50/60Hz and 5V current 1A (2,6W). NO USB Charger included. Protection IP65, impact protection IK07, impact resistance 2 mtr. Angle main beam 120°/60°. Light color 5700K. Ra >80. Dimension 9,9 x 4,0 x 5,0cm LxWxH, weight 0,13 kg.

Article No.	Description
90SCAN036212	Scangrip I-VIEW MULTI LED rechargeable headlamp



SCANGRIP ZOOM LED Headlamp

The name "ZOOM" is because the beam angle can be "zoomed" in and out according to the nature of the job to be done. Thus the beam angle can be adjusted from 10° providing a very long beam distance of 75 meter to a much wider beam angle of 60° providing a shorter beam distance of 30 meter. Adjustable light output 3 levels. Illuminance distance 75,0 meter. Light output 10-220 lumens. 55 lux @0.5 mtr. up to 1200 lux @0.5 mtr. Maximum burntime on battery charge 19,0 to 4,5 hours. Charging time 2,5 hours. Operating temperature -10°C to +40°C. Rechargeable battery Li-Polymer 3.7V 2000 mAh, and USB to mini charge cable, charge voltage 100-240V 50/60Hz and 5V current 1A (5,5W). NO USB Charger included. Protection IP54, impact protection IK07, impact resistance 1 mtr. Adjustable beam angle 10° to 60°. Light color 6500K. Ra >70. Dimension 7,80 x 4,63 x 4,66 cm LxWxH, weight 0,11 kg.

Article No.	Description
90SCAN035627	Scangrip ZOOM COB LED rechargeable headlamp



STREAMLIGHT PROTAC-HL USB Rechargeable LED Headlamp

Professional headlamp with a wide view, illuminates the entire workplace. Three light modes High 1000 lumens medium 400 lumens and low 65 lumens. Bright white light. Comes with extra red and green lens. Spot and Flood lenses. 90° tilting lamp head reduces neck fatigue. Extremely comfortable adjustable elastic strap fits well on head and helmet. Waterproof class IP X4. Impact resistant 1 mtr. Maximum burntime on battery charge 2-20 hours. Main light adjustable light output in 3 levels. Beam range max. 228 mtr. Weight 229 gram. Incl. Rechargeable battery Li-Ion (18650 type) Charged via USB port.

Article No.	Description
900730	Streamlight PROTAC-HL USB rechargeable headlamp



Headlamps Rechargeable ATEX

SCANGRIP EX-VIEW Headlamp for Zones 2-22

Rechargeable EX-PROOF head lamp with touchless sensor. The EX-PROOF line is made for hazardous atmospheres with a potential risk for explosion. Is provided with the very newest rechargeable battery technology with extraordinary long duration. When set on sensor mode I-VIEW is switched on/off only by waving a hand on front of the lamp. Main Light COB LED Light output 200 lumens. Illuminance max. 300 lux @0.5 mtr. Secondary Light: SMD LED output 100 lumens. Illuminance max. 100 lux @0.5 mtr. Beam angle 35°. Maximum burntime on battery charge 2,5 hours. Charging time 3,5 hours. Operating temperature -10°C to +45°C. Rechargeable battery Li-Ion 3.8V 1600 mAh, and USB to mini charge cable, charge voltage 100-240V 50/60Hz and 5V current 1A (1,6W). NO USB Charger included. Protection IP65, impact protection IK07, impact resistance 1 mtr. Angle main beam 110°. Light color 6000K. Ra >80. Dimension 9,03 x 4,0 x 5,2cm LxWxH, weight 0,13 kg. The lamp can be detached easily from the band and used as a hand lamp or placed on a magnetic surface. Certified: II 3G Ex ic IIC T5 Gc. Certified: II 3D Ex ic IIIC T100° Dc IP65. Approved by TÜV SÜD according to the ATEX Directive no. 2014/34/EU effective from April 2016 and according to IECEx. ATEX certificate no: TPS 18 ATEX 054006 0014 X and IECEx certificate no: IECEx TPS 18.0017X

Article No.	Description
90SCAN035606	Scangrip EX-VIEW rechargeable LED headlamp



Headlamps Rechargeable ATEX

Adaro ADALIT L-5R Rechargeable ATEX EX ZONE 0 LED Headlamp

Professional rechargeable EX ATEX safety lamp with high intensity LED and light sensor. Designed to attach on a helmet. Helmet adapter optional. Compatible with the majority of firefighters helmets. Also ideally as handlamp. Can also be used with Alkaline batteries. Provides 135 lumens light output. 3 light modes with runtime of 30, 8 or 4 hours. Waterproof class IP67. Impact resistant 1 mtr. Maximum burntime on battery charge 2-20 hours. Main light adjustable light output in 3 levels. Beam range 228 mtr. Dimensions 150x38x444mm weight 125 gram. Incl. Rechargeable battery Li-Ion. Optional 4x AAA R03 Alkaline batteries. Carry holster optional with 360° rotating device. EX ATEX Approval LOM 12ATEX2004 Ex ia IIC T4 Ga Ex ia IIIC T85° C Da

Article No.	Description
900541	Adaro Adalit L-5R Rechargeable ATEX Zone 0 flashlight
900541B	Adaro Adalit L-5R Helmet connector
900541C	Adaro Adalit L-5R Multifunctional Holster for belt



Adaro ADALIT L-50 Rechargeable ATEX EX ZONE 0 LED Headlamp

Professional rechargeable EX ATEX safety lamp for Zone 0 both gas and dust. Light beam Spot and Flood. Lamp light head connected to the battery and can be removed from the battery. Ideally as firefighter headlamp to attach on the firefighting helmet. Provides 300 lumens light output (15000 candela) 2 light modes with runtime of 12 or 48 hours. Waterproof class IP67. Headpiece Ø 7,1 cm | 6,9 cm weight 150 grams, triple LED, light beam 135 mtr. Battery pack 108x4.1x4.2 cm and weight 450 grams. Digital display on the battery pack with real time in hours and minutes burning indication. Incl. Rechargeable battery Li-Ion, standard 230Vac charger. Optional 5 bank charger available. EX ATEX Approval II 1G Ex ia IIC T4 Ga; / II 1D Ex ia IIIC T135°C Da; / I M1 Ex ia I Ma.

Article No.	Description
900522	Adaro Adalit L-50 Rechargeable ATEX Zone 0 flashlight



Headlamps NON Rechargeable

STREAMLIGHT PROTAC-HL LED Headlamp

Professional headlamp with a wide view, illuminates the entire workplace. Three light modes High 635 lumens medium 105 lumens and low 20 lumens. Bright white light. 90° tilting lamp head reduces neck fatigue. Adjustable beam. Extremely comfortable adjustable elasticated strap fits well on head and helmet. Waterproof class IP X4. Impact resistant 1 mtr. Maximum burntime on battery pack 1.75 - 8 - 36 hours. Main light adjustable light output in 3 levels. Beam range max. 184 mtr. Weight 187 gram. Battery type: Lithium 2x CR123A (included).

Article No.	Description
900729	Streamlight PROTAC-HL headlamp



Headlamps NON Rechargeable ATEX

KIRA AccuLux STL-1-Ex ATEX EX Zone 0 LED headlamp

Tough housing, tiltable, CREE LED for Zone 0 (all gasses). Waterproof Protection IP67. Batteries 3x AAA included. Light output 174/90 lumen. Distance beam appr. 100 mtr., weight 164gr. With headband. For hazard zone: 0. ATEX-Nr.: DEMKO 164ATEX1354X, II 1 G Ex ia IIC T4 Ga IP67. Illuminating duration up to 13 hours. Made in Germany. Incl allen key.

Article No.	Description
989KRL290655	LIRA STL-1-EX Zone 0 headlamp 3x AAA



PETZEL PIXA 1 ATEX EX ZONE 2/22 LED Headlamp

Professional headlamp with a wide view, illuminates the entire workplace. Automatic battery spare modus at the end of the battery life, the light starts flashing. Extremely comfortable adjustable elasticated strap fits well on head and helmet. Light output 20-60 lumen beam 10-15 mtr. Waterproof class IP67 down to 1 mtr. for 30 minutes. Impact resistant 2 mtr Maximum burntime on battery pack 16-3.5 hours. Reserve modus 10 lm for 6.5 hours. Battery type: Alkaline AA 2x (included) compatible with rechargeable Ni-Mh and lithium batteries. Easy turning knob to switch on/off. Weight 160 gram. Certified II 3 GD Ex nA ic IIB T4 Gc tc IIIC T135°C Dc.

Article No.	Description
900391A	Petzel PIXA 1 ATEX EX Zone 2/22 headlamp



STREAMLIGHT HAZ-LO ATEX EX ZONE 0 LED Headlamp

Extremely high light output of banded light. One light mode High 120 lumen and beam of 165 mtr. Bright white light. 6800 cd peak beam intensity. Parabolic reflector for long range brilliance and smooth uniform beam pattern. Extremely comfortable adjustable elasticated strap fits well on head and helmet. Waterproof class IP X4. Impact resistant 1 mtr. Maximum burntime on battery pack 11 hours hours. Weight 202 gram. Head strap and helmet strap included. Battery type: Alkaline AA 3x (included). ATEX Approval FTZU 11 ATEX 0052X II 1 G Ex ia IIC T3 Ga.

Article No.	Description
900373	Streamlight HAZ-LO ATEX EX Zone 0 headlamp



STREAMLIGHT Enduro Pro Ex ATEX ZONE 0 LED Headlamp

High light output of banded light and floodlight function. Three light modes spot and flood both 160 lumens, combined 235 lumens. Beam distance 73 meters, max candela 1,320. Runtime low 5.00 hours and high 4.75 hours. Extremely comfortable adjustable elasticated strap fits well on head and helmet. Waterproof class IPX7. Impact resistant 1 mtr. Weight 99,2 gram. Adjustable head strap and 3M Dual Lock Battery type: Alkaline AAA 3x (included). ATEX Approval: II 1G ia op is IIV T4 Ga - FTZU 18 ATEX 0101X IECEx: Ex ia op is IIC T4 Ga - IECX FTZU 19.0003X IMETRO: Ex ia op is IIC T4 Ga - DNV 20.0025X

Article No.	Description
900374	Streamlight Enduro Pro Ex ATEX Zone 0 headlamp

