

LED Flashlights and Handlamps NON Rechargeable

STREAMLIGHT KNUCKLEHEAD LED flashlight

High quality handlamp with 360° rotatable head. Removable magnet.
Housing of high-impact, super-tough nylon polymer for exceptional durability.
Available as FLOOD light (yellow housing) and SPOT light (orange housing).
Light output 200 lumens, 1150cd peak beam intensity FLOOD.
Light output 180 lumens, 1100cd peak beam intensity SPOT.
Distance beam 68 mtr FLOOD and 210 mtr SPOT.
Waterproof class IP X4, Impact resistance 2 mtr.
Maximum burntime on battery pack 16 hours. 4 modes High, Low, Moonlight and Flash. Dimension 23.4x7.2cm, weight 519 gram.
Needs 4 pieces of AA Alkaline batteries.



Article No.	Description
900960	Streamlight Knucklehead FLOOD Yellow Alkaline 4x AA
900962	Streamlight Knucklehead SPOT Orange Alkaline 4x AA

LED Floodlights and Spotlights Rechargeable

STREAMLIGHT E-Spot LITEBOX LED floodlight

Robust industrial work light with a 90° rotatable head. Cushioned grip handle.
Housing of high-impact ABS thermoplastic.
3 pcs C4 LED's and deep dish parabolic reflectors to produce a large spot pattern.
Available as SPOT and SPOT FIREBOX.
The Firebox contains 2 pcs of Blue signalling lamps at the back of the lamp especially designed for Firefighters.
Light output 540 lumens, 5500cd peak beam intensity. Distance beam 469 mtr.
Waterproof class IP X4.
Maximum burntime on battery pack 15 hours.
Battery: Zero maintenance Lead Acid battery 6V 12000mAh.
Up to 500 times rechargeable.
Standard charging voltage 230V or 12V.
Dimension 29.2x13x17x8cm, weight 3580 gram.



Article No.	Description
900953	Streamlight E-Spot Litebox LED Orange rechargeable 230V
900954	Streamlight E-Spot Litebox PF (power failure) LED Beige rechargeable 230V with Emergency light function
900952	Streamlight E-Spot Litebox Firebox LED Orange rechargeable 230V



STREAMLIGHT E-Flood LITEBOX LED floodlight

Robust industrial work light with a 90° rotatable head. Cushioned grip handle.
Housing of high-impact ABS thermoplastic.
6 pcs C4 LED's and white pattern parabolic reflectors to produce a smooth flood pattern.
Available as E-FLOOD and E-FLOOD PF (with power failure function), and E-Flood HL with a selectable diffuser filter.
Light output 615 lumens, 4000cd peak beam intensity.
E-Flood HL light output 5300 lumen, 3100 cd peak beam intensity.
Distance beam 126 mtr and E-Flood HL 352 mtr.
Waterproof class IP X4.
Maximum burntime on battery pack 18 hours. E-Flood HL 8 hours.
Battery: Zero maintenance Lead Acid battery 6V 12000mAh. Battery E-Flood HL 12V 7200 mAh Lead acid. Up to 500 times rechargeable.
Standard charging voltage 230V or 12V.
Dimension 29.2x13x17x8cm, weight 3580 gram.
Dimensions E-Flood HL 31x13x19cm weight 4700 grams.



Article No.	Description
900955	Streamlight E-Flood Litebox LED Orange rechargeable 230V
900958	Streamlight E-Flood Litebox PF (power failure) LED Beige rechargeable 230V with Emergency light function
900955B	Streamlight E-Flood HL Litebox LED Orange rechargeable 230V with selectable diffuser filter



Peli 9410L LED floodlight

LED Lantern with 4 high power LED's providing super bright LED beam.
120° swivel lamp head.
Housing of high-impact, super-tough nylon polymer for exceptional durability.
Light output 2207 lumens, 51304cd peak beam intensity.
Distance beam 453 mtr.
Waterproof class IP X4, Impact resistance 1 mtr.
Maximum burntime on battery pack 3.1/4 hours.
3 modes High 2207 lumen, Low 463 lumen, Flash.
Dimension 22.2m, weight 1267 gram.
Battery, Li-Ion type 18650 pack of 6 pcs total 7.2V.
Replacement battery pack 9419L Peli.



Article No.	Description
900519	Peli 9410L LED Floodlight rechargeable 230V