

Floor matting

Standard Coco Matting

Coco natural fiber material, removed soil from shoes like a brush.
Wear resist with a rubber backing to prevent sliding of the mat.
Available on the roll and in standard sizes.



Article No.	Description	Packing unit	IMPA
740201	Coco mat Roll 1 mtr width	10 mtr	-
740201B	Coco mat Cutting fee per cut	-	-
740203	Coco mat 60x100 cm	1 pcs	51 10 23
740208	Coco mat 90x120 cm	1 pcs	51 10 24



Combination Coco Matting

Coco natural fiber material, removed soil from shoes like a brush.
Galvanized steel wire with coco fiber rolls. Wear resist and super strong.

Article No.	Description	Packing unit	IMPA
740205	Coco combination mat 40x60 cm	1 pcs	51 10 31



Door mat extra cleaning

Polyamide mat with PVC backing. Removes moisture and dirt from the shoes.
Mats are washable on a maximum temperature of 30 °C. Not for (Industrial) tumble-dryer!
Colours Dark Brown and Antracite Grey.

Article No.	Description	Packing unit	IMPA	Article No.	Description	Packing unit	IMPA
740208BR	Mat 40x60 cm Dark Brown	1 pcs	-	740208AN	Mat 40x60 cm Antracite	1 pcs	-
740209BR	Mat 40x70 cm Dark Brown	1 pcs	-	740209	Mat 40x70 cm Antracite	1 pcs	-
740210BR	Mat 60x90 cm Dark Brown	1 pcs	51 11 51	740210	Mat 60x90 cm Antracite	1 pcs	51 11 51
740211BR	Mat 90x130 cm Dark Brown	1 pcs	51 11 53	740211	Mat 90x130 cm Antracite	1 pcs	51 11 53
740212BR	Mat 90x150 cm Dark Brown	1 pcs	51 11 54	740212	Mat 90x150 cm Antracite	1 pcs	51 11 54
740214BR	Mat 120x190 cm Dark Brown	1 pcs	-	740214	Mat 120x190 cm Antracite	1 pcs	-



Door mat NOTRAX UNI washable

For medium traffic. 100% Polyamide with 100% nitril rubber backing.
Nitril rubber borders 2,5 cm on each side. Thickness 8,5 mm Weight 2,8 kg/m²
Fire rating EN 13501-1 Bfl-S1. Machine washable at +50 °C or vacuum cleaning.
Never use a (industrial) tumble dryer.
Available in 5 different colours.

Article No.	Description	Packing unit	IMPA
74NO010S002301BL	Mat Notrax UNI 60x85 cm Black	1 pcs	-
74NO010S003401BL	Mat Notrax UNI 85x115 cm Black	1 pcs	-
74NO010S003501BL	Mat Notrax UNI 85x150 cm Black	1 pcs	-
74NO010S004601BL	Mat Notrax UNI 115x180 cm Black	1 pcs	-



Door mat NOTRAX GUZZLER

For medium intensive traffic. Decalon yarns and natural rubber backing. Rubber borders 2,5 cm on each side.
Thickness 10,5 mm, Weight 5,2 kg/m². Fire rating ASTM D2859 passes DOC-FF-1-70.
Vacuum/shampooing or use injection/extraction methode to clean.
Available in 7 different colours.

Article No.	Description	Packing unit	IMPA
74NO166060090CH	Mat Notrax GUZZLER 60x90 cm Black	1 pcs	-
74NO166060120CH	Mat Notrax GUZZLER 90x120 cm Black	1 pcs	-
74NO166090120CH	Mat Notrax GUZZLER 90x150 cm Black	1 pcs	-
74NO166090300CH	Mat Notrax GUZZLER 90x300 cm Black	1 pcs	-
74NO166120180CH	Mat Notrax GUZZLER 120x180 cm Black	1 pcs	-
74NO166120300CH	Mat Notrax GUZZLER 120x300 cm Black	1 pcs	-



Door mat NOTRAX WAYFARER 16 mm

For heavy duty traffic. Thick coils (strand diameter 1 mm) of extruded from 100% PVC.
Backing vinyl (DOP free). Pressed borders on all sides. Thickness 16 mm. Weight 6 kg/m².
Fire rating EN 13501-1 Bfl-S1. Can be cleaned by hose down with water or with a vacuum cleaner.
Colors; dark grey, navy blue and red.

Article No.	Description	Packing unit	IMPA
74NO267S0035CH	Mat Notrax WAYFARER 90x150 cm Grey	1 pcs	-
74NO267S0046CH	Mat Notrax WAYFARER 120x180 cm Grey	1 pcs	-
74NO267S0035NB	Mat Notrax WAYFARER 90x150 cm Blue	1 pcs	-
74NO267S0046NB	Mat Notrax WAYFARER 120x180 cm Blue	1 pcs	-
74NO267S0035RE	Mat Notrax WAYFARER 90x150 cm Red	1 pcs	-
74NO267S0046RE	Mat Notrax WAYFARER 120x180 cm Red	1 pcs	-



Floor matting

Door mat NOTRAX WAYFARER 10 mm

For medium traffic. Fine loops of extruded Vinyl from 100% PVC. Backing vinyl (DOP free). Pressed borders on all sides. Thickness 10 mm. Weight 3 kg/m². Fire rating EN 13501-1 Bfl-S1. Can be cleaned by hose down with water or with a vacuum cleaner. Colors, only grey



Article No.	Description	Packing unit	IMPA
74NO265S0035CH	Mat Notrax WAYFARER 90x150 cm Grey	1 pcs	-
74NO265S0046CH	Mat Notrax WAYFARER 120x180 cm Grey	1 pcs	-

Door mat 3M NOMAD Extra Duty

Polyamide fibers to remove moisture and dirt. Vinyl backing with approx. 20mm borders on all sides. Colour dark grey. Cleaning: Can be washed (no tumbling drying), or by vacuum cleaning.

Article No.	Description	Packing unit	IMPA
943M2255	3M NOMAD door mat 70x90cm Dark Grey	1 pcs	51 11 52



Door mat Rubber Open Ring

Heavy duty quality can be connected to each other. For outside (deck) use where water can be drained easily through the open structure. Cleaning: Can be cleaned by hose down with water.

Article No.	Description	Packing unit	IMPA
740234	Open Ring Rubber Mat 100x100 cm 16mm	1 pcs	51 10 71
740234B	Coupler for 16mm high open ring mat	1 pcs	51 10 82
740235	Open Ring Rubber Mat 100x150 cm 22 mm	1 pcs	51 10 71
740237	Open Ring Rubber Mat 80x120 cm 16 mm	1 pcs	51 10 71
740238	Open Ring Rubber Mat 80x120 cm 22 mm	1 pcs	51 10 71



Door mat NOTRAX Rubber Open Ring OCT-O-FLEX 599B Bevelled

For loose lay placement indoors or outdoors. For heavy traffic. Natural rubber, bevelled edges on all sides. Thickness 12,5 mm, weight 9,8 kg/m². Suitable for use in extreme weather, octagonal ring design with open construction. Small holes diameter 14 mm, compliant with EU norm for public entrances. Cleaning: Can be cleaned by hose down with water.

Article No.	Description	Packing unit	IMPA
74NO599B0035OB	Mat Notrax 599B Oct-O-Flex 90x150 cm	1 pcs	-
74NO599B0046OB	Mat Notrax 599B Oct-O-Flex 120x180 cm	1 pcs	-
74NO599B7090OB	Mat Notrax 599B Oct-O-Flex 70x90 cm	1 pcs	-



Floor mat VIDAR COIN SBR

For indoor use in industrial applications. A raised circular design on the surface of the mat. Temperature range: -30 °C up to +70 °C. Specifications: Strong and wear resistant. With a anti-slip profile on top of the mat. Hardness Shore A ± 5° = 80. Specific gravity grs/cm³ = 1,6. Tensile strength Mpa = 3,5. Elongation on break % = 250. Shear mm³ = 400. Compression at 70 °C for 22 hour % = 40. Available in Black and Grey. Thickness 3.0mm. Cleaning: Can be cleaned with water or by vacuum cleaning.

Article No.	Description	Packing unit	IMPA
21ZECS803000	Vidar Coin Mat 1,2x10,0 mtr Black	1 pcs	-
21ZECS803001	Vidar Coin Mat 1,0x10,0 mtr Black	1 pcs	-
21ZECSG803000	Vidar Coin Mat 1,2x10,0 mtr Grey	1 pcs	-
21ZECS804501	Vidar Coin Mat 1,0x10,0 mtr Grey	1 pcs	-



Floor mat VIDAR COIN SBR M3 FIRECLASS RATING

For indoor use in industrial applications. A raised circular design on the surface of the mat. Temperature range: -30 °C up to +70 °C. Specifications: Strong and wear resistant. With a anti-slip profile on top of the mat. Hardness Shore A ± 5° = 75. Specific gravity grs/cm³ = 1,6. Tensile strength Mpa = 4. Elongation on break % = 250. Shear mm³ = 400. Compression at 70 °C for 22 hour % = 40. M3 FIRECLASS Rating. Thickness 4.5mm. Cleaning: Can be cleaned with water or by vacuum cleaning.

Article No.	Description	Packing unit	IMPA
21ZECS803000	Vidar Coin Mat M3 1,0x10,0 mtr Black	1 pcs	-
21ZECS803001	Vidar Coin Mat M3 1,2x10,0 mtr Black	1 pcs	-



Floor mat CHECKER Type NBR

Checkered field design for excellent traction and easy cleaning. NBR oil resistant. Temperature range: -20 °C to +70 °C. Hardness Shore A ± 5° = 65. Specific gravity grs/cm³ = 1,5. Tensile strength Mpa = 3. Elongation on break % = 200. Thickness 3.0mm & 5.0mm. Cleaning: Can be cleaned with water or by vacuum cleaning.

Article No.	Description	Packing unit	IMPA
21ZEC01063142	Checker Mat 1,4x10,0 mtr Black 3.0 mm	1 pcs	-
21ZEC01065142	Checker Mat 1,4x10,0 mtr Black 5.0 mm	1 pcs	-



Floor matting

Floor mat FINE RIB NBR oil resistant

Strong and wear resist. Has an anti-slip ribberd surface and a fine cloth patern on the reverse. Oil resistant NBR. Ideally suited for loose lay applications for floors, walkways, rubbers, loading aerars, work benches etc. Temperature range: -20 °C up to +70 °C. Hardness Shore A $\pm 5^\circ = 65$. Specific gravity grs/cm³ = 1,5. Tensile strength Mpa = 3,5. Elongation on break % = 250. Thickness 3.0mm.


Article No.	Description	Packing unit	IMPA
21ZE01050303	Fine Rib Mat 1,0x10,0 mtr Black NBR	1 pcs	51 10 85
21ZE01050302	Fine Rib Mat 1,2x10,0 mtr Black NBR	1 pcs	51 10 85



Floor mat FINE RIB SBR Standard type

Strong and wear resist. Has an anti-slip ribberd surface and a fine cloth patern on the reverse. Ideally suited for loose lay applications for floors, walkways, rubbers, loading aerars, work benches etc. Temperature range: -20 °C up to +70 °C. Hardness Shore A $\pm 5^\circ = 65$. Specific gravity grs/cm³ = 1,5. Tensile strength Mpa = 3,0. Elongation on break % = 200. Thickness 3.0mm.

Article No.	Description	Packing unit	IMPA
21ZE01050310	Fine Rib Mat 1,0x10,0 mtr Black SBR	1 pcs	51 10 85
21ZE01050300	Fine Rib Mat 1,2x10,0 mtr Black SBR	1 pcs	51 10 85



Door mat NOTRAX 345 Rubber Brush Outdoor

For heavy foot traffic. Natural rubber with bevelled edges on all sides. Thickness 16 mm, weight 13,6 kg/m². Can be cleaned by hose down with water.

Article No.	Description	Packing unit	IMPA
74NO345S2432BL	Mat Notrax 345 60x80 cm Black	1 pcs	-
74NO345S3239BL	Mat Notrax 345 80x100 cm Black	1 pcs	-
74NO345S3660BL	Mat Notrax 345 90x150 cm Black	1 pcs	-
74NO345S3672BL	Mat Notrax 345 90x180 cm Black	1 pcs	-



Floor mat NOTRAX 745 DOTS

For dry industrial applications, medium duty traffic. Both sides with a safety yellow colored line. PVC (DOP free), bevelled edges on all sides. Thickness 4,7 mm, weight 4 kg/m². Fire rating EN 13501-1 Bfl-S1. Slip rating R9. Free of DOP, free of DMF, free of ozone depleting, substances, free of silicone and free of heavy metals. Cleaning by daily sweeping with a brush. Colour Black with Yellow side lining.

Article No.	Description	Packing unit	IMPA
74NO737120010	Mat Notrax 745 1,2x10,0 mtr Black/Yellow	1 pcs	-
74NO737120022	Mat Notrax 745 1,2x22,8 mtr Black/Yellow	1 pcs	-
74NO737091022	Mat Notrax 745 0,91x22,8 mtr Black/Yellow	1 pcs	-



Floor mat Electrical Insulating EPDM for switchboard flooring

Wear resist mat with a ribbed profile. Electrical insulating to prevent an electrical shock. According to standard IEC 61111:2009 Class 2 Color grey Hardness 70 Shore A +/-5, tensile strength 5 Mpa, elongation at break 250%. Specific gravity 1,5 grs/cm³. Temperature -25°C to +120°C. Standard IEC CEI 61111. Resistant against 30.000 volt (30 kV). Proof test voltage 20.000 volt (20 kV). **Maximum use voltage 17.000 volt (17 kV). Thickness 3.0mm.**

Article No.	Description	Packing unit	IMPA
7707298	Electrical Insulating Mat 1,0x10x0 mtr Grey	1 pcs	51 10 98



Floor mat Electrical Insulating EPDM for switchboard flooring

Wear resist mat with a ribbed profile. Electrical insulating to prevent an electrical shock. According to standard IEC 61111:2009 **Class 4** Color grey Hardness 70 Shore A +/-5, tensile strength 5 Mpa, elongation at break 250%. Specific gravity 1,5 grs/cm³. Temperature -25°C to +120°C. Standard IEC CEI 61111. Resistant against 50.000 volt (50 kV). Proof test voltage 40.000 volt (40 kV). **Maximum use voltage 36.000 volt (36 kV). Thickness 4.5mm.**

Article No.	Description	Packing unit	IMPA
7707299	Electrical Insulating Mat 1,0x10x0 mtr Grey	1 pcs	51 10 99



Floor mat NOTRAX 585 ECO STANCE OIL RESISTANT NITRILE RUBBER

For wet/dry and oily environments. For medium duty in industrial applications. For placement in ESD assembly lines, picking packing and logistics warehouses, individual work stations. 100% nitril rubber, ramps on 4 sides are raised to form a holder tray around the mat. Rough gripper surface prevents the sorbent from shifting. Thickness 12,7 mm, weight 6,8 kg/m². Free of DOP, free of DMF, free of ozone depleting, substances, free of silicone and free of heavy metals. Can be cleaned by hose down with water. Accessories: 580F Standard Sorbent for Eco Stance .

Article No.	Description	Packing unit	IMPA
77NO585S0035BL	Mat Notrax 585 ECO STANCE 87x157 cm Black	1 pcs	-
74NO580F	Standard Sorbent Pad	1 pcs	-

