

Water couplings GEKA Brass

Geka brass water couplings

Robust couplings for water applications. Body of brass.
Maximum pressure 25 bar. With EPDM seal temperature resistant to +95°C.



Article No.	Description	LUG in mm	Hose size mm	Hose Size inch
93450141	Geka coupling Hose end	40	13	1/2"
93450142	Geka coupling Hose end	40	19	3/4"
93450143	Geka coupling Hose end	40	25	1"
93450144	Geka coupling Hose end	40	38	1.1/4"



Article No.	Description	LUG in mm	Thread inch
93450151	Geka coupling fem. thread	40	1/2"
93450152	Geka coupling fem. thread	40	3/4"
93450153	Geka coupling fem. thread	40	1"
93450154	Geka coupling fem. thread	40	1.1/4"
93450155	Geka coupling fem. thread	40	1.1/2"



Article No.	Description	LUG in mm	Thread inch
93450161	Geka coupling male thread	40	1/2"
93450162	Geka coupling male thread	40	3/4"
93450163	Geka coupling male thread	40	1"
93450164	Geka coupling male thread	40	1.1/4"
93450165	Geka coupling male thread	40	1.1/2"



Article No.	Description	LUG in mm
93450160	Geka end cap	40



Article No.	Description	LUG in mm
93450167	Geka EPDM seal ring	40



Article No.	Description	LUG in mm
93450160S	Geka brass spray gun 3/4"	40



Heavy Duty Brass Wash Gun

Inlet connection 1/2" BSP female. Automatic switch-off trigger. Adjustable spray pattern. Rubber insulated housing doesn't leave residu or stripes. Trigger with lock mechanism. Not suitable for steam! Maximum workpressure WP 25 Bar.

Article No.	Description	Conn. Inch BSP
203000	Wash Gun Blue HD	1/2"

