

LED Portable Worklight FlexLED

Gifas FlexLED

Flexible LED Strip for illumination on both sides. Energy saving alternative for temporary illumination of work side. No shadows which is a big benefit in compare to spot lights. The FlexLed can easily be installed to ceilings, walls, stairways etc. and provides an optimum illumination. Installation is fast and easy what is a huge benefit using temporary illumination. The LED strip is covered by a high performance, durable, clear, flexible PVC tube. This provide the user more flexibility and a higher light output. The FlexLED is IP65 and can be used indoor and outdoor as well. The FlexLED is available in different lengths and comes ready for use on a cable reel with 1.5 connection cable with Euro plug. The FlexLED can be extended up to max. 100 meter.

GIFAS
ELECTRIC

rma
Repair Management Nederland B.V.
More management less firefighting

Technical features 230V:

LED: LED's double sided 2 x 180 LED's per meter length.
Voltage: 230Vac 50/60Hz.
System power: 325 Watt per 25 meter, (13W/m).
Light efficiency: 1.500 lm/m..
Light color: 4.000K
Light angle: 240° (120° on both sides).
Estimated useful life superior to >30.000 hour.
Protection: IP65 and IK08.
Ambient temperatures -25°C - +55°C.
Weight: 6 kg. for 25 meter reel.
Dimensions 16 x 8 mm (WxH).
Length: 10, 25 and 50 meter, extendable up to 100 meter.
Connection cable: 1.5 meter with Euro plug.

Technical features 42V:

LED: LED's double sided 2 x 180 LED's per meter length.
Voltage: 42Vac 50/60Hz.
System power: 200 Watt per 25 meter, (8W/m).
Light efficiency: 920 lm/m..
Light color: 4.000K
Light angle: 240° (120° on both sides).
Estimated useful life superior to >30.000 hour.
Protection: IP65 and IK08.
Ambient temperatures -25°C - +55°C.
Weight: 6 kg. for 25 meter reel.
Dimensions 16 x 8 mm (WxH).
Length: 10, 25 and 50 meter, extendable up to 100 meter.
Connection cable: 1.5 meter with Euro plug.

Article No.	Description	Wattage	Lumen output	W x H mm
83GF861020	FlexLED 25 mtr on HD reel	325	37.000	16 x 8
83GF800884	FlexLED 50 mtr on HD reel	650	75.000	16 x 8
83GF800833	FlexLED 10 mtr on light reel	130	15.000	16 x 8
83GF335081	FlexLED 25 mtr 42V on HD reel	200	23.000	16 x 8
83GF800834	FlexLED Emergency Battery	50W	-	-
83GF800835	FlexLED connection cable 1,5m	-	-	-
83GF800885	FlexLED T-Connector	-	-	-
83GF800836	FlexLED Repair set	-	-	-
605167	Safety Transformer 230Vac-42Vac 16A 315VA with 2 outlet, 3mtr cable + plug	-	-	-
605168	Safety Transformer 230Vac-42Vac 16A 630VA with 2 outlet, 5mtr cable + plug	-	-	-

