

## Hose Reels

### Heavy Duty Open Hose Reels

Heavy ribbed steel plate to ensure strong support. Spring located in the middle to ensure stability. For direction non-sag rollers to reduce wear abrasion. Adjustable guide arm for multi positional mounting. Special swivel joint for easy maintenance and repair. Ball bearing swivel joint structure, largely reducing friction. Dimensions 500x500x200mm. Pressure max. PN20 Bar.

Article No.	Description	Inlet	Outlet
609181	Incl. 15 mtr rubber air hose ID 10mm - 3/8"	3/8" BSPT	3/8" BSPT
609182	Without air hose reel only (max. capacity 15m)	-	-

Article No.	Description	Inlet	Outlet
609183	Incl. 15 mtr Hi-Vis PVC air and water hose ID 10mm - 3/8"	3/8" BSPT	3/8" BSPT

Article No.	Description	Inlet	Outlet
609184	Incl. 15 mtr Rubber Tech air and water hose ID 10mm - 3/8"	3/8" BSPT	3/8" BSPT

Article No.	Description	Inlet	Outlet
609185	Incl. 15 mtr rubber air hose ID 13mm - 1/2"	1/2" BSPT	1/2" BSPT
609185B	Without air hose reel only (max. capacity 15m)	-	-

Article No.	Description	Inlet	Outlet
609187	Incl. 15 mtr air and water R6 hose ID 13mm - 3/8"	1/2" BSPT	1/2" BSPT

### Heavy Duty Open Hose Reels

Dimensions 500x550x200mm. Pressure max. PN20 Bar.

Article No.	Description	Inlet	Outlet
609186	Incl. 20 mtr Hi-Vis PVC air and water hose ID 10mm - 3/8"	3/8" BSPT	3/8" BSPT

### Heavy Duty Open Hose Reels

Dimensions 500x600x500mm. Pressure max. PN20 Bar.

Article No.	Description	Inlet	Outlet
609190	Without air hose reel only (max. capacity 40m ID 19mm - 3/4")	-	-

### Heavy Duty HIGH PRESSURE Open Hose Reels spring rewind

Compact build, very suitable for limited spaces. Heavy duty construction with corrosion resistant powder coating. For direction non-sag rollers to reduce hose wear abrasion. Multi position ratchet lock and easy tension adjustment. Spring fully closed and lubricated. Full flow swivel. Adjustable guide arm for multi positioning mounting. Dimensions 500x500x200mm. Pressure max. PN150 Bar.

Article No.	Description	Inlet	Outlet
609188	Incl. 15 mtr black Jetwash R1 hose ID 10mm - 3/8"	3/8" BSP	M22x1.5
609188B	Without hose reel only (max. capacity 15m)	-	-

Article No.	Description	Inlet	Outlet
609191	Incl. 15 mtr blue Jetwash R1 hose ID 10mm - 3/8"	3/8" BSP	M22x1.5

### Heavy Duty HIGH PRESSURE Open Hose Reels manual rewind

Heavy duty construction with corrosion resistant powder coating. For direction non-sag rollers to reduce hose wear abrasion. Multi position ratchet lock and easy tension adjustment. Full flow swivel. Several mounting positions possible. Dimensions 400x480x400mm. Pressure max. PN270 Bar.

Article No.	Description	Inlet	Outlet
609189	Incl. 30 mtr blue Jetwash R2 hose ID 10mm - 3/8"	3/8" BSP	M22x1.5

Article No.	Description	Inlet	Outlet
609192	Incl. 30 mtr black Jetwash R2 hose ID 10mm - 3/8"	3/8" BSP	M22x1.5
609192B	Without hose reel only (max. capacity 30m)	-	-

Article No.	Description
609185W	Swivel mounting plate wall mount for 609185, 609186

### Extra Information

Contact our product specialists for more information.



## Hose Reels

### Faicom Open Manual Rewind Hose Reels type AM

For air and water. Frame with carry handle and wall mounting possible. Steel tube frame electrostatic powder coated. Scratch and UV resistant. Reel fully galvanized. For temperatures up to +40°C. Dimensions 280x310x285mm. Pressure max. PN20.

Article No.	Description	Inlet	Outlet
609211	Without hose reel only	1/4" BSP M	1/4" BSP F
609212	Incl. 30 mtr TPU air and water hose ID 8mm - 1/4"	1/4" BSP M	1/4" BSP M
609213	Incl. 40 mtr TPU air and water hose ID 8mm - 1/4"	1/4" BSP M	1/4" BSP M
609214	Incl. 25 mtr TPU air and water hose ID 10mm - 1/4"	3/8" BSP M	3/8" BSP M



### Faicom Industrial Closed Spring Rewind Hose Reels type MC

Suitable for air, water (hot and cold), oil and grease. For wall or ceiling mounting. **Excl. Inlet hose.** Optional 180° adjustable mounting bracket. Automatic rewind of the hose by spring located in the drum. The hose can be stopped at the desired length. High quality swivel on the drum for perfect sealing and smooth operation. Drum is hot-galvanized and coated with an electrostatic polyester powder coating resistant against UV rays. For temperatures up to +40°C. Dimensions 520x462x175mm. Pressure max. PN18. Hose SAE 100R6 for compressed air and water. Hose PU for compressed air. Other hose types on request.

Article No.	Description	Inlet	Outlet
609246	Incl. 10 mtr SAE 100R6 hose ID 8mm OD 14mm	3/8" BSP M	3/8" BSP F
609247	Incl. 15 mtr SAE 100R6 hose ID 8mm OD 14mm	3/8" BSP M	3/8" BSP F
609248	Incl. 20 mtr SAE 100R6 hose ID 8mm OD 14mm	3/8" BSP M	3/8" BSP F
609249	Incl. 10 mtr SAE 100R6 hose ID 10mm OD 17mm	3/8" BSP M	3/8" BSP F
609250	Incl. 15 mtr SAE 100R6 hose ID 10mm OD 17mm	3/8" BSP M	3/8" BSP F
609251	Incl. 10 mtr SAE 100R6 hose ID 13mm OD 20mm	1/2" BSP M	1/2" BSP M



Article No.	Description	Inlet	Outlet
609261	Incl. 20 mtr PU air hose ID 8mm OD 12mm	3/8" BSP M	3/8" BSP F
609262	Incl. 20 mtr PU air hose ID 10mm OD 14mm	3/8" BSP M	3/8" BSP F
609263	Incl. 15 mtr PU air hose ID 13mm OD 18mm	1/2" BSP M	1/2" BSP M
609251C	Inlet hose ID 8mm OD 14mm L=500mm	3/8" BSP M	3/8" BSP F
609251D	Inlet hose ID 13mm OD 20mm L=500mm	1/2" BSP F	1/2" BSP F
609251E	Inlet hose ID 10mm OD 17mm L=500mm	3/8" BSP M	3/8" BSP F
609251B	Adjustable mounting bracket 180° for type MC	-	-



### Zeca 804 Closed Spring Rewind Hose Reel

Impact resistant ABS plastic casing. Smooth reinforced KPU hose. Connection nipple with male BSP thread. Complete with pivot bracket for mounting. Automatic hose ratched stop device, easily removable if constant traction is required. For temperatures from -5°C to +40°C. Dimensions 310x125mm. Pressure max. PN15. Hose for compressed air and water.

Article No.	Description	Inlet	Outlet
609240	Incl. 9+1 mtr KPU air and water hose ID 8mm - 1/4"	1/4" BSP M	1/4" BSP M



### Zeca 813 Closed Spring Rewind Hose Reel

Diecast aluminium casing with matt finish. Bimaterial hose PVC with PU inner hose and large inner diameter, colour blue. Connection nipple with male BSP thread. Complete with pivot bracket for mounting. Automatic hose ratched stop device, easily removable if constant traction is required. For temperatures from -5°C to +40°C. Dimensions 360x175mm. Pressure max. PN15. Hose for compressed air and water.

Article No.	Description	Inlet	Outlet
609242	Incl. 10+2 mtr PVC air and water hose ID 8mm - 1/4"	1/4" BSP M	1/4" BSP F
609243	Incl. 7+2 mtr PVC air and water hose ID 10mm - 3/8"	3/8" BSP M	3/8" BSP F



### Zeca 805 Closed Spring Rewind Hose Reel

Impact resistant ABS plastic casing. Smooth reinforced KPU hose. Connection nipple with male BSP thread. Complete with pivot bracket for mounting. Automatic hose ratched stop device, easily removable if constant traction is required. For temperatures from -5°C to +40°C. Dimensions 380x205mm. Pressure max. PN15. Hose for compressed air and water.

Article No.	Description	Inlet	Outlet
609244	Incl. 15+1 mtr KPU air and water hose ID 8mm - 1/4"	1/4" BSP M	1/4" BSP F
609245	Incl. 15+1 mtr PVC air and water hose ID 10mm - 3/8"	3/8" BSP M	3/8" BSP F



### Airpro Closed Spring Rewind Hose Reel

For wall or ceiling mounting. Steel coated casing. Steel adjustable mounting bracket. Casing protected with a powder coating. Heavy duty spring rewinds automatically to hose on the reel. Brass connections 360° adjustable. Hose connection brass with BSP male thread. For temperatures from -5°C to +40°C. Pressure max. PN15. Hose for compressed air and water.

Article No.	Description	Inlet	Outlet
609295	Incl. 10 mtr PU air hose ID 8mm - 1/4"	1/4" BSP M	1/4" BSP M

## Hose Reels

### Open Manual Rewind Hose Reel

Reinforced steel tube construction, powder coated. Complete reel is 360° adjustable at his base plate. Foldable winding handle. Kink resistant PU hose. For temperatures from -50°C to +60°C. Pressure max. PN20.

Article No.	Description	Inlet	Outlet
609197	Incl. 30 mtr blue air hose ID 8mm - 1/4"	1/4" BSP M	1/4" BSP M



### GARDENA Hose Reels for Water

Good quality hose reels empty or complete with high quality water hoses. As reel with a carry handle. A full range of hose connectors and other accessories from Gardena can be supplied.

Article No.	Description	Inlet	Outlet
931049825	Hose reel 8007-20 without hose reel only Capacity for 50 mtr 1/2", 40 mtr 5/8" or 30 mtr 3/4" hose.	1/2" BSP M	1/2" BSP M

Article No.	Description	Inlet	Outlet
931087218	Hose reel 2687-20 with 15 mtr 1/2" Classic hose and accessories as connection pieces and spray gun. Max. capacity is 30 mtr 1/2" hose.	1/2" BSP M	1/2" BSP M



### REELWORKS 460 Open Manual Hose Reel

Developed for industrial applications. Housing made from heavy duty sheet steel protected with powder coating. Full flow inlet for maximum flow. Locking pin with spring for drum locking. Can be mounted in all directions. Comes without hose, reel only. Pressure max. PN200.

Article No.	Description	Inlet	Outlet
609202	Empty reel with capacity 105 mtr hose ID 10mm	3/8" BSP M	3/8" BSP M
609203	Empty reel with capacity 80 mtr hose ID 12,5mm	1/2" BSP M	1/2" BSP M



### RAMEX Automatic and Manual Hose Reels for Fuels

A complete range of high quality hose reels made from steel or stainless steel. Fuel and oil resistant special hoses. Delivery guns can also be ordered. All on request.

