

Electrical Indoor Distribution Blocks

DISTRIBUTION BLOCK or Multiway receptacles 230V 16A for indoor use

To use on all portable equipment. White polypropylene cover. According to VDE 0620-1:2005 and DIN 49 440 Part 1 Cable type H05VV-F. Max. Voltage 250V and 16A.

Article No.	Cable	Length mtr.	Number of sockets	IMPA
770339	3x1.5mm ²	1.5	2	79 29 63
770340	3x1.5mm ²	3	3	79 29 65
770341	3x1.5mm ²	1.5	4	79 29 67
770342	-	-	3	-
770343	-	-	4	-



DISTRIBUTION BLOCK or Multiway receptacles 230V 16A for indoor use

To use on all portable equipment. Polyamide PA 6 cover. According to VDE 0620-1:2005 and DIN 49 440 Part 1 Cable type H05VV-F. Max. Voltage 250V and 16A. Protection IP20. With illuminated on/off switch. * = Without switch

Article No.	Cable	Length mtr.	Number of sockets	IMPA
780300	3x1.5mm ²	3	4	79 29 67
780304A	3x1.5mm ²	5	10	-
780302	3x1.5mm ²	1.5	6	-
780303	3x1.5mm ²	1.5	8 *	-
780304	3x1.5mm ²	1.5	10 *	-



DISTRIBUTION BLOCK or Multiway receptacles 230V 16A for indoor use with overvoltage protection

To use on all portable equipment. Polyamide PA 6 cover. According to VDE 0620-1:2005 and DIN 49 440 Part 1 With overvoltage protection and interference filter 6.5Amp. * = Standard for 19" rack mounting Cable type H05VV-F. Max. Voltage 250V and 16A. Protection IP20. With illuminated on/off switch.

Article No.	Cable	Length mtr.	Number of sockets	IMPA
780306	3x1.5mm ²	3	6	-
780306A	3x1.5mm ²	3	6 *	-



Electrical Plugs Watertight

PLUGS and CONNECTORS Solid Rubber 230/250V 16A

Rubber plugs and connectors suitable for heavy duty industrial applications. Large wiring space, it can easily be connected up to wires 3x2.5mm². Plugs features a double earthing system according to SCHUKO and French/Belgium standards. Heat, frost and UV-resistant as well splash protected according to IP44. Max. Voltage 250V and 16A. * = With voltage indicator.

Article No.	Type	Standard	Number of sockets	IMPA
770330	Rubber short male plug	Schuko	-	-
770331	Rubber short female connector	Schuko	1	-
770330ABL	Rubber male plug	Schuko + F/B	-	-
770331ABL	Rubber female connector	Schuko	1	-
770334	Rubber female connector + cover	Schuko	1	-
770333	Rubber female triple suspended connector + cover	Schuko	3	-
77ABL1173503	Rubber female tripple suspended connector + self-closing black cover	Schuko	3 *	-
77ABL1173543	Rubber female tripple suspended connector + self-closing red cover	Schuko	3 *	-
77ABL1173563	Rubber female tripple suspended connector + self-closing grey cover	Schuko	3 *	-



PLUGS and CONNECTORS Solid Rubber 230/250V 16A ABL-SURSUM

Elamid 2-component technology, 2 earthing systems, quick-release mechanism. Very good grip, especially robust. Top of the range heavy duty in industrial applications. Large wiring space, it can easily be connected up to wires 3x2.5mm². Plugs features a double earthing system according to SCHUKO and French/Belgium standards. Heat, frost and UV-resistant as well splash protected according to IP54. Max. Voltage 250V and 16A. * = With voltage indicator.

Article No.	Type	Standard	IMPA
77ABL1529100	2-component male black plug	Schuko + F/B	-
77ABL1529140	2-component male red plug	Schuko + F/B	-
77ABL1529160	2-component male grey plug	Schuko + F/B	-
77ABL1589200	2-component female black connector	Schuko + F/B *	-
77ABL1589240	2-component female red connector	Schuko + F/B *	-
77ABL1589260	2-component female grey connector	Schuko + F/B *	-



Electrical Plugs Watertight

PLUGS and CONNECTORS Solid Rubber 230/250V 16A ABL-SURSUM

Elamid high performance plastic, 2 earthing systems. Very good grip, and very sturdy. Top of the range heavy duty in industrial applications. Large wiring space, it can easily be connected up to wires 3x2.5mm². Plugs features a double earthing system according to SCHUKO and French/Belgium standards. Also features kink protection for the cable and cable seal. Heat, frost and UV-resistant as well splash protected according to IP44. Max. Voltage 250V and 16A.

* = Connector with cover



Article No.	Type	Standard	IMPA
77ABL1519150	Elamid HD male blue plug	Schuko + F/B	-
77ABL1519140	Elamid HD male red plug	Schuko + F/B	-
77ABL1519100	Elamid HD male black plug	Schuko + F/B	-
77ABL1579150	Elamid HD female blue connector	Schuko + F/B	-
77ABL1579140	Elamid HD female red connector	Schuko + F/B	-
77ABL1579100	Elamid HD female black connector	Schuko + F/B	-
77ABL1579350	Elamid HD female blue connector *	Schuko + F/B	-
77ABL1579340	Elamid HD female red connector *	Schuko + F/B	-
77ABL1579300	Elamid HD female black connector *	Schuko + F/B	-



Electrical Plugs Indoor use

PLUGS and CONNECTORS Indoor 230/250V 16A

PVC and Duroplast white male Schuko plugs and female connectors. Protected according to IP20. UV resistant. Max. Voltage 250V and 16A. 2-pole + earth. Only for indoor use.

Article No.	Type	Standard	IMPA
770335	Male Plug Duroplast white	Schuko	79 29 21
770338	Female Connector Duroplast white	Schuko	79 29 35
770335ABLW	Male Plug PVC white	Schuko + F/B	79 29 21
770338ABLW	Female Connector PVC white	Schuko	79 29 35
770335H	Male Plug PVC black 90 degree entry	Schuko	-
770335HW	Male Plug PVC white 90 degree entry	Schuko	-



TRAVEL PLUGS Indoor

PVC white travel plugs. Protected according to IP20, 2-pole + Earth. UV resistant. Only for indoor use.

Article No.	Type	Amperé	IMPA
77178554	Travel Plug white EU to UK	13 Amp	-
770337B	Travel Plug white UK to EU	13 Amp	-
770337C	Travel Plug white EU to USA	15 Amp 125V	-



REDUCING PLUGS Indoor

PVC white plugs. Protected according to IP20, 2-pole + Earth. UV resistant. Only for indoor use.

Article No.	Type	Amperé	IMPA
770350	Two-way Plug Schuko to 2 x EURO	2.5 Amp	-
770338KWS	Two-way Plug Schuko to 2 x Schuko vertical	16 Amp	-
770338KWH	Two-way Plug Schuko to 2 x Schuko horizontal	16 Amp	79 29 30

