

## Industrial ladders Dirks

### Single straight ladder Dirks type DOE & DGE

Industrial robust ladder with a 28 cm wide tread surface and ergonomically-shaped rungs.

According to NEN 2184 / EN 131

An optimum rung-stile connection is achieved by means of an ingenious folding and flaring technique. Solid plastic ladder foot, manufactured from PVC, has a long lifetime and is oil and weather proof, also ozone resistant.

The type DOE is made of high quality uncoated aluminium.

The DGE is made of high quality coated aluminium for extra cleanliness during use.

Accessories and spare parts available.



Article No.	Description	Number of Steps	Length	Weight
632001	DOE 08 uncoated	8	2.45m	4.5 kg
632002	DOE 10 uncoated	10	3.00m	5.5 kg
632003	DOE 12 uncoated	12	3.60m	7.0 kg
632004	DOE 14 uncoated	14	4.15m	7.5 kg
632005	DOE 16 uncoated	16	4.70m	10.5 kg
632006	DOE 18 uncoated	18	5.25m	12.5 kg
632007	DOE 20 uncoated	20	5.80m	13.5 kg
632008	DOE 21 uncoated	21	6.10m	14.0 kg

Article No.	Description	Number of Steps	Length	Weight
632001C	DGE 08 coated	8	2.45m	4.5 kg
632002C	DGE 10 coated	10	3.00m	5.5 kg
632003C	DGE 12 coated	12	3.60m	7.0 kg
632004C	DGE 14 coated	14	4.15m	7.5 kg
632005C	DGE 16 coated	16	4.70m	10.5 kg
632006C	DGE 18 coated	18	5.25m	12.5 kg
632007C	DGE 20 coated	20	5.80m	13.5 kg
632008C	DGE 21 coated	21	6.10m	14.0 kg



### Stabilizer for Dirks straight Ladders

The stabilizer provide extra stability to the ladder and so enhanced user safety.

According to NEN 2184 / EN 131

Easy to connect to the ladder.

Article No.	Description
63DKSB0000	Dirks stabilizer for straight ladders



### Single straight ladder with bent rungs Dirks type DOU & DGU

Industrial robust ladder with a 28 cm wide tread surface and ergonomically-shaped rungs.

Same as above but with bent ladder rungs for enhanced stability.

According to NEN 2184 / EN 131

An optimum rung-stile connection is achieved by means of an ingenious folding and flaring technique.

Solid plastic ladder foot, manufactured from PVC, has a long lifetime and is oil and weather proof, also ozone resistant.

The type DOU is made of high quality uncoated aluminium.

The DGU is made of high quality coated aluminium for extra cleanliness during use.

Accessories and spare parts available.

Article No.	Description	Number of Steps	Length	Weight
632030	DOU 08 uncoated	8	2.45m	4.5 kg
632031	DOU 10 uncoated	10	3.00m	5.5 kg
632032	DOU 12 uncoated	12	3.60m	7.0 kg
632033	DOU 14 uncoated	14	4.15m	7.5 kg
632034	DOU 16 uncoated	16	4.70m	10.5 kg
632035	DOU 18 uncoated	18	5.25m	12.5 kg
632036	DOU 20 uncoated	20	5.80m	13.5 kg
632037	DOU 21 uncoated	21	6.10m	14.0 kg

Article No.	Description	Number of Steps	Length	Weight
632030C	DGU 08 coated	8	2.45m	4.5 kg
632031C	DGU 10 coated	10	3.00m	5.5 kg
632032C	DGU 12 coated	12	3.60m	7.0 kg
632033C	DGU 14 coated	14	4.15m	7.5 kg
632034C	DGU 16 coated	16	4.70m	10.5 kg
632035C	DGU 18 coated	18	5.25m	12.5 kg
632036C	DGU 20 coated	20	5.80m	13.5 kg
632037C	DGU 21 coated	21	6.10m	14.0 kg

## Industrial ladders Dirks

### Two piece push up ladder with bent rungs Dirks type DOU & DGU

Industrial robust ladder with a 28 cm wide tread surface and ergonomically-shaped rungs.

Bent ladder rungs for enhanced stability.

Smoothly and easily extending thanks to the plastic guides.

According to NEN 2184 / EN 131

An optimum rung-stile connection is achieved by means of an ingenious folding and flaring technique.

Solid plastic ladder foot, manufactured from PVC, has a long lifetime and is oil and weather proof, also ozone resistant.

Each section of a multi-part Dirks ladder can be used separately thanks to the patented slide-out system

The type DOU is made of high quality uncoated aluminium.

The DGU is made of high quality coated aluminium for extra cleanliness during use.

Accessories and spare parts available.

\* = with top rollers

Article No.	Description	Number of Steps	Length Retracted	Length Extended	Weight
632048	DOU 2x07 uncoated	2x7	2.19m	3.60m	9.5 kg
632049	DOU 2x08 uncoated	2x8	2.47m	4.15m	10.5 kg
632050	DOU 2x09 uncoated	2x9	2.75m	4.70m	11.0 kg
632051	DOU 2x10 uncoated	2x10	3.03m	5.25m	12.5 kg
632052	DOU 2x12 uncoated	2x12 *	3.60m	6.10m	17.5 kg
632053	DOU 2x14 uncoated	2x14 *	4.16m	7.25m	20.0 kg

Article No.	Description	Number of Steps	Length Retracted	Length Extended	Weight
632049C	DGU 2x08 coated	2x8	2.47m	4.15m	10.5 kg
632051C	DGU 2x10 coated	2x10	3.03m	5.25m	12.5 kg
632052C	DGU 2x12 coated	2x12 *	3.60m	6.10m	17.5 kg
632053C	DGU 2x14 coated	2x14 *	4.16m	7.25m	20.0 kg



Repair Management Nederland B.V.  
More management less firefighting

### Two and three piece push up combination ladder with bent rungs Dirks type DOR & DGR

Industrial robust ladder with a 28 cm wide tread surface and ergonomically-shaped rungs.

Bent ladder rungs for enhanced stability. Can be used free-standing

Smoothly and easily extending thanks to the plastic guides.

According to NEN 2184 / EN 131

An optimum rung-stile connection is achieved by means of an ingenious folding and flaring technique.

Solid plastic ladder foot, manufactured from PVC, has a long lifetime and is oil and weather proof, also ozone resistant.

Each section of a multi-part Dirks ladder can be used separately thanks to the patented slide-out system

The type DOR is made of high quality uncoated aluminium.

The DGR is made of high quality coated aluminium for extra cleanliness during use.

Accessories and spare parts available.

\* = with top rollers

Article No.	Description	Number of Steps	Length Retracted	Length Extended	Weight
63DKOR0208	DOR 2x08 uncoated	2x8	2.47m	4.15m	10.5 kg
63DKOR0210	DOR 2x10 uncoated	2x10	3.03m	5.25m	12.5 kg
63DKOR0212	DOR 2x12 uncoated	2x12 *	3.60m	6.10m	17.5 kg
63DKOR0214	DOR 2x14 uncoated	2x14 *	4.16m	7.25m	20.0 kg



Article No.	Description	Number of Steps	Length Retracted	Length Extended	Weight
63DKOR0208C	DGR 2x08 coated	2x8	2.47m	4.15m	10.5 kg
63DKOR0210C	DGR 2x10 coated	2x10	3.03m	5.25m	12.5 kg
63DKOR0212C	DGR 2x12 coated	2x12 *	3.60m	6.10m	17.5 kg
63DKOR0214C	DGR 2x14 coated	2x14 *	4.16m	7.25m	20.0 kg

Article No.	Description	Number of Steps	Length Retracted	Length Extended	Weight
63DKOR0308	DOR 3x08 uncoated	3x8	2.47m	5.85m	17.0 kg
63DKOR0310	DOR 3x10 uncoated	3x10 *	3.04m	7.00m	24.0 kg
63DKOR0312	DOR 3x12 uncoated	3x12 *	3.60m	8.65m	30.5 kg
63DKOR0314	DOR 3x14 uncoated	3x14 *	4.17m	10.05m	34.5 kg

Article No.	Description	Number of Steps	Length Retracted	Length Extended	Weight
63DKOR0308C	DGR 3x08 coated	3x8	2.47m	5.85m	17.0 kg
63DKOR0310C	DGR 3x10 coated	3x10 *	3.04m	7.00m	24.0 kg
63DKOR0312C	DGR 3x12 coated	3x12 *	3.60m	8.65m	30.5 kg
63DKOR0314C	DGR 3x14 coated	3x14 *	4.17m	10.05m	34.5 kg



## Industrial ladders Dirks

### Wäku Telescopic folding ladder WKTL

Ideal ladder for every service engineer.

According to NEN 2184 / EN 131

Due to its small retracted size it is ideal to fit in a service van or to store the ladder in a small space.

Solid plastic ladder foot, manufactured from PVC, has a long lifetime and is oil and weather proof, also ozone resistant.

Article No.	Description	Number of Steps	Length Retracted	Length Extended	A-stand Height	Weight
631048	WKTL0403	4x3	1.02m	3.10m	1.34m	10 kg
631049	WKTL0404	4x4	1.29m	4.20m	1.86m	13 kg
631050	WKTL0405	4x5	1.57m	5.30m	2.40m	16 kg
631051	WKTL0406	4x6	1.85m	6.40m	2.92m	20 kg



### Boat Boarding ladder

Aluminium ladder, with extra reinforcement against bending (from 8 rungs ladder and longer).

Width between the ladder rungs 295 mm.

Total Width 355 mm.

Optional available a support guide for mounting on top of the ladder.

The support guide comes with stainless steel fastening materials.

Article No.	Description	Number of Steps	Length	Weight
637003	Boarding ladder BL3	3	0.94m	3.5 kg
637004	Boarding ladder BL4	4	1.19m	4.0 kg
637005	Boarding ladder BL5	5	1.48m	4.2 kg
637006	Boarding ladder BL6	6	1.70m	5.4 kg
637007	Boarding ladder BL7	7	1.93m	5.9 kg
637008	Boarding ladder BL8	8	2.05m	7.3 kg
637009	Boarding ladder BL9	9	2.38m	7.6 kg
637010	Boarding ladder BL10	10	2.61m	8.1 kg
637011	Boarding ladder BL11	11	2.83m	8.7 kg
637012	Boarding ladder BL12	12	3.07m	9.6 kg
637013	Boarding ladder BL13	13	3.30m	10.5 kg
637014	Boarding ladder BL14	14	3.54m	10.9 kg
637015	Boarding ladder BL15	15	3.63m	12.0 kg
637016	Boarding ladder BL16	16	3.90m	13.0 kg
637017	Boarding ladder BL17	17	4.19m	14.0 kg
637018	Support guide for BL ladder	-	-	-



### Boat Boarding ladder Heavy Duty for Tankers

Heavy Duty Aluminium ladder with anti-slip surface ladder steps

Width between the ladder rungs 360 mm.

Total Width 460 mm.

Complete with ladder guide.

Extra reinforced against bending.

Article No.	Description	Number of Steps	Length	Weight
637025	Boarding ladder BT15	15	4.30m	14 kg
637027	Boarding ladder BT17	17	4.80m	15 kg
637029	Boarding ladder BT19	19	5.30m	16 kg



### Support guide for Dirks Ladders

As a telescopic arm, connected to the top section a ladder. Length up to 1100 mm.

According to NEN 2184 / EN 131

Easy to connect to the ladder.

Allows the user to enter the roof more safely from the ladder and step back on the ladder.

Article No.	Description
63DKTL1100	Dirks Support guide for straight ladders

