

Kira ATEX Flashlight NON-Rechargeable LED Zone 1, 2, 21, 22

Kira Leuchten GmbH type MHL-5-EX FLASHLIGHT
EXPLOSION-PROOF NON-RECHARGEABLE FLASHLIGHT FOR ZONE 1, 2, 21, 22

Mini flashlight for explosion-proof areas:

The MHL 5 EX high-power LED flashlight sets new standards with its shockproof and waterproof plastic housing (IP68). This compact flashlight, at just 14.5 cm long and a feather-light weight of just 45 g, redefines the pinnacle of comparable mini flashlights. The MHL 5 EX combines outstanding performance with a compact design and is perfect for a wide range of applications.

Small and robust:

The robust plastic housing gives the explosion-proof MHL 5 EX flashlight exceptional resistance to shock and water, making it a reliable companion in a wide variety of environments. Whether for outdoor activities, professional use or in emergency situations, this explosion-proof light is at your side with reliable lighting.

Batteries included:

With a lighting time of around 4 hours, the EX light offers an impressive lighting time thanks to the 2 micro batteries (AAA) included in delivery. This practical power supply ensures quick commissioning and allows you to immediately benefit from the powerful high-power LED. The flashlight is therefore always ready for use and ready to flood your surroundings with bright light.

Light and handy:

The MHL 5 EX flashlight is characterized not only by its functionality, but also by its handy size and minimal weight. These features make it a premium mini flashlight that fits comfortably in your bag, on your belt, or in your jacket pocket. This means you always have the MHL 5 EX at hand when you need it.

Experience the perfect combination of performance, compactness and reliability with the MHL 5 EX. This explosion-proof light is not just a light source, but a reliable companion for anyone looking for a compact, powerful flashlight for various applications.



INDEX



Technical specifications:

- Battery:** 2x AAA batteries included
- IP Protection Class:** IP68
- Impact Resistant housing:** Plastic composite
- Weight:** Approx. 45gr.
- Headlight range:** Approx. 30m
- Light level:** 42 lumen
- Flash function:** No
- Duration:** Approx. 4h
- Type LED's:** Power LED
- Headlight:** Not adjustable
- Tamb:** T4
- Others:** Submersible till 3 mtr

Application areas:

- Rescue
- Sewer cleaning
- Shipping
- Offshore
- Many areas with harsh environment conditions

ATEX Identification:

II 2 G Ex ib IIC T4 Ga(Gas)
II 2 D Ex ib IIIC T135°C Da (Dust)
Tool group: II
Category: 2G / 2D
Approvals: ATEX Zone 1, 2, 21, 22
ATEX Number: TÜV-A 13ATEX0004X



Dimensions:

a x b (in mm) 145 x 20



Article No.	Description	Charger	Range	Lumen	IP Class
89KRL290649	Acculux MHL 5 EX - Battery Version Zone 1 , 2, 21, 22 (2x AAA battery)	-	30 m	42 lm	IP68

