

KIRA Leuchten Hand Lamp KE-4010-LED IP65

Kira Leuchten GmbH type KE-4010-LED Hand Lamp IP65
DUST & WATER PROTECTED TUBE LIGHT 230V - 110V - 42V - 24V



The KE-LED 4010 industrial hand lamp represents the further development of the proven 4010 professional version and sets new standards for robust and powerful lighting in industrial applications. With 10 POWER LED modules, it guarantees outstanding luminous efficacy to meet the requirements of demanding industrial environments.

Glare-free work:

The impact-resistant polycarbonate protective tube of the KE-LED 4010 industrial hand lamp is equipped with an integrated diffuser film that ensures glare-free work. This innovative technology makes it possible to create clear visibility and optimal working conditions by minimizing annoying glare.

Durable and resistant:

The industrial version of this rod light has a robust and durable neoprene handle as well as a neoprene end cap with an integrated metal hanging hook. These features make the work light particularly durable and resistant to the challenges of industrial environments. Upon request, the LED light is available with an on/off switch integrated into the handle to make operation even easier.



Dustproof & water jet protected:

The KE-LED 4010 industrial hand lamp meets the industry standard with a supply cable in H07RN-F specification and an impressive IP65 protection rating. This protection class makes the luminaire ideal for use in industrial applications and areas where robust, splash-proof and jet-proof lighting solutions are required.

The KE-LED 4010-P Industry is the perfect mobile work light that can withstand the demands of industrial environments.

Tackle your tasks with maximum brightness, reliability and robustness. Trust the KE-LED 4010 industrial hand lamp to illuminate your industrial applications with clear, bright light and increase the efficiency of your work processes.

Typical applications:

- Heavy Industry and Shipyards
- Maritime and Offshore
- Tank Cleaning
- Car & Truck Repair Service

Technical specifications:

Nominal voltage: 230 - 110 - 42 - 24 V

Current: 0,04 up to 0,31 A

IP Protection Class: IP65

Impact Resistance: IK10

Protection Class: Class II/III

Weight: Approx. 0,75 kg

Tamb: -20°C - +40°C

Number of LED's: 10

Lifetime LED: >50.000h

Power: Depend on voltage

Real lumen: Depend on voltage

Light colour: 5.000K

Colour rendering: >70

Diffuser: Integrated diffuser film

Protective tube: Polycarbonate IK10

End Caps & handle: Neoprene


Hook: Metal rotatable

Cable: 5 mtr H07RN-F 2x1,5 mm²

Plug: 230V with and 110 - 42 - 24V w/o

MADE IN GERMANY

Dimensions:



a - b - c - d - e - f - g - h (in mm)

45 - 70 - 240 - 115 - 40 - 65 - 40 - 510



With a 360° rotatable sturdy metal hook



Article numbers 230 Vac

Article No.	Description	Voltage	Colour	Wattage	Lumen	Current
89KRL131429	KE-4010-LED with 5m cable H07RN-F 2x1,5 mm ² with plug	230 Vac	5.000K	7,4 W	780 lm	0,04 A
89KRL131459	KE-4010-LED with 10m cable H07RN-F 2x1,5 mm ² with plug	230 Vac	5.000K	7,4 W	780 lm	0,04 A

Article numbers 42 Vac/dc

There are multiple KIRA SELV safety transformers available.

Article No.	Description	Voltage	Colour	Wattage	Lumen	Current
89KRL131431	KE-4010-LED with 5m cable H07RN-F 2x1,0 mm ² w/o plug	42 V AC/DC	6.500K	8,0 W	850 lm	0,175A
89KRL131431C	KE-4010-LED with 5m cable H07RN-F 2x1,0 mm ² with CEE plug	42 V AC/DC	6.500K	8,0 W	850 lm	0,175 A
89KRL131442	KE-4010-LED with 10m cable H07RN-F 2x1,0 mm ² w/o plug	42 V AC/DC	6.500K	8,0 W	850 lm	0,175 A
89KRL131442C	KE-4010-LED with 10m cable H07RN-F 2x1,0 mm ² with CEE plug	42 V AC/DC	6.500K	8,0 W	850 lm	0,175 A

Accessories:

Article No.	Description
89KRL290700	Protective foil, SFO-LED-4010
89KRL290056	Mounting bracket (1 pcs) BFK D40
89KRL290600	Magnetic bracket (1 pcs) KM 40

