

## KIRA Leuchten Safety Transformers

### Kira Leuchten GmbH Transformers for protective low (SLEV) in portable housing

IP44 protected housings.

KIRA range of Transformers for prim. 230V to sec. 24V and 42V.  
KIRA range of Isolating Transformers 230V to 230V.



#### Reliable and safe:

With its IP44 high quality plastic or rubber housing with 1 of multiple socket outlets you can easily use your low voltage KIRA work lights and hand lamps in a safe way. With its low weight from 1,3 kg up to 7.0 kg the transformers are easy to handle at each work location.

#### Typical applications:

- Heavy Industry and Shipyards
- Maritime and Offshore
- Tank Cleaning
- Car & Truck Repair Service



#### Article numbers SELV types

| Article No. | Description               | Prim. Voltage | Sec. Voltage | Number of Sockets | Power  | Housing material | Weight Kg |
|-------------|---------------------------|---------------|--------------|-------------------|--------|------------------|-----------|
| 89KRL141130 | Transformer SELV 25/1-12  | 230 V         | 12 V         | 1x                | 25 VA  | Plastic          | 1,30 kg   |
| 89KRL141133 | Transformer SELV 25/1-24  | 230 V         | 24 V         | 1x CEE            | 25 VA  | Rubber KV10      | 1,30 kg   |
| 89KRL141124 | Transformer SELV 60/1-24  | 230 V         | 24 V         | 1x CEE            | 60 VA  | Rubber KV10      | 2,60 kg   |
| 89KRL141100 | Transformer SELV 100/1-24 | 230 V         | 24 V         | 1x CEE            | 100 VA | Rubber KV11      | 3,60 kg   |
| 89KRL141160 | Transformer SELV 160/2-24 | 230 V         | 24 V         | 2x CEE            | 160 VA | Rubber KV11      | 5,60 kg   |
| 89KRL141170 | Transformer SELV 250/2-24 | 230 V         | 24 V         | 2x CEE            | 250 VA | Rubber KV11      | 6,00 kg   |
| 89KRL141128 | Transformer SELV 250/4-24 | 230 V         | 24 V         | 4x CEE            | 250 VA | Rubber KV11      | 7,00 kg   |
| 89KRL141135 | Transformer SELV 25/1-42  | 230 V         | 42 V         | 1x CEE            | 25 VA  | Plastic          | 1,30 kg   |
| 89KRL141142 | Transformer SELV 60/1-42  | 230 V         | 42 V         | 1x CEE            | 60 VA  | Rubber KV10      | 2,60 kg   |
| 89KRL141200 | Transformer SELV 100/1-42 | 230 V         | 42 V         | 1x CEE            | 100 VA | Rubber KV10      | 3,60 kg   |
| 89KRL141210 | Transformer SELV 160/2-42 | 230 V         | 42 V         | 2x CEE            | 160 VA | Rubber KV11      | 5,60 kg   |
| 89KRL141211 | Transformer SELV 250/2-42 | 230 V         | 42 V         | 2x CEE            | 250 VA | Rubber KV11      | 6,00 kg   |
| 89KRL141134 | Transformer SELV 250/4-42 | 230 V         | 42 V         | 4x CEE            | 250 VA | Rubber KV11      | 7,00 kg   |



Plastic housing



Plastic housing



Rubber housing KV10



Rubber housing KV11

#### Article numbers TRAF0 types

For Isolating transformers only one socket plug on secondary side permissible. To prevent electric shock in wet environments, such as basements, construction sites or metal tanks.

| Article No. | Description                           | Prim. Voltage | Sec. Voltage | Number of Sockets | Power  | Housing material | Weight Kg |
|-------------|---------------------------------------|---------------|--------------|-------------------|--------|------------------|-----------|
| 89KRL141300 | Isolating Transformer TRAF0 100/1-230 | 230 V         | 230 V        | 1x CEE            | 100 VA | Rubber           | 3,60 kg   |
| 89KRL141131 | Isolating Transformer TRAF0 160/1-230 | 230 V         | 230 V        | 1x CEE            | 160 VA | Rubber           | 5,60 kg   |
| 89KRL141250 | Isolating Transformer TRAF0 250/1-230 | 230 V         | 230 V        | 1x CEE            | 250 VA | Rubber           | 6,00 kg   |

