

Lifting Equipment Polyester Slings

Estil Polyester Slings with both sides a loop Series PH

Safety factor 7:1, according to pr. NEN-EN 1492-1 and machine guidelines 98/37/EG chapter IIA.

Double webbing layers with 2 reinforced loops. Color code, tonnage stripes and tonnage print.

Professional sling for use in industrial applications. Use always protecting covers or protective corners at sharp corners or edges. All loops are reinforced.



Article No.	W.L.L. Tons	Type	Colour	Working length mtr	IMPA	Article No.	W.L.L. Tons	Type	Colour	Working length mtr	IMPA
66PH03001	1	PH30	Purple	1	23 21 31	66PH06001	2	PH60	Green	1	23 21 43
66PH03002	1	PH30	Purple	2	23 21 32	66PH06002	2	PH60	Green	2	23 21 44
66PH03003	1	PH30	Purple	3	23 21 33	66PH06003	2	PH60	Green	3	23 21 45
66PH03004	1	PH30	Purple	4	23 21 34	66PH06004	2	PH60	Green	4	23 21 46
66PH03005	1	PH30	Purple	5	23 21 35	66PH06005	2	PH60	Green	5	23 21 47
66PH03006	1	PH30	Purple	6	23 21 36	66PH06006	2	PH60	Green	6	23 21 48
66PH03007	1	PH30	Purple	7	-	66PH06007	2	PH60	Green	7	-
66PH03008	1	PH30	Purple	8	-	66PH06008	2	PH60	Green	8	-
66PH03009	1	PH30	Purple	9	-	66PH06009	2	PH60	Green	9	-
66PH03010	1	PH30	Purple	10	-	66PH06010	2	PH60	Green	10	-

Article No.	W.L.L. Tons	Type	Colour	Working length mtr	IMPA	Article No.	W.L.L. Tons	Type	Colour	Working length mtr	IMPA
66PH09001	3	PH90	Yellow	1	23 21 71	66PH12001	4	PH120	Grey	1	-
66PH09002	3	PH90	Yellow	2	23 21 72	66PH12002	4	PH120	Grey	2	-
66PH09003	3	PH90	Yellow	3	23 21 73	66PH12003	4	PH120	Grey	3	-
66PH09004	3	PH90	Yellow	4	23 21 74	66PH12004	4	PH120	Grey	4	-
66PH09005	3	PH90	Yellow	5	23 21 75	66PH12005	4	PH120	Grey	5	-
66PH09006	3	PH90	Yellow	6	23 21 76	66PH12006	4	PH120	Grey	6	-
66PH09007	3	PH90	Yellow	7	-	66PH12007	4	PH120	Grey	7	-
66PH09008	3	PH90	Yellow	8	-	66PH12008	4	PH120	Grey	8	-
66PH09009	3	PH90	Yellow	9	-	66PH12009	4	PH120	Grey	9	-
66PH09010	3	PH90	Yellow	10	-	66PH12010	4	PH120	Grey	10	-

Article No.	W.L.L. Tons	Type	Colour	Working length mtr	IMPA	Article No.	W.L.L. Tons	Type	Colour	Working length mtr	IMPA
66PH15001	5	PH150	Red	1	-	66PH18001	6	PH180	Brown	1	-
66PH15002	5	PH150	Red	2	-	66PH18002	6	PH180	Brown	2	-
66PH15003	5	PH150	Red	3	-	66PH18003	6	PH180	Brown	3	-
66PH15004	5	PH150	Red	4	-	66PH18004	6	PH180	Brown	4	-
66PH15005	5	PH150	Red	5	-	66PH18005	6	PH180	Brown	5	-
66PH15006	5	PH150	Red	6	-	66PH18006	6	PH180	Brown	6	-
66PH15007	5	PH150	Red	7	-	66PH18007	6	PH180	Brown	7	-
66PH15008	5	PH150	Red	8	-	66PH18008	6	PH180	Brown	8	-
66PH15009	5	PH150	Red	9	-	66PH18009	6	PH180	Brown	9	-
66PH15010	5	PH150	Red	10	-	66PH18010	6	PH180	Brown	10	-

Article No.	W.L.L. Tons	Type	Colour	Working length mtr	IMPA	Article No.	W.L.L. Tons	Type	Colour	Working length mtr	IMPA
66PH24001	8	PH240	Blue	1	-	66PH30001	10	PH300	Orange	1	-
66PH24002	8	PH240	Blue	2	-	66PH30002	10	PH300	Orange	2	-
66PH24003	8	PH240	Blue	3	-	66PH30003	10	PH300	Orange	3	-
66PH24004	8	PH240	Blue	4	-	66PH30004	10	PH300	Orange	4	-
66PH24005	8	PH240	Blue	5	-	66PH30005	10	PH300	Orange	5	-
66PH24006	8	PH240	Blue	6	-	66PH30006	10	PH300	Orange	6	-
66PH24007	8	PH240	Blue	7	-	66PH30007	10	PH300	Orange	7	-
66PH24008	8	PH240	Blue	8	-	66PH30008	10	PH300	Orange	8	-
66PH24009	8	PH240	Blue	9	-	66PH30009	10	PH300	Orange	9	-
66PH24010	8	PH240	Blue	10	-	66PH30010	10	PH300	Orange	10	-



LOAD CAPACITY



Never use damaged slings. Check always before starting lifting operation.

