


Lifting Equipment Weld-On Transport Rings

Estil Weld-On transport rings

The Weld-On transport rings are Grade-8 with a base forged from St 52-3 steel and the ring in 23NM. Welding must only be carried out by a qualified welder (according to EN287-1) in accordance with DIN 8563 resp. 15429. The surfaces to be welded must be clean, without oil, grease or paint. The transport rings are delivered without springs. The Weld-On Transport Ring is available in a range with a working load from 1.2t up to 15.5t. Safety factor 4x WLL, finish is painted white. Temperature range -40°C up to +200°C. Certification 2.1, 2.2, 3.1 and CE.



Article No.	Type	W.L.L. Tons	Diameter a mm	Inside Width b mm	Inside Length c mm	Base Length d mm	Base Height e mm	IMPA
66EAOV1	PAS 1	1.2	13	40	42	35	28	
66EAOV3	PAS 3	3.2	18	45	48	42	33	
66EAOV5	PAS 5	5.4	22	55	57	49	44	
66EAOV8	PAS 8	8.2	26	70	67	64	51	
66EAOV12	PAS 12	12.8	28	85	90	78	55	
66EAOV15	PAS 15	15.5	34	99	93	90	63	




Lifting Equipment Eye Bolts & Eye Nuts

Eye Nut DIN 582

Both Eye Nut and Eye Bolt are available as galvanized and black version. Quality C15

*= Not DIN standardized. Working Load is with one Eye Nut in one direction!

Article No. Galvanized	Article No. Black	Thread Metric	W.L.L. Tons	d2 mm	d3 mm	d4 mm	h mm	IMPA
0158206 *	01582ZW06 *	M6	0.14	20	36	20	36	-
0158208	01582ZW08	M8	0.14	20	36	20	36	69 34 01
0158210	01582ZW10	M10	0.23	25	45	25	45	69 34 02
0158212	01582ZW12	M12	0.34	30	54	30	53	69 34 03
0158214 *	01582ZW14 *	M14	0.49	30	54	30	53	-
0158216	01582ZW16	M16	0.7	35	63	35	62	69 34 04
0158218 *	01582ZW18 *	M18	0.7	35	63	35	62	-
0158220	01582ZW20	M20	1.2	40	72	40	71	69 34 05
0158222 *	01582ZW22 *	M22	1.2	40	72	40	71	-
0158224	01582ZW24	M24	1.8	50	90	50	90	69 34 06
0158227 *	01582ZW27 *	M27	2.5	65	108	60	109	-
0158230	01582ZW30	M30	3.6	65	108	60	109	69 34 07
0158233 *	01582ZW33 *	M33	3.6	65	108	60	109	-
0158236	01582ZW36	M36	5.1	75	126	70	128	69 34 08
0158239 *	01582ZW39 *	M39	7	85	144	80	147	-
0158242	01582ZW42	M42	7	85	144	80	147	69 34 09




Eye Bolt DIN 580

Both Eye Bolt and Eye Nut are available as galvanized and black version. Quality C15

*= Not DIN standardized. Working Load is with one Eye Bolt in one direction!

Article No. Galvanized	Article No. Black	Thread Metric	W.L.L. Tons	d2 mm	d3 mm	d4 mm	h mm	l mm	IMPA
0158006 *	01580ZW06 *	M6	0.14	20	36	20	36	13	-
0158008	01580ZW08	M8	0.14	20	36	20	36	13	69 22 01
0158010	01580ZW10	M10	0.23	25	45	25	45	17	69 22 02
0158012	01580ZW12	M12	0.34	30	54	30	53	20.5	69 22 03
0158014 *	01580ZW14 *	M14	0.49	30	54	30	53	20.5	-
0158016	01580ZW16	M16	0.7	35	63	35	62	27	69 22 04
0158018 *	01580ZW18 *	M18	0.7	35	63	35	62	27	-
0158020	01580ZW20	M20	1.2	40	72	40	71	30	69 22 05
0158022 *	01580ZW22 *	M22	1.2	40	72	40	71	30	-
0158024	01580ZW24	M24	1.8	50	90	50	90	36	69 22 06
0158027 *	01580ZW27 *	M27	2.5	65	108	60	109	45	-
0158030	01580ZW30	M30	3.6	65	108	60	109	45	69 22 07
0158033 *	01580ZW33 *	M33	3.6	65	108	60	109	45	-
0158036	01580ZW36	M36	5.1	75	126	70	128	54	69 22 08
0158039 *	01580ZW39 *	M39	7	85	144	80	147	63	-
0158042	01580ZW42	M42	7	85	144	80	147	63	-



Eye Bolts and Eye Nuts are also available in stainless steel