

## VYR TYCH FOX LED

The Interior lighting fixture FOX-LED IP40 is designed shops, corridors, changing rooms, toilets and technical rooms. Surface wall or ceiling mounted.  
The driver is type EP - electronic 220-240Vac, 50/60Hz and 220-240Vdc 0Hz.  
Complies with relevant EMC regulations. Meets photobiological safety according to EN 62471:2009. Suitable for persons with high sensitivity to UV radiation and blue spectrum part.

Housing white painted steel sheet RAL 9003.

Diffuser PC (Polycarbonate), UV stable plastic profile.

Screwless terminal block for easy mounting, maximum diameter of wires 2.5 mm<sup>2</sup>. The lighting fixture is prepared for loop-in (possibility of connection of two cables).

Standard rubber plug M20 for diameter cable 7-12 mm.

LED Light source 4000K, CRI +80, MacAdam3 (also available in 3000K).

Calculated life time LED modules:

L80B10 ta30 - 75.000 hours, L70B10 ta30 - 100.000 hours.

Tolerance of luminous flux and power input of the lighting fixture +/- 10%.

For ambient temperatures of +30°C. Factory warranty 5 years.

Options available as: EM - Non-maintained emergency lighting (1h, 3h).

MULTI - maintained emergency lighting (1h, 3h).

Dimmable ballast (DSI, DALI). 2.7K - 6.5K various color temperatures.


NANO lighting fixtures can be protected by special nano-layer (hydrophobic, oleophobic or antibacterial protection). CRI colour rendering >90.

# VYR TYCH




## FOX-LED

IP 40



Article No.	Description	Watt	Lumen	Dimensions in mm AxBxC	Mounting spacing in mm DxEx	Light color
83VT053140	FOX-LED 2900-4K IP40	19	2312	600x165x63	400x120	4000K
83VT053141	FOX-LED 3700-4K IP40	25	2827	600x165x63	400x120	4000K
83VT053146	FOX-LED 5300-4K IP40	37	4622	1103x165x63	730x120	4000K
83VT053142	FOX-LED 6350-4K IP40	44	5148	1103x165x63	730x120	4000K
83VT053143	FOX-LED 7400-4K IP40	52	5899	1103x165x63	730x120	4000K
83VT053144	FOX-LED 8400-4K IP40	53	6618	1590x165x63	1217x120	4000K
83VT053145	FOX-LED 5900-4K IP40	66	7406	1590x165x63	1217x120	4000K



Article No.	Description	Watt	Lumen	Dimensions in mm AxBxC	Mounting spacing in mm DxEx	Light color
83VT053130	FOX-LED 2900-3K IP40	19	2196	600x165x63	400x120	3000K
83VT053131	FOX-LED 3700-3K IP40	24	2686	600x165x63	400x120	3000K
83VT053136	FOX-LED 5300-3K IP40	37	4390	1103x165x63	730x120	3000K
83VT053132	FOX-LED 6350-3K IP40	44	4888	1103x165x63	730x120	3000K
83VT053133	FOX-LED 7400-3K IP40	51	5602	1103x165x63	730x120	3000K
83VT053134	FOX-LED 8400-3K IP40	53	6289	1590x165x63	1217x120	3000K
83VT053135	FOX-LED 5900-3K IP40	63	7040	1590x165x63	1217x120	3000K



A



B

Article No.	Description
83VT120000	Cable suspender 2 mtr Y 1 pc (A)
83VT051155	Ceiling cap with transparent cable 3x1.5mm <sup>2</sup> L= 2.5 mtr 1 pc (B)

