LED Indoor recessed ceiling panels

VYRTYCH HARRIER-LED IP20

Interior lighting fixture HARRIER-LED is designed for office buildings, schools and commercial areas


The driver is type EP - electronic 220-240Vac, 50/60Hz. Protection IP20. Complies with relevant EMC regulations. Meets photobiological safety according to EN

62471:2009. Suitable for persons with high sensitivity to UV radiation and blue spectrum part.

Spectrum part.
Housing white painted aluminium profile RAL 9003.
Diffuser MP - Microprismatic, UV stable material.
LED Light source 4000K, CRI +80, MacAdam5.
Connection: By means of free power supply cable from an external ballast to a terminal block (terminal block is not part of the packing).
Fastening: Mounting to false-ceiling modules 600 with visible systems of trunking rails, minimum height false-ceiling woid 200mm, direct fastening to a ceiling by means of support frame (119007), suspension by means of cable suspensions (119006), fastening to a hole in plasterboard by means of holders (119005), fastening to module 625 with visible systems of trunking rails by means of a frame for mounting M625 (119008).
Calculated life time LED modules:
L80B10 ta30 - 50.000 hours, L70B10 ta30 - 80.000 hours.
Tolerance of luminous flux and power input of the lighting fixture +/- 10%.
For ambient temperatures of+30°C. Factory warranty 5 years.

For ambient temperatures of+30°C. Factory warranty 5 years. Options available as:

MULTI - maintained emergency lighting (1h, 3h). Dimmable ballast (DSI, DALI). NANO lighting fixturers can be protected by special nano-layer (hydrophobic, oleophobic or antibacterial protection).



VYRTYCH

гmп



Article No.	Description	Watt	Lumen	Dimensions in mm AxBxC	Mounting hole in plaster- board in mm	Light color	Ta max (°C)
83VT119000	Harrier-LED 4950-4K-IP20	42	3875	596x596x12	578x578	4000K	40
83VT119001	Harrier-LED 4950-4K-IP20-DIM-DALI	42	3875	596x596x12	578x578	4000K	30
83VT119002	MultiHarrier-LED 4950-4K-IP20 1h	42	3875	596x596x12	578x578	4000K	30
83VT119003	MultiHarrier-LED 4950-4K-IP20 3h	42	3875	596x596x12	578x578	4000K	30
83VT119004	Harrier-LED 4950-4K-IP20-DIM-DSI/DALI	42	3875	596x596x12	578x578	4000K	30

Vyrtych accessories for HARRIER-LED

Article No.	Description
83VT119005 Set of plasterboard holders Harrier-LED	
83VT119007	Support frame for surface mounting Harrier-LED RAL9003
83VT119008	Frame for recessed installation M625 Harrier-LED
83VT119006	Set of cable suspenders Harrier-LED

