

## Zettex MMA FAST 2-C Adhesives

### Zettex MMA Ultra-Fast

Is a 2-component construction adhesive based on Methyl Methacrylate.  
Specially designed for gluing composite materials, metals and synthetics.

MMA Ultra-Fast has an excellent chemical resistance to acids and bases from 3 to 10 PH.

**Properties:**

Working time **1.5 minutes**. Filling properties up to 4.0mm Fully hardened within **6 minutes**.  
High chemical resistant.

**Applications:**

For gluing all metals, woods, vinyl, PVC, polycarbonates, carbon fibres, acrylates, styrene, gel coatings, polyester, urethane, fibre-reinforced plastics.

Available form: 50 ml duo cartridge.

Color: Black (other colors on request).

Surface: All surfaces must be free of grease and dust.

Tensile strength: 25 Mpa

Processing temperature: -50°C to +120°C.

Storage temperature between 12°C and 23°C.

The product may never be allowed to freeze.

Article No.	Description
68ZE461002	MMA Ultra-Fast Black 50 ml. cartridge without mixing nozzle
68ZE400108	MMA 2-C Cartridge nozzle and application gun
68ZE104007	MMA mixing nozzle



### Zettex MMA Fast

Is a 2-component construction adhesive based on Methyl Methacrylate.  
Specially designed for gluing composite materials, metals and synthetics.

MMA Ultra-Fast has an excellent chemical resistance to acids and bases from 3 to 10 PH.

**Properties:**

Working time **3 minutes**. Filling properties up to 4.0mm Fully hardened within **10 minutes**.  
High chemical resistant.

**Applications:**

For gluing all metals, woods, vinyl, PVC, polycarbonates, carbon fibres, acrylates, styrene, gel coatings, polyester, urethane, fibre-reinforced plastics.

Available form: 50 ml duo cartridge.

Color: Transparent Amber (other colors on request).

Surface: All surfaces must be free of grease and dust.

Tensile strength: 25 Mpa

Processing temperature: -50°C to +120°C.

Storage temperature between 12°C and 23°C.

The product may never be allowed to freeze.

Article No.	Description
68ZE461003	MMA Fast Transparent Amber 50 ml. cartridge without mixing nozzle
68ZE400108	MMA 2-C Cartridge nozzle and application gun
68ZE104007	MMA mixing nozzle



### Zettex MMA Standard

Is a 2-component construction adhesive based on Methyl Methacrylate.  
Specially designed for gluing composite materials, metals and synthetics.

MMA Ultra-Fast has an excellent chemical resistance to acids and bases from 3 to 10 PH.

**Properties:**

Working time **5 minutes**. Filling properties up to 4.0mm Fully hardened within **15 minutes**.  
High chemical resistant.

**Applications:**

For gluing all metals, woods, vinyl, PVC, polycarbonates, carbon fibres, acrylates, styrene, gel coatings, polyester, urethane, fibre-reinforced plastics.

Available form: 50 ml duo cartridge.

Color: Black (other colors on request).

Surface: All surfaces must be free of grease and dust.

Tensile strength: 25 Mpa

Processing temperature: -50°C to +120°C.

Storage temperature between 12°C and 23°C.

The product may never be allowed to freeze.

Article No.	Description
68ZE461001	MMA Standard Black 50 ml. cartridge without mixing nozzle
68ZE400108	MMA 2-C Cartridge nozzle and application gun
68ZE104007	MMA mixing nozzle

