

# Vyrtych watertight LED Linear Luminaires Extreme Temperatures

## Linear watertight luminaire SALUKA-LED

Metal dustproof lighting fixture SALUKA-LED with splash water resistance designed for workshops, garages, industrial and production areas with higher ambient temperature or warehouses and freezers with low temperatures.

Complies with relevant EMC regulations. Meets photobiological safety according to EN 62471:2009.

Suitable for persons with high sensitivity to UV radiation and blue spectrum part.

Screwless three-pole terminal block, maximum diameter of wires 2.5mm<sup>2</sup>.

Cable gland M20 suitable for cables with outer diameter 7-12mm.

Rated voltage 220-240Vac 50/60Hz, 220-240 VDC 0Hz, Electronic ballast.

Light color 4000K RA>80, CRI+80, MaxAdam3. (other colors available on request).

Designed service life L80B10 75.000 hours at Ta +40°C, L70B10 110.000 hours at Ta +40°C.

Diffuser; clear hardened safety glass or Opal mat safety glass.

Body of white painted sheet steel RAL 9003 (optional in Stainless Steel AISI 304 or AISI 316).

Protection category IP66, IK07 and class I.

Temperature operating range from -40°C to +70°C.

HACCP Suitable for food industry.

Multiple options on request available such as a dimmable ballast (DALI), emergency light, through wiring, Gesis connector etc.

Tolerance of luminous flux and power input of the lighting fixture +/- 10%.

Factory warranty 5 years.

# VYRTYCH




SALUKA-LED Optional Stainless Steel housing available in AISI 304 & AISI 316.  
(In case of stainless steel version its declared for ambient temperature decreased about 5-10°C.)

## SALUKA-LED-PLUS/FROST

IP 66



Article No.	Description	Wattage	Lumen output	LxWxH mm	Ta max (°C)	Diffuser
83VT053019	Saluka LED PLUS OP 2500-118-4K	17	2245	705x192x90	65	Matt
83VT053020	Saluka LED PLUS OP 5000-218-4K	33	4223	705x192x90	60	Matt
83VT053021	Saluka LED PLUS OP 2500-136-4K	17	2245	1305x192x90	65	Matt
83VT053022	Saluka LED PLUS OP 5000-236-4K	33	4223	1305x192x90	60	Matt
83VT053023	Saluka LED PLUS OP 3500-158-4K	25	3140	1605x192x90	60	Matt
83VT053024	Saluka LED PLUS OP 7500-258-4K	47	6625	1605x192x90	65	Matt
83VT053025	Saluka LED-PLUS OP 9600-258-4K	57	7876	1605x192x90	65	Matt
83VT053017	Saluka LED-PLUS70 OP 5000-236-4K	28	4270	1305x192x90	70	Matt
83VT053018	Saluka LED-PLUS70 OP 7500-258-4K	43	6669	1605x192x90	70	Matt
83VT054492	Saluka LED-FROST OP 5000-136-4K	28	4382	1305x192x90	-40	Matt
83VT054493	Saluka LED-FROST OP 10000-236-4K	56	8245	1305x192x90	-40	Matt
83VT054494	Saluka LED-FROST OP 4750-158-4K	26	4255	1605x192x90	-40	Matt
83VT054495	Saluka LED-FROST OP 7500-258-4K	43	6830	1605x192x90	-40	Matt
83VT054496	Saluka LED-FROST OP 12500-258-4K	69	10348	1605x192x90	-40	Matt



## Accessories SALUKA-LED

There are multiple accessories available for the SALUKA-LED to meet the customers needs.

Article No.	Description
83VT051139	Saluka set of ceiling brackets (2 pcs) (A)
83VT063754	Saluka set of adjustable bracket (2 pcs) (B)
83VT051145	Saluka pole bracket for Ø 50mm Stainless steel (1 pc) (C)
83VT064018	Saluka pole bracket for Ø 40mm Stainless steel (1 pc) (C)
83VT051147	Saluka wall arm bracket 60° stainless steel (1 pc) (D)

