

WENCON Repair Kit 8750

WENCON®



Wencon Steel Pipe/Plate & GRE Repair Kit

Repair Kit for Temporary Repairs & Daily Maintenance

Optimize your efficiency and safety onboard with swift and effective repair kits at sea. For dry - wet - high temperature applications. Major repair kit capable of carrying out most jobs on board the vessel, including both temporary repairs and maintenance that extend the service life of the equipment

- For pipes from DN6 up to DN250
- For (steel) plate repairs up to 2,5 m²
- For damage in an exhaust gas pipe

Article 108750 -> IMPA 81 23 41



Advantages

- Repairs done by crew
- Adheres to GRE & Steel
- Cable Pipe
- HYD return line
- Heating Coil
- MGO Pipe
- SW Strainer housing
- Sludge Pipe
- Fast curing time
- Adheres in wet conditions
- Cargo Pipe
- HT & LT Cooling Pipe
- IGG Pipe
- SW Pipe
- Scrubber Pipe (GRE)
- Steam Pipe to 7 bars

Class
Type
Approved
products
by DNV-GL,
ABS, BV,
RINA

Repair possibilities some examples

- Repair of a steel pipe **DN32**, length 300mm. Putty, Rapid and 3 layers of Reinforcement Tape (0,05x10m). **16 Pcs**
- Repair of a steel pipe **DN100**, length 300mm. Putty, Rapid and 3 layers of Reinforcement Tape (0,05x10m). **6 Pcs**
- Repair of a steel pipe **DN150**, length 300mm. Putty, Cream and 3 layers of Reinforcement Tape (0,05x10m). **2 Pcs**
- Repair of a steel pipe **DN250**, length 300mm. Putty, Cream and 3 layers of Reinforcement Tape (0,05x10m). **1 Pcs**
- Repair of steel pipe damage **DN32** with Ø5mm hole, length 105mm. Putty and Roll Pipe Tape 0,05x1,5m. **5 Pcs**
- Repair of steel pipe damage **DN100** with Ø5mm hole, length 105mm. Putty and Roll Pipe Tape 0,05x1,5m. **2 Pcs**
- Repair of steel pipe damage **DN150** with Ø5mm hole, length 105mm. Putty and Roll Pipe Tape 0,1x3,5m. **2 Pcs**
- Repair of steel pipe damage **DN200** with Ø5mm hole, length 105mm. Putty and Roll Pipe Tape 0,1x3,5m. **2 Pcs**
- Coating of FW HT Pipe with Hi-Temp coating
- Repair of GRE pipe **DN125**, length 250mm. UW Coating and 3 layers of Reinforcement Tape (0,05x10m). **1 Pcs**
- Repair of SW Strainer/filter housing with Cream and Coating. **1,2 m²**
- Repair of Pump Well with UW Cream and UW Coating (2 layers of 500 µ each). **0,44 m²**
- Repair of cracked paint under water or at oil-polluted surfaces. UW Coating (2 layers of 500 µ each). **0,44 m²**
- Putty 5000 µ (for repair of penetrated holes). **0,1 m²**
- Cream 2000 µ (for building up surface). **0,3 m²**
- Coating White (first layer of coating). **2 m²**
- Coating Blue (second layer of coating). **2 m²**



LOGISTICS
NO
DANGEROUS
GOOD
DOCUMENTS
NEEDED

BENELUX DISTRIBUTOR FOR WENCON

Repair Management Nederland B.V. – Jade 300 – 3316 LJ Dordrecht – Netherlands
Phone +31 (0)85 27 32 216 – email info@rmn.eu - www.rmn.eu - ww.wencon.nl