

Trade name : Revision date : Print date : Wencon Cleaner 13.09.2019 26-09-2019

Version (Revision) :

4.1.1 (4.1.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Wencon Cleaner (WENCON CLEANER) TETRACHLOROETHYLENE; CAS No.: 127-18-4; EC No.: 204-825-9; INDEX No.: 602-028-00-4; REACH registration No.: 01-2119475329-28 PR-number (Danish): 184269

1.2 Relevant identified uses of the substance or mixture and uses advised against Cleaning liquid

Relevant identified uses

In compliance with the conditions described in the annex to this safety data sheet. See section 16 for a comprehensive list of uses, for which an exposure scenarion is provided as an annex.

Sector of uses [SU]

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Process categories [PROC]

PROC 19 - Manual activities involving hand contact

PROC 21 - Low energy manipulation of substances bound in materials and/or articles

PROC 24 - High (mechanical) energy work-up of substances bound in/on materials and/or articles

Environmental release categories [ERC]

ERC 8c - Widespread use leading to inclusion into/onto article (indoor)

ERC 8f - Widespread use leading to inclusion into/onto article (outdoor)

ERC 10a - Widespread use of articles with low release (outdoor)

ERC 11a - Widespread use of articles with low release (indoor)

Article categories [AC]

AC 7 - Metal articles

Uses advised against

Do not use for private purposes (household).

Remark

The product is intended for professional use.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer) :	Wencon ApS
Street :	Jyllandsvej 15
Postal code/city :	DK-5400 BOGENSE
Telephone :	+45 6481 1010
Information contact :	wencon@wencon.com

1.4 Emergency telephone number

+44 870 600 62 66 (UK National Poisons Emergency Number)

European emergency number: 112. Danmark: (Giftlinjen +45 82 12 12 12), only for the purpose of informing medical personnel in cases of acute intoxications.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 2 ; H411 - Hazardous to the aquatic environment : Chronic 2 ; Toxic to aquatic life with long lasting effects.

Carc. 2 ; H351 - Carcinogenicity : Category 2 ; Suspected of causing cancer.

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.



Trade name : **Revision date :** Print date :

Wencon Cleaner 13.09.2019 26-09-2019

Version (Revision) :

4.1.1 (4.1.0)

Skin Sens. 1B; H317 - Skin sensitisation: Category 1B; May cause an allergic skin reaction. STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms



	Health hazard (GHS08) · Environment (GHS09) · Exclamation mark (GHS07)		
	Signal word		
	Warning		
	Hazard statements		
	H351	Suspected of causing cancer.	
	H315	Causes skin irritation.	
	H317	May cause an allergic skin reaction.	
	H319	Causes serious eye irritation.	
	H336	May cause drowsiness or dizziness.	
	H411	Toxic to aquatic life with long lasting effects.	
	Precautionary state	ements	
	P201	Obtain special instructions before use.	
	P202	Do not handle until all safety precautions have been read and understood.	
	P312	Call a POISON CENTER/doctor/ if you feel unwell.	
	P308+P313	IF exposed or concerned: Get medical advice/attention.	
	P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
	P405	Store locked up.	
2.3	Other hazards		
	N1		

None

SECTION 3: Composition/information on ingredients

3.1 Substances

Substance name : TETRACHLOROETHYLENE **INDEX No. :** 602-028-00-4 EC No.: 204-825-9 REACH No.: 01-2119475329-28 CAS No.: 127-18-4 **Purity :** ≥ 95 % [mass]

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately. If unconscious place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration.



Trade name : Revision date : Print date : Wencon Cleaner 13.09.2019 26-09-2019

Version (Revision) :

4.1.1 (4.1.0)

In case of skin contact

In case of skin reactions, consult a physician. Immediately remove any contaminated clothing, shoes or stockings. After contact with skin, wash immediately with plenty of water and soap. Do not use force or solvents to remove product incrustations from affected skin areas. Do not let product dry on skin.

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting. Keep at rest.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Effects

After eye contact Irritating to eyes.

In case of skin contact Irritating to skin. May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam Carbon dioxide (CO2) Extinguishing powder Water mist

Unsuitable extinguishing media

Extinguishing media which must not be used for safety reasons Water spray jet

5.2 Special hazards arising from the substance or mixture

Burning produces heavy smoke. Use suitable breathing apparatus.

Hazardous combustion products

Carbon monoxide

5.3 Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures For non-emergency personnel

Do not breathe gas/fumes/vapour/spray. Remove all sources of ignition. Provide adequate ventilation. Remove persons to safety. Use personal protection equipment. See protective measures under point 7 and 8.

For emergency responders

Do not breathe gas/fumes/vapour/spray. Use personal protection equipment. See protective measures under point 7 and 8.



Trade name : Revision date : Print date : Wencon Cleaner 13.09.2019 26-09-2019

Version (Revision) :

4.1.1 (4.1.0)

6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Ensure waste is collected and contained.

6.3 Methods and material for containment and cleaning up

For containment

Ensure waste is collected and contained. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation. Clean with detergents. Avoid solvent cleaners. Treat the recovered material as prescribed in the section on waste disposal.

6.4 Reference to other sections

None

SECTION 7: Handling and storage



7.1 Precautions for safe handling

Protective measures

It is recommended to design all work processes always so that the following is excluded: Inhalation of vapours or spray/mists Skin contact Eye contact Do not breathe gas/fumes/vapour/spray. When using do not eat, drink, smoke, sniff. Wear personal protection equipment (refer to section 8). Never use pressure to empty container. Use only in well-ventilated areas.

Measures to prevent fire

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Environmental precautions

Do not allow to enter into surface water or drains.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Only use containers specifically approved for the substance/product. Keep/Store only in original container. Keep container tightly closed.

Hints on joint storage

Keep away from: Oxidizing agent alkali Acid

Further information on storage conditions

Keep only in the original container in a cool, well-ventilated place. Store in a place accessible by authorized persons only. Handle and open container with care.

7.3 Specific end use(s)

Observe instructions for use. The regulations of the national employment safety and employment protection commission about the handling for polyurethane/epoxy have to be observed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

TETRACHLOROETHYLENE ; CAS No. : 127-18-4

Limit value type (country of origin) : Exposure Limit (8h) (DK) Parameter : TGG 8 uur



Trade name : **Revision date :** Print date :

Wencon Cleaner 13.09.2019 26-09-2019

Version (Revision) :

4.1.1 (4.1.0)

Limit value : Version : Parameter : Limit value : Version .

Limit value type (country of origin) : Exposure Limit (8h) (DK) TGG 8 uur 70 mg/m³

10 ppm

8.2 Exposure controls

Personal protection equipment



Eye/face protection

Suitable eye protection

Eye glasses with side protection

Skin protection

Hand protection

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Wear cotton undermitten if possible.

Suitable gloves type : Disposable gloves.

Suitable material : NBR (Nitrile rubber)

Required properties : liquid-tight.

Breakthrough time (maximum wearing time) : > 60 minutes

Thickness of the glove material : > 0.5 mm

Recommended glove articles : EN 374

Additional hand protection measures : Do not wear gloves near rotary machines and tools. Check leak tightness/impermeability prior to use. Wear cotton undermitten if possible. Use gloves only once. Take recovery periods for skin regeneration.

Remark : For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Observe the wear time limits as specified by the manufacturer. Breakthrough times and swelling properties of the material must be taken into consideration. In the case of wanting to use the gloves again, clean them before taking off and air them well. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Barrier creams are not substitutes for body protection.

Body protection

Remark : Body protection: not required.

Respiratory protection

exceeding exposure limit values

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Suitable respiratory protection apparatus

Combination filtering device (EN 14387) Filtering device (DIN EN 147) Full-/half-/quarter-face masks (DIN EN 136/140) Filtering Half-face mask (DIN EN 149) Particle filter device (DIN EN 143).

Filtering device (full mask or mouthpiece) with filter: A P Additional measures for respiratory protection

Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m3 (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m³ (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m³ (1.0 % by vol.) Half-face mask or quarter facepiece: maximum use concentration for substances with exposure limits: P1 filter: up to a max. of 4 times the exposure limit. P2 filter: up to a max. of 10 times the exposure limit. P3 filter: up to a max. of 30 times the expo. Full-face mask or mouthpiece with particulate filter: maximum use concentration for substances with exposure limits: P1 filter: up to a max. of 4 times the exposure limit. P2 filter: up to a max. of 15 times the exposure

limit. P3 filter: up to a max. of

Remark



Trade name : Revision date : Print date : Wencon Cleaner 13.09.2019 26-09-2019

Version (Revision) :

-22 ℃ 121 ℃ 4.1.1 (4.1.0)

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

General health and safety measures

When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Wash hands before breaks and after work. Immediately remove any contaminated clothing, shoes or stockings.

Occupational exposure controls

Product related measures to prevent exposure

Further information: see technical data sheet.

Instructional measures to prevent exposure

Further information: see technical data sheet.

Organisational measures to prevent exposure

Further information: see technical data sheet.

Technical measures to prevent exposure

Technical measures and the application of suitable work processes have priority over personal protection equipment. See section 7. No additional measures necessary.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Liquid	
Appearance	
Colour : transparent	
Safety relevant basis dat	a
Melting point/melting range :	
Initial boiling point and boiling range : (1013 hPa	
Decomposition temperature :	

Decomposition temperature :			No data available		
Flash point :		>	100	°C	DIN 53213-1
Ignition temperature :			No data available		
Evaporation rate :			0,12		
Flammable gases :			Not applicable.		
Flammable solids :			Not applicable.		
Oxidising properties.			No data available.		
Lower explosion limit :			No data available		
Upper explosion limit :			No data available		
Explosive properties :			No data available.		
Vapour pressure :	(50 °C)	<	1000	hPa	
Relative vapour density :			5,8		
Relative density :	(20 °C)		1,619	g/cm ³	DIN 53217
Water solubility :	(20 °C)		insoluble		
Partition coefficient n- octanol/water :			No data available		
pH :			No data available		
Viscosity :	(20 °C)		not applicable		
Cinematic viscosity :	(40 °C)		No data available		
Odour threshold :			No data available		
Other information					

9.2 Other information

None

SECTION 10: Stability and reactivity



Trade name : Revision date : Print date : Wencon Cleaner 13.09.2019 26-09-2019

4.1.1 (4.1.0)

10.1 Reactivity

No information available.

10.2 Chemical stability The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 Possibility of hazardous reactions No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

Ignition hazard.

10.5 Incompatible materials No information available.

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Acute effects

Acute oral toxicity	
Parameter :	LD50
Exposure route :	Oral
Species :	Rat
Effective dose :	2629 mg/kg
Parameter :	LD50 (TETRACHLOROETHYLENE ; CAS No. : 127-18-4)
Exposure route :	Oral
Species :	Rat
Effective dose :	2629 mg/kg
Acute inhalation toxicity	
Parameter :	LC50
Exposure route :	Inhalation
Species :	Rat
Effective dose :	34,2 g/kg
Parameter :	LC50 (TETRACHLOROETHYLENE; CAS No.: 127-18-4)
Exposure route :	Inhalation
Species :	Rat
Effective dose :	34,2 g/kg
Irritant and corrosive effe	-ts

Irritant and corrosive effects

Primary irritation to the skin Irritating to skin.

Irritating to eyes.

Sensitisation

Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed. Risk of serious damage to eyes. Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.

In case of skin contact

May cause an allergic skin reaction.

Practical experience/human evidence

Vapours may cause drowsiness and dizziness. Sensitised persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. May be absorbed through the skin. Ingestion causes nausea, weakness and central nervous system effects.



Trade name : Revision date : Print date : Wencon Cleaner 13.09.2019 26-09-2019

Version	(Revision)	•
10131011	(1001)	

4.1.1 (4.1.0)

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

Assessment/classification

Suspected of causing cancer. Carc. 2, H351

STOT-single exposure

STOT SE 3

May cause drowsiness or dizziness.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Aquatic toxicity

The substance/mixture does not fullfill the criteria of the acute aquatic toxicity according to Regulation (EC) No 1272/2008 [CLP], Annex I. Toxic to aquatic life. May cause long lasting harmful effects to aquatic life.

Sediment toxicity

Toxicity to soil macroorganisms Acute earthworm toxicity Chronical earthworm toxicity (reproduction) Long-term toxicity of organisms living in the sediment

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment No information available.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3). Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Do not allow to enter into surface water or drains.

Waste treatment options

Appropriate disposal / Product

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Dispose of waste according to applicable legislation.

Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of. Handle contaminated packages in the same way as the substance itself.


SECTION 14: Transport information



Trade name : Revision date : Print date : Wencon Cleaner 13.09.2019 26-09-2019

Version (Revision) :

4.1.1 (4.1.0)



SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation



Trade name : Revision date : Print date : Wencon Cleaner 13.09.2019 26-09-2019

Version (Revision) :

4.1.1 (4.1.0)

Authorisations and/or restrictions on use

Restrictions on use

Use restriction according to REACH annex XVII, no.: 3

National regulations

MAL code number according to Executive Order no. 301 from 13 May 1993 on the determination of code numbers (The Danish Working Environment Service)

MAL code number 5-3

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

16.1 Indication of changes

15. Restrictions on use

16.2 Abbreviations and acronyms

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road ASTM = American Society of Testing and Materials (US) CAS No = Chemical Abstracts Service Number (see ACS - American Chemical Society) DNEL = Derived No-Effect Level DT50 = Time for 50% loss; half-life

- EbC50 = Median effective concentration (biomass, e.g. of algae)
- EC50 = Median effective concentration

EINECS = European Inventory of Existing Commercial Chemical Substan

ELINCS = European List of Notified (New) Chemicals (see Tab 7, Background - Guide)

ErC50 = Median effective concentration (growth rate, e.g. of algae)

EWC = European Waste Catalogue

IATA = International Air Transport Association

IC50 = Concentration that produces 50% inhibition

IMDG = International Maritime Dangerous Goods Code

IMO = International Maritime Organization

LC50 = Concentration required to kill 50% of test organisms

LD50 = Dose required to kill 50% of test organisms

LEL = Lower Explosive Limit/Lower Explosion Limit

- LOAEL = Lowest observed adverse effect level
- MRL = Maximum Residue Limit
- NOAEL = No Observed Adverse Effect Level
- NOEC = No observed effect concentration
- NOEL = No Observable Effect Level
- OEL = Occupational Exposure Limits
- PBT = Persistent, Bioaccumulative or Toxic
- PNEC = Previsible Non Effect Concentration
- STEL = Short-Term Exposure Limit
- TWA = Time-Weighted Average

vPvB = Very Persistent and Very Bioacccumulative

16.3 Key literature references and sources for data

None

^{16.4} Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.4 Relevant H- and EUH-phrases (Number and full text)

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.



Trade name :	Wencon Cleaner		
Revision date :	13.09.2019	Version (Revision) :	4.1.1 (4.1.0)
Print date :	26-09-2019		

H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.

16.5 Training advice

The regulations of the national employment safety and employment protection commission about the handling for polyurethane/epoxy have to be observed.

16.6 Additional information

This safety data sheet contains more than one ES in an integrated form. Contents of the exposure scenarios have been included into sections 1.2, 8, 9, 12, 15 and 16 of this safety data sheet.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.